NOT MEASUREMENT SENSITIVE

MIL-B-41809/29B
14 May 1990
SUPERSEDING
MIL-B-41809/29A
31 December 1978

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, US ARMY RESERVE RECRUITER, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Red brass

DIMENSIONS:
HEIGHT (Overall): 1-7/8 inch (4.76 cm) (REF)
WIDTH (Overall): 2-1/4 inches (5.72 cm) (REF)
EDGE DEPTH (Overall): .100 inch (0.254 cm) (MIN)

WEIGHT: 480 grains ± 60 grains

FINISH: Oxidized, relieved, matte finish, polished highlights

NOTES:
1. Attaching device shall be prong and clutch type. Three prongs shall be located on a 1-3/8 inch (3.49 cm) diameter circle. Each prong shall be 120 degrees apart with one prong located on the vertical centerline at the top of the badge.
2. A full forcer shall be used to bring up the design and meet the weight requirements.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-0504)

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:38Z
Check the source to verify that this is the current version before use.