NOT MEASUREMENT SENSITIVE

MIL-B-41809/29C
21 September 1994
SUPERSEDING
MIL-B-41809/29B
14 May 1990

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, RECRUITER, ARMY RESERVE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Red Brass

FINISH: Oxidized Relieved Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 3.

DIMENSIONS:
HEIGHT (Overall): 1-7/8 inches (4.76 cm) (REF)
WIDTH (Overall): 2-1/4 inches (5.72 cm) (REF)
THICKNESS (Between Hat & Scroll): 0.035 inch ± 0.005 (0.89 cm ± 0.025 cm)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:38Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The attaching device shall be prong and clutch type. Three prongs shall be located on a 1-3/8 inch (3.49 cm) diameter circle. Each prong shall be 120 degrees apart with one prong located on the vertical center line at the top of the badge.

3. A full forcer shall be used to bring up the design.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0766)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:38Z
Check the source to verify that this is the current version before use.