NOT MEASUREMENT SENSITIVE


MIL-B-41809/30D
21 September 1994
SUPERSEDING
MIL-B-41809/30C
14 May 1990

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, DELIVERY SERVICES EMPLOYEES, U.S. POSTAL SERVICE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated (Red Brass Only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14. Recessed Areas shall not be Relieved.

DIMENSIONS:
HEIGHT (Overall): 2-9/16 inches (6.51 cm) (REF)
WIDTH (Overall): 2-1/8 inches (5.4.60 cm) (REF)
EDGE DEPTH (Overall): 0.140 inch (0.355 cm) (REF)
EDGE THICKNESS: 0.035 inch + 0.010 inch - 0 (0.088 cm + 0.025 cm - 0)

WEIGHT (Assembled): 1.37 ounce ± 0.05 ounce

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:38Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnish hub or die.

2. A full forcer shall be used to bring up the design and meet the weight requirement. If the attaching device is to be soft soldered to the badge, the forcer shall contain three platforms for soldering purposes. The platforms shall be located at the top, center and bottom of the area covered by the base of the attaching device.

3. Attaching device shall be a pin with top opening catch. The joint shall be located on the vertical center line 1/8 inch ± 1/32 inch (0.32 cm ± 0.08 cm) below the top of the badge. The attaching device shall be soft soldered or secured to the badge by two hollow rivets 9/64 inch (0.36 cm) in length and 0.085 inch (0.215 cm) in diameter. The rivets shall be hard soldered on the vertical center line of the badge and be a minimum of 1-1/8 inch (2.86 cm) apart.

4. The numbers (2345) are for illustration only. The numbers shall be stamped in as specified in the procurement document. The numbers shall be Gothic condensed, 5/16 inch (0.79 cm) in height.

Custodian:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0766)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:38Z
Check the source to verify that this is the current version before use.