NOT MEASUREMENT SENSITIVE


MIL-B-41809/35D
21 September 1994
SUPERSEDING
MIL-B-41809/35C
30 April 1992

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, NURSE CADET PROGRAM, ARMY ROTC

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Gilding Metal

FINISH:
MALTESE CROSS: Hard Enameled, Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.
CADUCEUS: Hard Enameled, Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7.

DIMENSIONS:
MALTESE CROSS:
HEIGHT (Overall): 53/64 inch (2.10 cm) (REF)
WIDTH (Overall): 53/64 inch (2.10 cm) (REF)
THICKNESS (At Thickness Point): 0.065 inch ± 0.005 inch (0.165 cm ± 0.012 cm)
CADUCEUS:
HEIGHT (Overall): 1/2 inch (1.27 cm) (REF)
WIDTH (Overall): 39/64 inch (1.55 cm) (REF)
THICKNESS (Letter "N"): 0.075 inch ± 0.005 inch (0.190 cm ± 0.012 cm)

ASSEMBLED THICKNESS (Letter "N"): 0.140 inch ± 0.010 inch (0.355 cm ± 0.025 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:39Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The color shall conform to the applicable TIOH color chips listed below or the standard sample:

COLOR	CHIP NO.
Black	26
White	28

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

4. The caduceus shall be located as shown and shall be secured to the cross by one hollow rivet.

5. The attaching device shall be prong and clutch type. Two prongs shall be located on the vertical center line, equidistant from each end and 9/16 inch (9.43 cm) apart.

6. At the option of the manufacturer for commercial sale only, insignia may be manufactured using 22 karat gold plate with nickel underplating. The Maltese Cross shall have a mirror-like polished finish which shall match TIOH Metal Finish Chip Number 9. The Caduceus shall have a matte finish which shall match TIOH Metal Finish Chip Number 10.

Custodian:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0766)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:39Z
Check the source to verify that this is the current version before use.