NOT MEASUREMENT SENSITIVE

MIL-B-41809/37A
14 May 1990
SUPERSEDING
MIL-B-41809/37
12 April 1985

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, US ARMY NATIONAL GUARD MASTER RECRUITER

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Red brass

DIMENSIONS:
DIAMETER: 2-1/4 inch (5.72 cm) (REF)
EDGE DEPTH (On ribbon): .100 inch ± .010 inch (0.254 cm) ± (0.025 cm)
THICKNESS (Minimum): .030 inch (0.076 cm) (See note 1)
WEIGHT (Maximum): 1.0 ounce (See note 2)

FINISH: Gold plated, matte finish, wreath, rope, lettering and numbering area polished, minuteman highlighted

NOTES:
1. A full forcer shall be used to bring up the design. The minimum thickness of .030 inch (0.076 cm) shall be present in all areas.
2. The weight shall be taken with all three prongs and clutches mounted.
3. Attaching device shall be prong and clutch type. Three prongs shall be located on a 1-3/4 inch (4.45 cm) diameter circle. Each prong shall be spaced 120 degrees apart with one prong located on the vertical centerline 1/4 inch ± 1/64 inch (0.64 cm) ± (0.04 cm) below the top of the badge.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:40Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Review activity:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0511)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:40Z
Check the source to verify that this is the current version before use.