NOT MEASUREMENT SENSITIVE

MIL-B-41809/38B
21 September 1994
SUPERSEDING
MIL-B-41809/38A
14 May 1990

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, CHIEF OF PARTY, NATIONAL OCEANOGRAPHIC ATMOSPHERIC ADMINISTRATION

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Red Brass

DASH NO.
-1: Regular size
-2: Miniature size

DIMENSIONS:

LENGTH (Each Side):
-1: 1-5/16 inches (3.33 cm) (REF)
-2: 21/32 inch (1.67 cm) (REF)

THICKNESS (At Thickest Point):
-1: 0.155 inch ± 0.010 inch (0.393 cm ± 0.025 cm)
-2: 0.100 inch ± 0.010 inch (0.254 cm ± 0.025 cm)

FINISH: Gold Plated, Matte Finish, Burnished Highlights.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-21T19:40Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The attaching device shall be prong and clutch type. For Dash No. 1, three prongs shall be located 3/16 inch (0.48 cm) in from each tip. For Dash No. 2, two prongs shall be located on the vertical center line, equidistant from each end and 3/8 inch (0.95 cm) apart.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0766)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:40Z
Check the source to verify that this is the current version before use.