NOT MEASUREMENT SENSITIVE

MIL-B-41809/39A
14 May 1990
SUPERSEDING
MIL-B-41809/39
14 June 1988

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, DEFENSE MAPPING AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.

MATERIAL: Gilding metal

DIMENSIONS:
DIAMETER: 2-3/8 inches (6.03 cm) (REF)
THICKNESS (At thickest point): .060 inch ± .010 inch (0.152 cm) ± (0.025 cm)

FINISH: Hard enameled, oxidized, relieved, matte finish, highlights polished

NOTES:
1. Attaching device shall be prong and clutch type. Three prongs shall be located on a 1-3/4 inch (4.45 cm) diameter circle. Each prong shall be 120 degrees apart with one prong on the vertical center at the top of the badge.
2. Blue enamel shall conform to TIOH color chip No. 20 or the standard sample.
3. A full forcer shall be used to bring up the details of the design.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-0513)

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:41Z
Check the source to verify that this is the current version before use.