NOT MEASUREMENT SENSITIVE

MIL-B-41809/39C
21 September 1994
SUPERSEDING
MIL-B-41809/39B
30 March 1993

MILITARY SPECIFICATION SHEET

BADGE, IDENTIFICATION, DEFENSE MAPPING AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-B-41809.



MATERIAL: Gilding Metal

DIMENSIONS:
DIAMETER: 2-3/8 inches (6.03 cm) (REF)
THICKNESS (At Thickest Point): 0.060 inch ± 0.010 inch (0.152 cm ± 0.025 cm)

FINISH: Hard Enameled, Oxidized, Relieved, Matte Finish, Polished Highlights

NOTES:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. A full forcer shall be used to bring up the details of the design.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:40Z
Check the source to verify that this is the current version before use.

3. Enamel color shall be Blue as indicated. The enamel color shall conform to the TIOH chip number 20 or the standard sample.

4. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

5. Attaching device shall be three prongs with clutches. Three prongs shall be located on a 1-1/8 inch (2.86 cm) diameter circle. Each prong shall be 120 degrees apart with one prong on the vertical center at the top of the badge. The prongs shall be 7/16 inch ± 1/64 inch (1.11 cm ± 0.04 cm) long and 0.045 inch ± 0.002 inch (1.14 cm ± 0.05 cm) in diameter. The prongs shall be soldered or fused to the reverse of the badge.

Custodians:
Army – IH

User Activities:
Other – CT

Preparing Activity:
Army – IH

(Project No. 8455-0766)

Source: https://assist.dla.mil - Downloaded: 2026-10-21T19:40Z
Check the source to verify that this is the current version before use.