INCH-POUND
MIL-M-28787/109B(SH)
AMENDMENT 1
18 December 1991

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

DRIVER, INTERFACE, DIGITAL, KEY CODE MDL

This amendment forms a part of Military Specification MIL-M-28787/109B(EC), dated 4 February 1983, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

TABLE I, Test condition F1, Droop parameter, Min columns: Delete "0.0" (four places) and substitute "-0.3" (four places).

TABLE I, Test condition F1, Droop parameter, Max columns: Delete "0.3" (four places) and substitute "0.0" (four places).

PAGE 6

TABLE I, Test condition L, Test type column: Delete "X" and substitute "S".

PAGE 7

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through W shall be performed in any order with the following exceptions. Test conditions A, L, N, P, Q, and V are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, L, N, P, Q, or V are part of a sequence of tests, the order of testing shall be as follows: A, L, N, P, Q, and V where applicable, followed by the remaining tests in the sequence."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:03Z
Check the source to verify that this is the current version before use.

4.5.1: Delete the third sentence and substitute the following:

"When electrical testing is called for at the end of each temperature stabilization period, test conditions B through K, M, S through U, and W shall be performed in the order specified in 4.4.2 using the initial limits for applicable operating temperature."

4.5.3: Delete and substitute the following:

"4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests B through K, M, S through U, and W shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements in table I. Following the return of the module to 25 ± 5°C, electrical tests B through K, M, S through U, and W shall be performed in the order specified in 4.4.2 using the 25 ± 5°C ambient end-of-life requirements in table I."

PAGE 17

TABLE IV, Test condition F1, Droop parameter, Min column: Delete "0.0" (one place) and substitute "-0.3" (one place).

TABLE IV, Test condition F1, Droop parameter, Max column: Delete "0.3" (one place) and substitute "0.0" (one place).

Preparing activity:
Navy - SH

(Project 5963-N789)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:03Z
Check the source to verify that this is the current version before use.