MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

MULTIPLEXER, DIGITAL, KEY CODE KHQ

This amendment forms a part of Military Specification MIL-M-28787/72B(EC), dated 29 April 1983, and is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test condition K1-K13, Min column: Delete "-0.10" (four places) and substitute "0" (four places).

TABLE I, Test condition K14-K27, Min column: Delete "-0.20" (four places) and substitute "0" (four places).

TABLE I, Test condition M1-M11, Min column: Delete "10" (four places) and substitute "5" (four places).

TABLE I, Test condition M12-M22, Min column: Delete "20" (four places) and substitute "10" (four places).

PAGES 41 and 42

TABLE XII, Test conditions K1 through K13, Min column: Delete "-0.10" and substitute "0".

TABLE XII, Test conditions K14 through K27, Min column: Delete "-0.20" (two places) and substitute "0" (two places).

PAGES 45 and 46

TABLE XIV, Test condition M1 through M11, Min column: Delete "10" and substitute "5".

TABLE XIV, Test conditions M12 through M22, Min column: Delete "20" (three places) and substitute "10" (three places).

Agent:
DLA-ES

Preparing activity:
Navy - EC

(Project 5963-N642)

FSC 5963

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:53Z
Check the source to verify that this is the current version before use.