INCH-POUND

MIL-M-28787/72B (SH)
AMENDMENT 2
24 August 1990
SUPERSEDING
AMENDMENT 1
15 February 1985

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

MULTIPLEXER, DIGITAL, KEY CODE KHQ

This amendment forms a part of Military Specification MIL-M-28787/72B (SH), dated 29 April 1983, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

* TABLE I, Test conditions D1-D11, Test type column: Delete "X" and substitute "S".

* TABLE I, Test conditions H1-H27, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions K1-K13, Min columns: Delete "-0.10" (four places) and substitute "0" (four places).

TABLE I, Test conditions K14-K27, Min columns: Delete "-0.20" (four places) and substitute "0" (four places).

TABLE I, Test conditions M1-M11, Min columns: Delete "10" (four places) and substitute "5" (four places).

TABLE I, Test conditions M12-M22, Min columns: Delete "20" (four places) and substitute "10" (four places).

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-20T15:53Z
Check the source to verify that this is the current version before use.

PAGE 8

* 4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through V shall be performed in any order with the following exceptions. Test conditions A, B, C, D, and H are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, or H are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, and H where applicable, followed by the remaining tests in the sequence."

4.5.1, fifth line: Delete "D through U" and substitute "E through G and J through U".

4.5.3, third line: Delete "D through U" and substitute "E through G and J through U".

4.5.3, sixth line: Delete "D through V" and substitute "E through G and J through U".

PAGES 41 AND 42

TABLE XII, Test conditions K1 through K13, Min column: Delete "-0.10" and substitute "0".

TABLE XII, Test conditions K14 through K27, Min column: Delete "-0.20" (two places) and substitute "0" (two places).

PAGES 45 AND 46

TABLE XIV, Test conditions M1 through M11, Min column: Delete "10" and substitute "5".

TABLE XIV, Test conditions M12 through M22, Min column: Delete "20" (three places) and substitute "10" (three places).

Source: https://assist.dla.mil -- Downloaded: 202610-20T15:53Z
Check the source to verify that this is the currentversion before use.

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH

(Project 5963-N772)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:53Z
Check the source to verify that this is the current version before use.