INCH-POUND

MIL-M-28787/75A
AMENDMENT 1
31 December 1992

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

GATE, NAND, DIGITAL, KEY CODE LHP

This amendment forms a part of Military Specification MIL-M-28787/75A(EC), dated 17 August 1983, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions D1-D4, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions E1-E4, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions F1-F32, Test type column: Delete "X" and substitute "S".

PAGE 6

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through V shall be performed in any order with the following exceptions. Test conditions A, B, C, D, E, and F are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, E, or F are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, E, and F where applicable, followed by the remaining tests in the sequence."

4.5.1, line 5: Delete "D through U" and substitute "G through U".

4.5.3, line 3: Delete "D through U" and substitute "G through U".

4.5.3, line 6: Delete "D through V" and substitute "G through V".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:55Z
Check the source to verify that this is the current version before use.

PAGE 62

FIGURE 22, Item C01 box: Delete "C01" and substitute "C06".

FIGURE 22, NOTE 3, first line: Delete "C01" and substitute "C06".

FIGURE 22, NOTE 3, second line. Delete "Frequency = 120 Hz." and substitute "Frequency = 1 KHz."

Custodians:
Army - ER
Navy - SH
Air Force - 85

Preparing activity:
Navy - NW

(Project 5963-0117)

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:55Z
Check the source to verify that this is the current version before use.