INCH-POUND

MIL-M-28787/80A(SH)
AMENDMENT 1
24 August 1990

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

MEMORY, RANDOM ACCESS, DIGITAL, KEY CODE BYF

This amendment forms a part of Military Specification MIL-M-28787/80A (SH), dated 12 October 1983, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions F and G, Test type column: Delete "X" and substitute "S".

PAGE 6

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through X shall be performed in any order with the following exceptions. Test conditions A, B, C1-C4, F, and G are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C1-C4, F or G are part of a sequence of tests, the order of testing shall be as follows: A, B, C1-C4, F, and G where applicable, followed by the remaining tests in the sequence."

4.5.1: Delete and substitute the following:

"4.5.1 Operating temperature tests. The operating temperature tests shall be conducted in accordance with MIL-M-28787. Before starting these tests, test conditions A through X in table I shall be performed in the order specified in 4.4.2 using the initial limits at 25°C ambient. When electrical testing is called for at the end of each temperature stabilization period, test conditions C5-C22, D, E, and H through V shall be performed in the order specified in 4.4.2 using the initial limits for the applicable operating temperature. At all other times during the operating temperature tests, the module shall be operated in the test circuit shown on figure 6."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:58Z
Check the source to verify that this is the current version before use.

4.5.2: Delete and substitute the following:

"4.5.2 Vibration tests. The vibration tests shall be conducted in accordance with MIL-M-28787. During the vibration tests, the module shall be operated in the test circuit shown on figure 10. Following the vibration tests, the electrical tests in table I which are marked with an "X" in the test type column and test condition V, shall be performed using the initial limits at 25 ± 5°C ambient."

4.5.3: Delete and substitute the following:

"4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 6. Following the life test and while still at the maximum class temperature, electrical tests C5-C22, D, E, and H through V shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements in table I. Following the return of the module to 25 ± 5°C, electrical tests C5-C22, D, E, and H through V shall be performed in the order specified in 4.4.2 using the 25 ± 5°C ambient end-of-life requirements in table I."

PAGE 83

FIGURE 38, NOTE 3, Second line: Delete "Frequency = 120 Hz" and substitute "Frequency = 1 KHz"

Preparing activity:
Navy - SH

(Project 5963-N751)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:58Z
Check the source to verify that this is the current version before use.