INCH-POUND

MIL-M-28787/82A
AMENDMENT 2
31 December 1992
SUPERSEDING
AMENDMENT 1
14 November 1983

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

INVERTER, DIGITAL, KEY CODE RBG

This amendment forms a part of Military Specification MIL-M-28787/82A(EC), dated 18 January 1980, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 6

*TABLE II, Test conditions D1-D18, Test type column: Delete "X" and substitute "S".

*TABLE II, Test conditions E1-E18, Test type column: Delete "X" and substitute "S".

*TABLE II, Test conditions F1-F18, Test type column: Delete "X" and substitute "S".

PAGE 8

4.3: Delete and substitute the following:

"4.3 Test equipment. Test equipment specified on figures and in tables with a type designator shall be as specified in MIL-STD-1665. Other equipment and components shall be as specified on the figures. All resistors shall be metal film and all capacitors shall be ceramic unless otherwise specified."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:59Z
Check the source to verify that this is the current version before use.

PAGE 9

*4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through Y shall be performed in any order with the following exceptions. Test conditions A, B, C, D, E, and F are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, E, or F are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, E, and F where applicable, followed by the remaining tests in the sequence."

*4.5.1, line 5: Delete "D through X" and substitute "G through X".

*4.5.3, line 3: Delete "D through X" and substitute "G through X".

*4.5.3, line 5: Delete "D through Y" and substitute "G through Y".

PAGE 15

FIGURE 5, ITEM R06 box: Delete "100 V ± 10%" and substitute "100 Vdc ± 10%."

PAGE 17

FIGURE 6: Delete and substitute new figure 6 as printed on page 4 of this amendment.

PAGE 26

FIGURE 10: Delete and substitute new figure 10 as printed on page 5 of this amendment.

PAGE 29

FIGURE 11: Delete and substitute new figure 11 as printed on page 6 of this amendment.

PAGE 78

FIGURE 25, ITEM C01 box: Delete "C01" and substitute "C06".

FIGURE 25, NOTE 3, first line: Delete "C01" and substitute "C06".

FIGURE 25, NOTE 3, second line: Delete "Frequency = 120 Hz." and substitute "Frequency = 1 KHz."

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:59Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.


Custodians:
Army - ER
Navy - SH
Air Force - 85

Preparing activity:
Navy - NW

(Project 5963-0121)

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES


Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:59Z
Check the source to verify that this is the current version before use.



NOTE: R1 = 249Ω ± 1%, 1/4W.

FIGURE 6. V_{OUT} (low-loaded) test circuit for table IV.


Source: https://assist.dla.mil -- Downloaded: 20260-20T15:59Z
Check the source to verify that this is the current version before use.



NOTE: R1 = 590Ω ± 1%, 1/4W.

FIGURE 10. Input clamp diode voltage test circuit for table VIII.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:59Z
Check the source to verify that this is the current version before use.



NOTE: R1 = R2 = 51Ω ± 5%, 1/2W.

FIGURE 11. Static output voltage (low-level and high-level) test circuit for tables IX and X.

Source: https://assist.dla.mil -- Downloaded: 202610-20T15:59Z
Check the source to verify that this is the current version before use.