INCH-POUND

MIL-M-28787/83B
AMENDMENT 1
31 December 1992

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

GATE, NAND, DIGITAL, KEY CODE RBF

This amendment forms a part of Military Specification MIL-M-28787/83B(EC), dated 31 January 1983, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 4

TABLE I, Test conditions D1-D12, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions E1-E12, Test type column: Delete "X" and substitute "S".

TABLE I, Test conditions F1-F24, Test type column: Delete "X" and substitute "S".

PAGE 6

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through Y shall be performed in any order with the following exceptions. Test conditions A, B, C, D, E, and F are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, E, or F are part of a sequence of tests, the order of testing shall be as follows: A, B, C, D, E, and F where applicable, followed by the remaining tests in the sequence."

4.5.1, line 5: Delete "D through X" and substitute "G through X"

4.5.3, line 3: Delete "D through X" and substitute "G through X".

4.5.3, line 6: Delete "D through Y" and substitute "G through Y".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:00Z
Check the source to verify that this is the current version before use.

PAGE 62

FIGURE 25, Item C01 box. Delete "C01" and substitute "C06".

FIGURE 25, NOTE 3, first line: Delete "(C01)" and substitute "(C06)".

FIGURE 25, NOTE 3, second line: Delete "Frequency = 120 Hz." and substitute "Frequency = 1 KHz."

Custodians:
Army - ER
Navy - SH
Air Force - 85

Preparing activity:
Navy - NW

(Project 5963-0122)

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:00Z
Check the source to verify that this is the current version before use.