MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC
REGULATOR, POSITIVE, POWER, KEY CODE ARM

This amendment forms a part of Military Specification MIL-M-28787/87B(EC), dated 27 August 1980, and is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

* TABLE I: Delete and substitute page 4 of table II as printed on page 2 of this amendment.

PAGE 15

* TABLE V, footnote 1/: Delete "±15 mV" and substitute "±23 mV".

PAGE 21

* TABLE VIII: Delete and substitute table VIII as printed on page 3 of this amendment.

PAGE 31

FIGURE 15, NOTE 1: Delete "$t_{THL} = t_{TLH} = 10 \pm 5$ ns" and substitute "$t_{THL} = t_{TLH} = 1.0 \pm 0.1$ µs".

NOTE: The margin of this amendment is marked with asterisks to indicate where a change from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaulate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5963-N403)

FSC 5963

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:02Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements.

Test condition	Parameter	Ref test table	Test type 1/-3/	Acceptance requirements 25°±5°C ambient temperature				Operating temperature 0° to 60°C				Unit
				Initial		End-of-life		Initial		End-of-life		
				Min	Max	Min	Max	Min	Max	Min	Max	
A1-A8	Isolation	II	X	10	∞	1.0	∞	10	∞	1.0	∞	MΩ
B1-B4	Continuity	III	X	0.0	1.0	0.0	1.0	0.0	1.0	0.0	1.0	Ω
B5	Continuity	III	S	0.0	1.0	0.0	1.0	0.0	1.0	0.0	1.0	Ω
C1	Output voltage program	IV	X	4.95	5.05	4.90	5.10	4.90	5.10	4.85	5.15	Vdc
C2	Output voltage program	IV	X	14.70	15.30	14.55	15.45	14.55	15.45	14.40	15.60	Vdc
D1	DC input voltage regulation	V	X	4.95	5.05	4.90	5.10	4.90	5.10	4.85	5.15	Vdc
D2-D7	DC input voltage regulation	V	X	← ±23 mV variance max from D1 →								
D8	DC input voltage regulation	V	X	14.70	15.30	14.55	15.45	14.55	15.45	14.40	15.60	Vdc
D9-D12	DC input voltage regulation	V	X	← ±35 mV variance max from D8 →								
E1, E2	Output short circuit current	VI	X	96.3	117.7	93.6	120.3	85.0	128.8	82.5	131.3	mAdc
E3, E4	Output short circuit current	VI	X	183.6	224.4	178.5	229.5	160.0	243.8	150.0	253.8	mAdc
E5, E6	Output short circuit current	VI	X	276.4	337.6	268.6	345.4	230.0	370.0	210.0	390.0	mAdc
E7, E8	Output short circuit current	VI	X	363.6	444.4	353.5	454.5	320.0	480.0	300.0	500.0	mAdc
F1, F2	Input modulation regulation	VII	X	0.1	750.0	0.1	750.0	0.1	750.0	0.1	750.0	μVrms
F3, F4	Input modulation regulation	VII	X	0.01	2.25	0.01	2.25	0.01	2.25	0.01	2.25	mVrms
G1	Output load regulation	VIII	X	4.95	5.05	4.90	5.10	4.90	5.10	4.85	5.15	Vdc
G2-G5	Output load regulation	VIII	X	← ±10 mV variance max from G1 →								
G6	Output load regulation	VIII	X	← ±15 mV variance max from G1 →								
G7	Output load regulation	VIII	X	← ±20 mV variance max from G1 →								
G8	Output load regulation	VIII	X	14.70	15.30	14.55	15.45	14.55	15.45	14.60	15.40	Vdc

See footnotes at end of table.

Source: https://assist.dla.mil/ -- Downloaded: 2026-10-20T16:02Z
Check the source to verify that this is the current version before use.

TABLE VIII. Output load regulation test.

Test condition	Parameter	PO1 (Vdc)	S1 position	Connect		Calculation 1/	Initial limits 25°±5°C ambient		Unit	Test figure
				A to pin	B to pin		Min	Max		
G1	Output load regulation	10 ±0.1	1	Open	13	Initial V_{OUT}	4.95	5.05	Vdc	10
G2			2	Open		G1 - G2	-10	10	mVdc	
G3			3	Open		G1 - G3	-10	10		
G4			4	6		G1 - G4	-10	10		
G5			5	6		G1 - G5	-10	10		
G6			6	7		G1 - G6	-15	15		
G7			7	6, 7		G1 - G7	-20	20		
G8		20 ±0.2	8	Open	14	Initial V_{OUT}	14.70	15.30	Vdc	
G9			9	Open		G8 - G9	-30	30	mVdc	
G10			10	Open		G8 - G10	-30	30		
G11			11	6		G8 - G11	-30	30		
G12			2	6		G8 - G12	-30	30		
G13			3	7		G8 - G13	-30	30		
G14			4	6, 7		G8 - G14	-30	30		

1/ For test conditions G2 - G7 and G9 - G14 the indicated subtraction shall meet the given limits.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:02Z
Check the source to verify that this is the current version before use.