MILITARY SPECIFICATION

CONNECTORS, ELECTRICAL, DEEP SUBMERGENCE, SUBMARINE

This supplement forms a part of Military Specification MIL-C-24217A(SH), dated 5 September 1984.

SPECIFICATION SHEETS

MIL-C-24217/1(SH) - Receptacle Assembly (Welded Type).

MIL-C-24217/2(SH) - Receptacle Assembly (Flanged - Welded Type).

MIL-C-24217/3(SH) - Receptacle Assembly (In line Type).

MIL-C-24217/4(SH) - Receptacle Assembly (Mid-Flanged Bolted Type).

MIL-C-24217/5(SH) - Receptacle Assembly (End-Flanged Bolted Type).

MIL-C-24217/6(SH) - Receptacle Assembly (Locknut Flange Type).

MIL-C-24217/7(SH) - Plug Assemblies, Straight.

MIL-C-24217/8(SH) - Plug Assemblies, Right Angle.

MIL-C-24217/9(SH) - Pressure Proof Plug Cap Assembly.

MIL-C-24217/10(SH) - Pressure Proof Receptacle Cap Assembly.

MIL-C-24217/11(SH) - Receptacle Assembly (Union Type).

MIL-C-24217/12(SH) - Receptacle Assembly (Mid-Flange, Bolted, Union Type).

MIL-C-24217/13(SH) - Receptacle Assembly (Mid-Flange, Locknut, Union Type).

MIL-C-24217/14(SH) - Union Plug Assemblies, Straight.

MIL-C-24217/15(SH) - Union Plug Assemblies, Right Angle.

Preparing activity:
Navy - SH

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 20261O-19T20:02Z
Check the source to verify that this is the current version before use.