INCH-POUND
MIL-DTL-24211/1B
25 November 1998
SUPERSEDING
MIL-G-24211/1A
28 February 1969

DETAIL SPECIFICATION SHEET

GASKETS, WAVEGUIDE FLANGE (COVER)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the gaskets described herein shall consist of this document and the latest issue of Specification MIL-DTL-24211.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Reference data: See table I.

Part number: Consists of the basic number of this specification sheet and a dash number from table I.

Example:

M24211/1	-001
Basic document number	Dash number from table I

TABLE I. Reference data.

Part number M24211/1-	Used with flanges 1/	Part number M24211/1-	Used with flanges 1/
001	UG-51/U and UG-138/U	004	UG-1530/U
002	UG-39/U and UG-135/U	005	UG-595/U and UG-597/U
003	UG-419/U and UG-1665/U	006	UG-599/U

1/ Flanges are in accordance with MIL-F-3922.

AMSC N/A FSC 5985
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:58Z
Check the source to verify that this is the current version before use.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:58Z
Check the source to verify that this is the current version before use.

FIGURE 1. Dimensions and configurations.

Part number M24211/1-	A	B	C	D	E ± .01 (.25)	G ± .01 (.25)
001	1.122 ± .004 (28.50 ± .10)	.497 ± .004 (12.62 ± .10)	.561 ± .002 (14.25 ± .05)	.2485 ± .0020 (6.31 ± .05)	1.532 (38.91)	.907 (23.04)
002	.900 ± .003 (22.86 ± .08)	.400 ± .003 (10.16 ± .08)	.4500 ± .0015 (11.43 ± .04)	.2000 ± .0015 (5.08 ± .04)	1.300 (33.02)	.800 (20.32)
003	.622 ± .002 (15.80 ± .05)	.311 ± .002 (7.90 ± .05)	.311 ± .001 (7.90 ± .03)	.1555 ± .0010 (3.95 ± .03)	1.006 (25.55)	.695 (17.65)
004	.340 ± .002 (8.64 ± .05)	.170 ± .002 (4.32 ± .05)	.170 ± .001 (4.32 ± .03)	.085 ± .001 (2.16 ±.03)	.580 (14.73)	.410 (10.41)
005	.420 ± .002 (10.67 ± .05)	.170 ± .002 (4.32 ± .05)	.210 ±.001 (5.33 ± .03)	.085 ± .001 (2.16 ± .03)	.660 (16.76)	.410 (10.41)
006	.2800 ± .0015 (7.11 ± .04)	.1400 ± .0015 (3.56 ± .04)	.1400 ± .0008 (3.56 ± .02)	.0700 ± .0008 (1.78 ± .02)	.474 (12.04)	.334 (8.48)

Part number M24211/1-	K	L ± .01 (.25)	M ± .02 (.51)	N	S ± .003 (.08)	U ± .02 (.51)	V ±. .005 (.13)	W ± .005 (.13)	X Min
001	.676 ± .002 (17.17 ± .05)	.94 (23.88)	1.88 (47.75)	.737 ± .002 (18.72 ± .05)	.169 (4.29)	1.25 (31.75)	.026 (.66)	.110 (2.79)	.064 (1.63)
002	.610 ± .002 (15.49 ± .05)	.82 (20.83)	1.63 (41.40)	.640 ± .002 (16.26 ± .05)	.169 (4.29)	1.06 (26.92)	.026 (.66)	.110 (2.79)	.050 (1.27)
003	.497 ± .002 (12.62 ± .05)	.66 (16.76)	1.31 (33.27)	.478 ± .002 (12.14 ± .05)	.144 (3.66)	.88 (22.35)	.026 (.66)	.110 (2.79)	.040 (1.02)
004	.320 ± .001 (8.13 ± .03)	.44 (11.18)	.88 (22.35)	.335 ± .001 (8.51 ± .03)	.116 (2.95)	.57 (14.48)	.020 (.51)	.100 (2.54)	.040 (1.02)
005	.320 ± .001 (8.13 ± .03)	.44 (11.18)	.88 (22.35)	.335 ± .001 (8.51 ± .03)	.116 (2.95)	.57 (14.48)	.020 (.51)	.100 (2.54)	.040 (1.02)
006	.250 ± .001 (6.35 ± .03)	.38 (9.65)	.75 (19.05)	.265 ± .001 (6.73 ± .03)	.116 (2.95)	.47 (11.94)	.015 (.38)	.080 (2.03)	.040 (1.02)

NOTES:

1. Dimensions are in inches.
2. Millimeters are in parentheses.
3. Metric equivalents (to the nearest 0.01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
4. Except where noted, break sharp edges and remove burrs.
5. Flange is symmetrical about both centerlines.
6. Electrical contact area to be at least 0.003 (0.08) higher than adjacent metal surface.
7. Surface roughness of mating surfaces other than the raised electrical contact area shall be no greater than 63 micro inches in accordance with ANSI B46.1.
8. Any raised embossed pattern for electrical contact is acceptable provided R.F. leakage requirement is met.

FIGURE 1. Continued.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Preparing activity:
DLA - CC

(Project 5985-1095-01)

Review activities:
Army - MI, AR
Navy - OS, CG, SH
Air Force - 11, 17, 19

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:58Z
Check the source to verify that this is the current version before use.