INCH-POUND
MIL-P-24212C(SH)
AMENDMENT 2
21 April 1998

MILITARY SPECIFICATION

PRESSURE TRANSDUCER EQUIPMENT (ELECTRICAL)

This amendment forms a part of MIL-P-24212C(SH) dated 24 May 1991, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1, SPECIFICATIONS, FEDERAL, delete:

"PPP-F-320 - Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes."

2.1.1, SPECIFICATIONS, MILITARY, delete:

"MIL-E-17555 - Electronic and Electrical Equipment, Accessories, and Provisioned Items (Repair Parts): Packaging of.
MIL-L-19140 - Lumber and Plywood, Fire Retardant Treated."

2.1.1, STANDARDS, MILITARY, delete:

"MIL-STD-275 - Printed Wiring for Electronic Equipment.
MIL-STD-454 - Standard General Requirements for Electronic Equipment."

PAGE 5

3.4.1, delete and substitute:

"3.4.1 Materials. Transducer materials shall be in accordance with the prohibited and galvanic corrosion material requirements of MIL-E-917 and MIL-P-24423."

PAGE 9

3.5.10.1, add to end of paragraph: "contacted by measurement fluid except for OX application (see 1.2.1.2) where all surfaces of the detector shall be cleaned."

AMSC N/A FSC 6685
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:58Z
Check the source to verify that this is the current version before use.

PAGE 10

3.5.10.2(a), change to read “Detector for OX service shall be clean gas calibrated, cleaned and pressure connection capped (sealed for shipment).

3.5.12.1, line 2: Delete “microbrazed” and substitute “nicrobrazed.” line 3: Delete “microbrazing” and substitute “nicrobrazing.”

3.5.12.2, delete and substitute:

“3.5.12.2 Oxygen applications. Joints shall be welded for all pressure ranges. MIL-STD-278, class P-1 shall apply.”

PAGE 11

3.5.15, add:

“(i) National Stock Number (NSN).”

PAGE 12

3.6.5, delete “MIL-STD-275 and.”

PAGE 14

3.7.19, delete and substitute:

“3.7.19 Electromagnetic interference emission and susceptibility (EMI). The pressure transducers shall meet the following requirements of MIL-STD-461, table II, except as modified below:

(a) Requirement CS114 shall be met as specified except as follows:

(1) At frequencies between 2 MHz and 30 MHz, the full output of the generator (source impedance of 50 ohms, and an output capability of 12.25 volts rms, or 3 watts, when connected to a 50-ohm load) shall be applied to all power and signal leads of the test sample.
(2) The “calibrating resistor”, or 50-ohm load, as specified in MIL-STD-462, shall not be connected during the test.
(3) The test sample output shall not vary more than 1.0 percent of transducer span.

(b) Requirement of RS103 shall be met as specified except as follows:

(1) Between the frequencies of 14 kHz and 18 GHz, the electric field strength test level shall be 10 V/M.

(c) Requirements CE101 and CE102 shall be met as specified except as follows:

(1) The emission signal shall be measured only on ac power leads of the test sample.”

3.8: Delete paragraph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:58Z
Check the source to verify that this is the current version before use.

PAGE 17

TABLE IV, delete and substitute:

"TABLE IV. Quality conformance inspection.

Inspection	Requirement	Inspection
General examination	3.4	4.6
Output	3.4.4	4.8.20
Static error band and repeatability	3.7.1 and 3.7.2	4.8.1
Overpressure	3.7.12	4.8.12
Insulation resistance	3.7.15	4.8.16"

4.5, second and third lines: Delete ", from each lot offered for delivery."

PAGE 18

4.5, fourth sentence: Delete "based on test results."

PAGE 22

4.8.11.4.1, line 1: Delete "Requirements of transducer." and substitute "Requirements during temperature cycling."

4.8.11.5, line 2: Delete "4.8.11.3" and substitute "4.8.2."

PAGE 23

TABLE VI, delete and substitute:

"TABLE VI. Amplitudes of vibration.

Frequency range Hz	Table amplitude (inches)	
	Exploratory	Variable frequency
5 to 20	0.010 ± 0.002	0.030 ± 0.006
21 to 50	0.004 ± 0.001	0.020 ± 0.004
51 to 100	0.0015 ± 0.0003	0.010 ± 0.002
101 to 175	0.0005 ± 0.0001	0.0015 ± 0.0003"

PAGES 24 & 25

5. through 5.1(a)(2), delete and substitute:

"5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity with the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:58Z
Check the source to verify that this is the current version before use.

PAGE 25

6.2(g): Delete line.

Preparing activity:
Navy - SH
(Project 6685-0037)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T19:58Z
Check the source to verify that this is the current version before use.