MILITARY SPECIFICATION SHEET

RECEPTACLE ASSEMBLY (FLANGED - WELDED TYPE)

This specification sheet is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the receptacle assembly described herein shall consist of this document and the latest issue of MIL-C-24217.




FIGURE 1. Configuration of receptacle assembly.


FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:03Z
Check the source to verify that this is the current version before use.

TABLE I. Parts description.

RECEPTACLE ASSY NO.	RECEPTACLE SHELL NO.	NO. OF CONTACTS & PIN SIZE	A O-RING	B O-RING	C PROTECTIVE CAP
M24217/2-001	M24217/2-025	3 NO. 16	AS-568A-114	AS-568A-117	M24217/1-040
M24217/2-002	M24217/2-026	5 NO. 16	AS-568A-117	AS-568A-121	M24217/1-041
M24217/2-003	M24217/2-027	9 NO. 16	AS-568A-121	AS-568A-125	M24217/1-042
M24217/2-004	M24217/2-028	14 NO. 16	AS-568A-125	AS-568A-129	M24217/1-043
M24217/2-005	M24217/2-029	24 NO. 16	AS-568A-131	AS-568A-134	M24217/1-044
M24217/2-006	M24217/2-030	37 NO. 16	AS-568A-137	AS-568A-140	M24217/1-045
M24217/2-007	M24217/2-031	48 NO. 16	AS-568A-144	AS-568A-148	M24217/1-046
M24217/2-008	M24217/2-032	3 NO. 12	AS-568A-121	AS-568A-125	M24217/1-047
M24217/2-009	M24217/2-033	5 NO. 12	AS-568A-125	AS-568A-129	M24217/1-048
M24217/2-010	M24217/2-034	9 NO. 12	AS-568A-131	AS-568A-134	M24217/1-049
M24217/2-011	M24217/2-035	3 NO. 8	AS-568A-125	AS-568A-129	M24217/1-048
M24217/2-012	M24217/2-036	3 NO. 4	AS-568A-131	AS-568A-134	M24217/1-048
M24217/2-013	M24217/2-037	3 NO. 12 3 NO. 8	AS-568A-131	AS-568A-134	M24217/1-049
M24217/2-014	M24217/2-038	2 NO 0 4 NO. 12	AS-568A-137	AS-568A-140	M24217/1-050

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:03Z
Check the source to verify that this is the current version before use.



NOTE: For all other dimensions, requirements, parts and contact arrangements see MIL-C-24217/1.

FIGURE 2. Receptacle shell (mid-flanged - welded type).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:03Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions.

PART NO.	NO. OF CONTACTS & PIN SIZE	P ±.005	R	S
M24217/2-025	3 NO. 16	1.500	.370 / .380	.915 / .925
M24217/2-026	5 NO. 16	1.875	.370 / .380	1.040 / 1.050
M24217/2-027	9 NO. 16	2.062	.370 / .380	1.165 / 1.175
M24217/2-028	14 NO. 16	2.500	.370 / .380	1.290 / 1.300
M24217/2-029	24 NO. 16	2.875	.370 / .380	1.415 / 1.425
M24217/2-030	37 NO. 16	3.375	.370 / .380	1.415 / 1.425
M24217/2-031	48 NO. 16	4.250 / 4.245	.545 / .535	1.543 / 1.553
M24217/2-032	3 NO. 12	2.062	.870 / .880	1.510 / 1.520
M24217/2-033	5 NO. 12	2.375	.870 / .880	1.687 / 1.697
M24217/2-034	9 NO. 12	2.750	.870 / .880	1.687 / 1.697
M24217/2-035	3 NO. 8	2.375	.870 / .880	1.687 / 1.697
M24217/2-036	3 NO. 4	2.750	.870 / .880	1.687 / 1.697
M24217/2-037	3 NO. 12 3 NO. 8	2.750	.870 / .880	1.687 / 1.697
M24217/2-038	2 NO. 0 4 NO. 12	3.375	.870 / .880	1.625 / 1.635

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:03Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. Dimensions and configuration: See figures and tables.
2. Contact gasket (face seal) may be molded and secured to the receptacle web with adhesive or poured in place using a clear RTV silicone, General Electric RTV 615 with General Electric SS-4120 primer or equal. Either method shall prevent the entrance of water under the seal.
3. Receptacle assemblies shall be packaged as shown in the assembly view (protective cover tightened to compress the O-ring), except that the interior O-ring (O-ring "A") shall be separately packaged.

Preparing activity:
Navy - SH
(Project 5935-N246-2)

☆U S GOVERNMENT PRINTING OFFICE 1984 — 708-040/A4454

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:03Z
Check the source to verify that this is the current version before use.