MIL-C-51234(MU)
AMENDMENT 3
19 December 1974
SUPERSEDING
AMENDMENT 2
16 August 1968

MILITARY SPECIFICATION

COUPLING ASSEMBLY, QUICK DISCONNECT,

PLAIN AND SELF-SEALING

This amendment forms a part of Military Specification MIL-C-51234(MU), 18 June 1965.

Page 1

2.1: Delete "MIL-P-25732 - Packing, Preformed, Petroleum Hydraulic Fluid Resistant, 275 Deg. F."

2.1: Under "DRAWINGS," delete and substitute the following:

Delete	Substitute
'C150-1-1"	"D150-1-1"
"C150-1-2"	"D150-1-2"
"C150-1-3"	"D150-1-3"
"C150-1-4"	"D150-1-4"
"C150-1-5"	"D150-1-5"
"C150-1-6"	"D150-1-6",
"C150-1-7"	"D150-1-7"
"C150-1-8"	"D150-1-8"
"C150-1-9"	"D150-1-9"
"C150-1-10"	"D150-1-10"
"C150-1-12"	"D150-1-12"

Page 3

3.3: Delete "3.4.1" and substitute "3.3.1."

3.3.1: Under new "3.3.1" in Table I in Drawing column delete all "C" size drawings and substitute "D".

3.5: Delete in its entirety.

3.6.2: Delete "275° ± 5°F" and substitute "160° ± 5°F."

FSC 4730

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.

Page 4

3.8: Delete "165° ± 5°" and substitute "160° ± 5°F."

Page 5

4.2.2: Delete "3.5."

Page 7

6.1: Delete in its entirety and substitute the following:

"6.1 Intended use. These couplings are intended for use in high pressure air, hydraulics or hydrocarbon fuel applications."

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4730-A450

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.