MILITARY SPECIFICATION

FUZE, M814, TACTICAL AND TELEMETRY PARTS, ASSEMBLING, LOADING AND PACKING FOR

This Amendment forms a part of Military Specification MIL-F-48173(PA), dated 15 May 1973, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 3, Paragraph 3.3.2 - Delete in its entirety and substitute the following:

"3.3.2 Sustainer Motor Ignition.-Prior to sustainer motor ignition time, the sustainer ignition lead shall be electrically connected to fuze ground. The sustainer ignition lead shall be electrically transferred from fuze ground to fuze B plus (B+) for a period of 0.200 ± 0.100 seconds at the following times, measured from zero time:

a. 0.265 to 0.404 seconds at -45°F.
b. 0.265 to 0.355 seconds at +70°F.
c. 0.240 to 0.355 seconds at +140°F.

After the 0.200 ± 0.100 second transfer period, the sustainer ignition lead shall be returned to fuze ground."

Page 3, Paragraph 3.3.3 - Delete in its entirety and substitute the following:

"3.3.3 Fuze Arming.-When subjected to a longitudinal acceleration of 33 g's, the fuze shall arm at the following times, measured from zero time:

a. 1.29 to 2.05 seconds at -45°F.
b. 1.45 to 2.05 seconds at +70°F.
c. 1.26 to 2.05 seconds at +140°F.

The fuze shall not arm when subjected to a longitudinal acceleration below 5 g's and shall arm when subjected to a longitudinal acceleration of 10 g's."

FSC: 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

Page 30, Paragraph 4.3.3.1.1 - In the requirement column for Code No. 34016, change "3.3.7" to "3.3.5".

Page 56, Paragraph 4.4.19, seventh line - Change "10,000 ohms" to "5 ohms".

Page 56, Paragraph 4.4.19, sixth line from bottom - Change "33 g's" to "33 g's maximum".

Page 56, Paragraph 4.4.19 - Delete the last four lines on the page and substitute the following:

"Armed fuzes scheduled for functioning by the Impact Switch (IMP) shall first have the detonator resistance measured, across the PIG leads, and then shall satisfy the requirements of 3.3.5. The value of detonator resistance shall be recorded and reported with the test results for all fuzes subjected to the Impact Switch test. Fuzes scheduled for functioning by Self-Destruct (SD) shall satisfy the requirements of 3.3.6. A fuze shall be classed defective if it fails to satisfy any of the applicable requirements."

NOTE: When measuring detonator resistance, use a meter with current limited to 20 microamperes maximum. The test should be conducted in an explosive protected area with explosive handling safety procedures in effect.

Page 57, Paragraph 4.4.20, fourteenth line - Change "33 g's" to "33 g's maximum".

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1340-A480

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.