INCH-POUND
MIL-PRF-55514/9C
w/AMENDMENT 1
17 September 2018
SUPERSEDING
MIL-PRF-55514/9C
6 September 2013

PERFORMANCE SPECIFICATION SHEET

CAPACITOR, FIXED, METALLIZED PLASTIC DIELECTRIC, DC, IN NONMETAL CASES, ESTABLISHED RELIABILITY, STYLES CFR13 AND CFR14

This specification sheet is approved for use by all Departments and and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-55514.




FIGURE 1. Style CFR13 capacitors.




FIGURE 2. Style CFR14 capacitors.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.

Inches	mm
.002	0.05
.005	0.13
.032	0.81
.156	3.96
.312	7.93
.360	9.14
1.750	44.45

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics.

Style CFR13 (characteristic L)														
Part or identifying number (PIN) 1/	Capacitance nominal	DC rated voltage (at +105°C)	Capacitance tolerance available	D	L ±.062(1.57)	M 2/	ESR Ohms 20 - 100 kHz Max	Maximum ripple current (AMPS RMS) 20-100 kHz case temperature						
								+25°C	+35°C	+45°C	+55°C	+65°C	+75°C	+85°C
CFR13ALB105--	1.0	100	J, K, M	.469 (11.91) ±.062 (1.57)	.750 (19.05)	.032 (0.81)	.015	9.2	8.5	7.8	7.0	6.0	4.9	4.5
CFR13ALB205--	2.0	100	J, K, M	.534 (13.56) ±.062 (1.57)	.938 (23.81)	.032 (0.81)	.012	10.8	10.0	9.1	8.2	7.0	5.8	5.3
CFR13ALB305--	3.0	100	J, K, M	.624 (15.85) ±.093 (2.36)	.938 (23.81)	.040 (1.02)	.011	12.1	11.2	10.3	9.2	8.0	6.5	5.9
CFR13ALB505--	5.0	100	J, K, M	.640 (16.26) ±.093 (2.36)	1.250 (31.75)	.040 (1.02)	.010	13.8	12.7	11.6	10.4	9.0	7.4	6.7
CFR13ALB106--	10.0	100	J, K, M	.805 (20.45) ±.093 (2.36)	1.500 (38.10)	.040 (1.02)	.009	15.0	15.0	14.2	12.7	11.0	9.0	8.2
CFR13ALB206--	20.0	100	J, K, M	.875 (22.23) ±.125 (3.18)	2.250 (57.15)	.040 (1.02)	.008	15.0	15.0	15.0	15.0	13.6	11.1	10.0
CFR13ALB306--	30.0	100	J, K, M	1.075 (27.31) ±.125 (3.18)	2.250 (57.15)	.040 (1.02)	.006	15.0	15.0	15.0	15.0	15.0	12.4	11.4
CFR13ALC105--	1.0	200	J, K, M	.450 (11.43) ±.062 (1.57)	1.250 (31.75)	.032 (0.81)	.020	7.3	7.3	7.3	7.3	7.2	5.9	5.4
CFR13ALC205--	2.0	200	J, K, M	.605 (15.37) ±.093 (2.36)	1.250 (31.75)	.032 (0.81)	.015	12.0	12.0	11.3	10.1	8.7	7.1	6.5
CFR13ALC305--	3.0	200	J, K, M	.654 (16.61) ±.093 (2.36)	1.500 (38.10)	.040 (1.02)	.013	15.0	13.8	12.6	11.3	9.8	8.0	7.3
CFR13ALC505--	5.0	200	J, K, M	.769 (19.53) ±.093 (2.36)	1.750 (44.45)	.040 (1.02)	.011	15.0	15.0	14.7	13.1	11.4	9.3	8.5
CFR13ALC106--	10.0	200	J, K, M	.905 (22.99) ±.125 (3.18)	2.250 (57.15)	.040 (1.02)	.009	15.0	15.0	15.0	15.0	13.8	11.3	10.3
CFR13ALC206--	20.0	200	J, K, M	1.315 (33.40) ±.125 (3.18)	2.250 (57.15)	.040 (1.02)	.006	15.0	15.0	15.0	15.0	15.0	14.1	12.8
CFR13ALE105--	1.0	400	J, K, M	.620 (15.75) ±.093 (2.36)	1.500 (38.10)	.040 (1.02)	.019	9.5	9.5	9.5	9.5	9.5	7.8	7.1
CFR13ALE205--	2.0	400	J, K, M	.802 (20.37) ±.093 (2.36)	1.750 (44.45)	.040 (1.02)	.015	15.0	15.0	15.0	13.4	11.6	9.5	8.7
CFR13ALE305--	3.0	400	J, K, M	.961 (24.41) ±.125 (3.18)	1.750 (44.45)	.040 (1.02)	.012	15.0	15.0	15.0	15.0	13.1	10.7	9.8
CFR13ALE505--	5.0	400	J, K, M	1.067 (27.10) ±.125 (3.18)	2.250 (57.15)	.040 (1.02)	.010	15.0	15.0	15.0	15.0	15.0	12.5	11.4
CFR13ALE106--	10.0	400	J, K, M	1.543 (39.19) ±.125 (3.18)	2.250 (57.15)	.040 (1.02)	.006	15.0	15.0	15.0	15.0	15.0	15.0	14.1

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics - Continued.

Style CFR14 (characteristic L)														
PIN 1/	Capacitance nominal	DC rated voltage (at +105°C)	Capacitance tolerance available	D	L ±.078(1.98)	L_1 ±0.62(1.57)	ESR Ohms 20 - 100 kHz Max	Maximum ripple current (AMPS RMS) 20-100 kHz case temperature						
								+25°C	+35°C	+45°C	+55°C	+65°C	+75°C	+85°C
CFR14LLB105--	1.0	100	J, K, M	.469 (11.91) ±.062 (1.57)	.922(23.42)	1.640(41.66)	.015	10.3	9.5	8.7	7.8	6.7	5.5	5.0
CFR14LLB205--	2.0	100	J, K, M	.534 (13.56) ±.062 (1.57)	1.110(28.19)	1.828(46.43)	.012	12.0	11.0	10.0	8.9	7.8	6.3	5.8
CFR14LLB305--	3.0	100	J, K, M	.624 (15.85) ±.093 (2.36)	1.110(28.19)	1.828(46.43)	.011	13.3	12.3	11.2	10.0	8.7	7.1	6.5
CFR14LLB505--	5.0	100	J, K, M	.640 (16.26) ±.093 (2.36)	1.422(36.12)	2.140(54.36)	.010	14.8	13.7	12.5	11.2	9.7	7.9	7.2
CFR14LLB106--	10.0	100	J, K, M	.805 (20.45) ±.093 (2.36)	1.672(42.47)	2.390(60.71)	.009	17.8	16.5	15.0	13.5	11.7	9.5	8.7
CFR14LLB206--	20.0	100	J, K, M	.875 (22.23) ±.125 (3.18)	2.422(61.52)	3.140(79.76)	.008	21.6	20.0	18.3	16.4	14.2	11.6	10.6
CFR14LLB306--	30.0	100	J, K, M	1.075 (27.31) ±.125 (3.18)	2.422(61.52)	3.140(79.76)	.006	24.3	22.5	20.5	18.4	15.9	13.0	11.9
CFR14LLC105--	1.0	200	J, K, M	.450 (11.43) ±.062 (1.57)	1.422(36.12)	2.140(54.36)	.020	7.3	7.3	7.3	7.3	7.2	6.4	5.8
CFR14LLC205--	2.0	200	J, K, M	.605 (15.37) ±.093 (2.36)	1.422(36.12)	2.140(54.36)	.015	14.3	13.3	12.1	10.8	8.7	7.7	7.0
CFR14LLC305--	3.0	200	J, K, M	.654 (16.61) ±.093 (2.36)	1.672(42.47)	2.390(60.71)	.013	15.9	14.7	13.5	12.0	9.8	8.5	7.8
CFR14LLC505--	5.0	200	J, K, M	.769 (19.53) ±.093 (2.36)	1.922(48.82)	2.640(67.06)	.011	18.3	17.0	15.5	13.9	11.4	9.8	8.9
CFR14LLC106--	10.0	200	J, K, M	.905 (22.99) ±.125 (3.18)	2.422(61.52)	3.140(79.76)	.009	22.4	20.7	18.9	16.9	13.8	12.0	10.9
CFR14LLC206--	20.0	200	J, K, M	1.315 (33.40) ±.125 (3.18)	2.422(61.52)	3.140(79.76)	.006	27.4	25.4	23.2	20.7	15.0	14.7	13.4
CFR14LLE105--	1.0	400	J, K, M	.620 (15.75) ±.093 (2.36)	1.672(42.47)	2.390(60.71)	.019	9.5	9.5	9.5	9.5	9.5	8.3	7.5
CFR14LLE205--	2.0	400	J, K, M	.802 (20.37) ±.093 (2.36)	1.922(48.82)	2.640(67.06)	.015	15.0	15.0	15.0	14.2	11.6	10.0	9.1
CFR14LLE305--	3.0	400	J, K, M	.961 (24.41) ±.125 (3.18)	1.922(48.82)	2.640(67.06)	.012	21.1	19.5	17.8	15.9	13.1	11.3	10.3
CFR14LLE505--	5.0	400	J, K, M	1.067 (27.10) ±.125 (3.18)	2.422(61.52)	3.140(79.76)	.010	24.4	22.6	20.6	18.5	15.0	13.1	11.9
CFR14LLE106--	10.0	400	J, K, M	1.543 (39.19) ±.125 (3.18)	2.422(61.52)	3.140(79.76)	.006	30.0	27.8	25.4	22.7	15.0	16.1	14.7

1/ The complete PIN will include additional symbols to indicate capacitance tolerance and product level (C, M, P, R, and S).
2/ Comparable AWG sizes are No. 20 AWG (.032 inch (0.81 mm)) and No. 18 AWG (.040 inch (1.02 mm)).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1, figure 2, and table I.

Case: Non-hermetic.

Dielectric: Normally polypropylene, metallized.

Capacitance (cap.) value: See table I.

Capacitance tolerance: See table I.

Rated voltage: See table I.

Operating temperature range: -55°C to +105°C for dc operation.

Product level: Non-established reliability - C; Established reliability - M, P, R or S.

Preconditioning: Not applicable.

Burn-in: In accordance with MIL-PRF-55514, except for the following conditions:

DC burn-in voltage shall be 140 percent of the dc rated voltage applied for 48 hours, minimum at +105°C, +4°C, -0°C.

AC burn-in: Not applicable.

Dielectric withstanding voltage (DWV): In accordance with MIL-PRF-55514, except the charge time shall be 2 minutes, maximum at 200 percent of the rated dc voltage.

Insulation resistance: In accordance with MIL-PRF-55514, except the test voltage shall be 100 V dc.

Dissipation factor (DF): Not more than 0.1 percent when measured in accordance with MIL-PRF-55514.

Low temperature conditioning and capacitance change with temperature: In accordance with MIL-PRF-55514.

Resistance to soldering heat: In accordance with MIL-STD-202-210, condition B.

ΔCap: $\pm$ 0.25 percent, maximum.

Life (at +105°C): In accordance with MIL-PRF-55514.

Accelerated condition: 140 percent of the +105°C rated voltage.

Rated condition: 100 percent of the +105°C rated voltage.

IR (at +25°C, terminal to terminal): Not less than 50.0 percent of the initial requirement.

ΔCap (at +25°C): 1.0 percent, maximum.

DF (at +25°C) after life: 0.12 percent, maximum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.

AC conditioning: In accordance with MIL-PRF-55514. The following details shall apply:

Qualification: Rated ac ripple current at +85°C and 40 kHz.

Group B: Rated ac ripple current at +85°C and 40 kHz on test samples in accordance with table II herein at 12-month intervals.

TABLE II. AC conditioning test samples.

DC rated voltage (volts)	Sample size	Capacitance range for selection of sample 1/ (µF)
100	24	1.0 to 30.0
200	24	1.0 to 20.0
400	24	1.0 to 10.0

1/ Each test sample shall contain at least one capacitor of the highest and lowest capacitance value of each voltage group manufactured during the 12-month period.

Amendment notations: The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-55514, this document references MIL-STD-202-210.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-2018-034)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:29Z
Check the source to verify that this is the current version before use.