MILITARY SPECIFICATION

PROJECTILE, 105MM SMOKE, WP,

M60E1; FILLING ASSEMBLY

This amendment forms a part of Military Specification MIL-P-51338(MU), 20 May 1969.

Page 1

2.1: Add the following, after MIL-STD-105:

"MIL-STD-1168 - Lot Numbering of Ammunition."

Page 3

4.2.1: Delete in its entirety and substitute the following:

"4.2.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168. Contained in any one interfix number of filled projectiles, no more than one interfix number from one manufacturer of the following components is permitted:

(a) Projectile bodies
(b) Burster casings".

Page 5

4.2.4.2: Delete in its entirety and substitute the following:

"4.2.4.2 Leakage. The projectile shall be placed in an oven in a vertical, filling-end-down position and maintained at $160^{\circ} \pm 5^{\circ}$ F temperature for the required time. Alternate method: The projectile shall be placed in an oven at 207° to 212° F in a vertical, filling-end-down position for the required time. When testing at 207° to 212° F the temperature of the projectiles shall be measured by thermocouples or thermometers in the burster wells of at least two projectiles in each oven batch. Leakage shall be determined by visual examination."

6.4 In first sentence delete "and wire brushes" and place a period after "lances."

Custodian:
Army - MU

Preparing activity:
Army - MU(EA)

Project No. 1315-A755

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:57Z
Check the source to verify that this is the current version before use.