MILITARY SPECIFICATION

PRIMER, STAB, M97
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification, MIL-P-60026 (MU), dated 10 April 1964, and is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add the following preamble underneath the title:

"This specification is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense."

PAGE 4

4.2.1c: Delete in its entirety and substitute the following:

"(c) Lead azide of the same type from not more than two lots produced by the same manufacturer in accordance with the same specification and same specification revision and which have subsequently been subjected to uniformly controlled drying and operating condition at the loading plant."

PAGE 6

4.2.3.5: Delete in its entirety and substitute the following:

"4.2.3.5 Sensitivity and output (see 3.6). - Major defect - Code No. 05012. - A sample of three hundred and fifteen (315) primers shall be randomly selected from each lot. If three (3) or more primers fail to comply with the specified requirements, the lot shall be rejected. If one or two defectives occur, a second sample of 315 primers shall be selected and tested. If, in the combined first and second sample, a total of four (4) or more

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 20261O-23T00:04Z
Check the source to verify that this is the current version before use.

defectives occur, the lot shall be rejected. The test shall be as specified in 4.3.3.1 using test equipment as specified in 4.2.4."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A244)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:04Z
Check the source to verify that this is the current version before use.