MILITARY SPECIFICATION

RADIO SET AN/ARC-131( )
(Units of)

This amendment forms a part of MIL-R-55563(EL), 17 October 1969.

1. Page 11, paragraph 3.17.12, delete and substitute:

3.17.12 Deviation

3.17.12.1 Narrow Band Deviation (See 4.9.12.1) The deviation of the transmitter shall be 8 ±2 KHz.

3.17.12.2 Wide Band Deviation (See 4.9.12.2) The deviation of the transmitter shall be 8 ±2 KHz.

2. Page 18, paragraph 4.5.1, Line 4: Delete "AGL's" and substitute "AQL's."

3. Page 20, Table I, under heading "Electrical Transmitter": delete "Deviation, 3.17.12, 4.9.12." and substitute, "Narrow Band Deviation, 3.17.12.1, 4.9.12.1" and "Wide Band Deviation 3.17.12.2, 4.9.12.2".

4. Page 22, Table III, Subgroup I under heading "Transmitter, Electrical": Delete "Frequency Accuracy".

5. Page 25, paragraph 4.7, add sub-paragraph "i" as follows: "Channel frequencies 33.90 MHz, 45.20 MHz, 56.50 MHz, and 67.80 MHz shall not be used".

6. Page 25, paragraph 4.8, Line 6: Delete "3.18.16" and substitute "3.18.6.1".

7. Page 25, paragraph 4.7.f, delete and substitute:

4.7.f Input Impedance - RF 50 OHMS, audio narrow band 150 OHMS, audio wide band 2000 OHMS.

8. Page 25, paragraph 4.7.g, delete and substitute:

4.7.g Input Level - Audio narrow band 0 DBM at 1000 Hz, audio wideband 4.24 VOLTS RMS at 1000 Hz.

9. Page 28, paragraph 4.9.2.2, first sentence, delete and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:35Z
Check the source to verify that this is the current version before use.

"With the transmitter deviated by a signal applied at the wideband terminal producing an 8 KHz deviation, the distortion shall be measured at the wideband output of a receiver which has the narrow band filters removed and replaced with dummy filters having input and output connected together internally. The transmitter output shall be attenuated to give an RF input to the receiver between 500 and 10,000 microvolts. Distortion measurements shall be made at 1,000, 5,000, 10,000 and 20,000 Hz to determine compliance with 3.17.2.2. This measurement shall be made at one RF frequency."

10. Page 29, paragraph 4.9.7, last sentence: Delete.

11. Page 30, paragraph 4.9.12, delete and substitute:

4.9.12 Deviation Test

4.9.12.1 Narrow Band Deviation Test - The transmitter shall be operated under appropriate standard conditions. The deviation shall be measured at 30.00, 52.00, 53.00, and 75.00 MHz to determine compliance with 3.17.12.1.

4.9.12.2 Wide Band Deviation Test - The transmitter shall be operated under appropriate standard conditions. The deviation shall be measured at 30.00, 52.00, 53.00, and 75.00 MHz to determine compliance with 3.17.12.2.

Custodian:
Army - EL

Preparing Activity:
Army - EL

Project No. 5821-A085

☆ U. S. GOVERNMENT PRINTING OFFICE: 1971-714-157/1670

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:35Z
Check the source to verify that this is the current version before use.