MIL-R-60862(MU)
AMENDMENT 1
17 January 1969

MILITARY SPECIFICATION
REMOVER, AIRCRAFT CANOPY
OVERHAUL, MODIFICATION AND CONVERSION
OF P/N 2218-17 TO P/N 2818-18

This amendment forms a part of Military Specification MIL-C-60862(MU) dated 10 April 1968.

Paragraph 2.1 Under STANDARDS: Delete

"MIL-STD-639 - Surface Roughness Values Preferred for Army Ordnance Materiel"

Following the parenthetical note of paragraph 2.1, add the following:

"2.2 Other publications.- The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ASA B46.1 - Surface Texture

(Application for copies should be addressed to the American Standards Association, 10 East 40th Street, New York, N.Y. 10016)"

Paragraph 4.3.3: Delete and substitute:

"4.3.3 Air firing test.- Utilize the air firing test fixture specified in T.O. 11P4-11-3. Prior to test, disassemble the remover as specified in Paragraph 3-1.j. Remove retaining pin P/N 2218-111 and re-assemble. An air pressure hose shall be connected to the fixture to actuate the remover under test. A pressure sensitive device shall be used to measure the pressure exerted to actuate the remover under test. The pressure sensitive device shall be inserted into the system by means of a Tee coupling between the remover and the hose connection. The remover shall be tested in accordance with the functional requirements of 3.4.3 and T.O. 11P4-11-3 and the results recorded."

Custodian:
Army - MU

Preparing Activity:
Army - MU
Project No. 1377-A331

FSC 1377

☆ U. S. GOVERNMENT PRINTING OFFICE: 1969-341-516/A-4196

Source: https://assist.dla.mil -- Downloaded: 202610-23T01:02Z
Check the source to verify that this is the current version before use.