MILITARY SPECIFICATION

SEALED RUBBER ROUND SECTION

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of sealed rubber round section used on a demolition charge container.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATION

MILITARY

MIL-P-116 ----- Preservation, Method of

STANDARDS

MILITARY

MIL-STD-105 --- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 -- Lot Numbering of Ammunition

DRAWINGS

ORDNANCE CORPS

8808362 ------- Packing and Marking for Storage and Shipments

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

8837236 ------- Gasket Container
8846448 ------- Packing for Container Gasket
EL-8837236 ---- Equipment List

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The sealed rubber round section shall comply with all requirements specified on the drawing (dwg) 8837236, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not applicable.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Tables I and II), and inspected for all characteristics in the applicable classification. Any characterisitcs in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed, as long as all characteristic inspections are performed.

Table I

Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II

Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Sealed rubber round section (see dwg 8837236).

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Length	*Measure
102.	Diameter	Gage
103.	No splits, cracks, inclusions, blisters, holes, flow line with visable change in contour	Visual
104.	Material (see 3.1)	Visual

*Measure with suitable scale.

Minor: None defined

4.3.2.1.2 Bag, packing, for repair parts (see dwg 8846448) covering dwg part number 8837236 and Section 5.

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Material (see 3.1)	Visual
102.	Length before packing, min.	*Measure
103.	Width before packing, min.	*Measure
104.	Proper heat seal	Visual/Manual
105.	Properly packed	Visual/Manual
106.	Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116	Visual
107.	No tear, split, crack or hole in bag	Visual

*Measure with suitable scale.

Minor		
201.	Marking correct and legible	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.3.2.1.3 Packing and marking for storage and shipments (see dwg 8808362) and Section 5.

Categories	Characteristics	Method of Inspection
Critical:	None defined	
Major		
101.	Gross load weight, max.	*Measure
102.	Contents tight in package	Manual
103.	Correctly packed	Visual/Manual
104.	Material (see 3.1)	Visual

*Determine weight with suitable scale.

Minor		
201.	Marking, correct and legible	Visual

4.3.3 Testing. This test shall be performed.

Test	Test Classification
a. Pull	Major

This test is not destructive. Samples tested may be returned to the lot.

4.3.3.1 Pull. A sample shall be selected at random in accordance with Table III. The sample shall be tested in accordance with 4.4.1. If any item fails to comply with drawing requirements, the lot shall be rejected.

Table III

Sample Sizes for Nondestructive Testing

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL's). (See EL-8837236.) When either of the conditions listed below exists, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).

b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on EL's. The acceptance inspection equipment, operating instructions, and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances, less the accuracy tolerances of the test equipment used.

4.4.1 Pull (see 4.3.3.1). The splice of each gasket shall be pulled to minimum drawing requirement with approved equipment that will not damage gasket.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The sealed rubber round section shall be packaged in accordance with dwgs 8846448 and 8808362 using the specified moisture barrier.

5.1.2 Level C. The sealed rubber round section shall be packaged in accordance with dwg 8808362, except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Levels A or C. The sealed rubber round section shall be packed in accordance with dwgs 8846448 and 8808362.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

5.3 Marking. Marking shall be as specified in accordance with dwgs 8846448 and 8808362, as applicable.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when specified on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey, 07801, ATTN: SMUPA-QA-N-I.

Custodian:
Army - MU

Preparing activity:
Army - MU
Project No-5330-A041

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.