MIL-S-80201C
6 July 1987
SUPERSEDING
MIL-S-80201B
1 June 1986

# MILITARY SPECIFICATION

## SAWS, BAND, METAL CUTTING, VERTICAL, CONTOUR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers vertical, contour, metal cutting band saws, having a nonfeeding tilt type worktable.

1.2 Classification. The band saws covered by this specification shall be of the following sizes. The size supplied shall be as specified (see 6.2.1). ‘

Size 14 - 14 inch - throat width
Size 20 - 20 inch - throat width
Size 26 - 26 inch - throat width
Size 36 - 36 inch - throat width
Size 60 - 60 inch - throat width

## 2. APPLICABLE DOCUMENTS

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issue of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSM, Memphis, Tennessee 38114-5051, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document by letter.

AMSC N/A FSC 3405
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

sJ,tj~[~I(;AˊJIONs

MI I,l′I′ARY

MI IJ-M-18058 - Machinery, Metal and Woodworking, Packaging of.

sTANDARDS

FEDERAL

FED- STD-H28 - Screw Thread Standards for Federal Services.

FE D-S TD-376 - Preferred Metric Units for General Use by the Federal Government.

MILITARY

MI L-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.

2.1.2 Other Government documents and publications. The following other Government documents and publications form a part of this specification to the extent specified here;n. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U. S. DEPARTMENT OF LABOR

29 CFR 1910 - Occupational Safety and Health Standards (OSHA).

(Application for copies should be addressed to the Superintendent of Documents, Government Pr<nting Office, Washington, DC 20402-0001. )

(Copies of specifications, standards, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity. )

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issue of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issue of documents not listed in the DoDISS shall be the issue of the non-Government documents which are current on the date of the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI B11.10 - Safety Requirements for the Construction, Care, and Use of Metal Sawing Machines.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

ANSI/NFPA 79 - Electrical Standard for Industrial Machinery.

ANSI/NEMA MG-1 - Motors and Generators.

(Application for copies should be addressed to the American National Standards Institute, ATTN: Sales Dept., 1430 Broadway, New York, NY 10018-3308. )

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 3951 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103-1187. )

AMERICAN GEAR MANUFACTURER'S ASSOCIATION (AGMA)

AGMA 360.02 - Manual for Machine Tool Gearing.

AGMA 390.03 - Gear Classification, Materials and Measuring Methods For Unassembled Gears.

(Application for copies should be addressed to the American Gear Manufacturer's Association, Standards Department, Suite 1000, 1901 North Fort Meyer Drive, Arlington, VA 22209-1695. )

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION (1S0)

1S0 54 – Cylindrical Gears For General Engineering and For Heavy Engineering, Modules and Diametral Pitches of.

(Application for copies should be addressed to the International Organization for Standardization, c/o American National Standards Institute, ATTN: Sales Department, 1430 Broadway, New York, NY 10018-3308. )

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this sp==on and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order (see 6.2.1), a sample shall be subjected to first article inspection (see 4.2.1 and 6.3).

3.2 DesiKn. The band saw machine shall be new and one of the manufacturer's current models capable of operations in accordance with the requirements herein. The machine shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.2.1 Measurement systems. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (S1) shall be used in the design and construction of the band saw. When only one system of measurement is acceptable, the particular system required shall be as specified (see 6.2.1). In this specification, all measurements, dimensions, sizes, and capacities are given in US units. These measurements may be converted to S1 units through the use of the conversion factors and methods specified in FED-STD-376.

3.2.2 Reclaimed materials. The band saw may contain reclaimed materials provided such materials will not jeopardize the band saw's intended use and performance. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner which will restore them to the same chemical composition and physical properties as the materials originally selected for use on the band saw.

3.2.3 Energy efficiency. The band saw and its components that directly consume energy in normal operation shall be designed and constructed for energy efficiency as governed by the developments available within the industry.

3.2.4 Controls. All operating controls shall be located convenient to the operator at his normal work station.

3.2.5 Safety and health requirements. Covers, guards, or other safety devices sh=ll be provided for all parts of the saw that present safety hazards. The safety devices shall not interfere with the operation of the saw. The safety devices shall prevent unintentional contact with the guarded part, and shall be removable to facilitate inspection, maintenance, and repair. All saw parts, components, mechanisms, and assemblies furnished on the saw, whether or not specifically required herein, shall comply with all of the requirements of OSHA 29 CFR 1910 that are applicable to the saw. In addition, the saw shall comply with all the requirements of ANSI B11.1O that are designated therein as the responsibility of the saw manufacturer. In the event of conflict between the requirements of OSHA and ANSI standards,



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

the requirements of OSHA shall apply. Additional safety and healtl] requirements shall be as specified (see 6.2.1).

3.2.6 Mercury restriction. ‘he band saw shall not contain mercury or mercury compound~nor be exposed to free mercury during manufacture.

3.2.7 Asbestos restriction. Asbestos and materials containing asbestos shall not be used on or in the band saw.

3.2.8 Environmental protection. The band saw shall be so designed and constructed that under the operating, service, transportation, and storage conditions described herein, the band saw shall not emit materials hazardous to the ecological system as prescribed by Federal, state, or local statutes in effect at the point of installation.

3.2.9 Lubrication. Means shall be provided to ensure adequate lubrication for all moving parts. Recirculating lubrication systems shall include a filter which is cleanable or replaceable. Each lubricant reservoir shall have means for determining fluid level. All oil holes, grease fittings, and filler caps shall be accessible.

3.2.10 Interchangeability. To provide for replacement of worn parts, all parts shall be manufactured to definite dimensions and tolerances.

3.3 Construction. The band saw shall be constructed of parts which are new, without defects, and free of repairs. The structure shall be capable of withstanding all forces encountered during operation of the band saw to its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free of defects, scale and mismatching. No processes such as welding, peening, plugging, or filling with solder or paste shall be used for reclaiming any defective part.

3.3.2 Fastening devices. All screws, pins, bolts, and other fasteners shall be installed in a manner to prevent change of tightness. Fastening devices subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently installed.

3.3.3 Surfaces. All surfaces shall be clean and free of sand, dirt, fins , sprues, flash, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer’s commercial practice.

3.3.4 Welding, brazing, or soldering. Welding, brazing or soldering shall be employed only where specified in the original design. None of these operations shall be employed as a repair measure for any defective part .

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

3. ’3.5 Painting. Unless otherwise specified (see 6.2.1), the band saw shall be p;lin((>d in accordance with the manufacturer’s commercial practice.

3.3.6 Threads. All threaded parts used on the band saw and its related attachments and accessories shall conform to FED-STD-H28 and the applicable “De(a iled Standard” section referenced t-herein.

3.3.7 Gears. All gears and pinions of spindle and axis drive trains shall be designed and manufactured of a suitable ferrous material to meet or exceed the requirements of AGMA 360.02 and 390.03 for the English (US) system or 1S0 54 for the metric (S1) system. The gears shall be of proper width and size to transmit full-rated torque and horsepower throughout the speed ranges without failure for the expected service life of the machine. Gears in the drive train shall be hardened and ground steel.

3.4 Components. The saw shall consist essentially of a frame, band drive system, band guides and guide post, worktable and other components as described herein.

3.4.1 Frame. The frame shall support the drive motor, band carrier wheels, band drive mechanism, band tensioning mechanism, band guides and guide posts, worktable and workpiece feed mechanisms, and other accessory equipment manufactured for installation thereon. The frame shall maintain mutual component alignment to the degree necessary to enable the saw to meet the performance requirements of 3.6. The frame base shall have provisions for anchoring the saw. Hinged access doors, or removable covers, shall facilitate changing bands, servicing and adjusting the internal components. When specified (see 6,2.1), size 14 saw frames shall accept a block type insert which will increase the throat height to not less than 12 inches.

3.4.2 Band carrier wheels. The band carrier wheels shall be supported by permanently lubricated ball or roller bearings. The carrier wheels shall have means for aligning and tracking the band. The =aw shall have a band tensioning mechanism capable of providing tensions required for the size bands specified in table I. Band tension indicator shall reveal the amount of band tension applied. Band tensioning and tracking handwheels and controls shall be conveniently located. The band wheels shall run true in a lateral and radial direction, either be flanged or have oil resistant tires and be balanced to meet the performance re - quirements specified herein.

3.4.3 Bands. The saw shall use all stated size bands up to the including the width spe=d in table 1. Saw bands of the specified quantity, size, tooth pitch and type (see 6.2.1), shall be furnished with each machine. When specified (see 6.2.1), file bands in the specified herein.

3.4.4 Band drive system. The band drive system shall consist of an electric motor operating in conjunction with either a belt drive system, a multi-speed transmission or step cone pulleys and a band drive wheel. Unless otherwise specified, the band drive system shall have an electric motor having a horsepower rating conforming to the requirements shown as “Standard” in table 1. When


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

specified (see 6.2.1), the band drive system shall have an electric motor conforming to the requirements shown under "Optional" in ;able. 1. The band drive system shall provide the number of evenly spaced band speed selections and the band speed range specified in table I. When specified (see 6.2.1), size 60 saws shall have special band speeds, such as 10,000 or 15,000 band feed per minute.

3.4.5 Guide post. The guide post shall be supported on the upper hand carrier wheel housing and shall adjust to accommodate workplaces up to the maximum thickness required herein. The vertically adjustable guide post shall be capable of being maintained in any adjust position within its adjustment range. The guide post shall support band guides, mist or air coolant attachments, and all other guide post mounted accessories commercially furnished by the manufacturer. The guide post shall have rigidity to prevent twisting of the band and assure that the band runs perpendicular to the table top surface to meet the performance requirements herein.

3.4.6 Band guides. Band guides shall be suitable for use with the specified size bands and at the band speeds specified herein. When nonrotating guides furnished, the inserts for all band sizes above 1/4 inch shall either be hardened steel or carbide faced on all surfaces which contact the band. Rotating guides shall be either hardened steel or carbide faced and shall be mounted on ball or roller bearings. A complete set of band guides and inserts covering the range of bands specified herein shall be furnished when specified (see 6.2.1). A backup support platen and guide for abrasive bands shall be furnished when specified (see 6.2.1). Means shall be provided to facilitate platen and guide adjustment.

3.4.7 Worktable. The worktable of each saw shall be of the fixed (nonfeeding) type, capable of being tilted through the tilt angles specified in table 1. A table tilt quadrant shall indicate the angle of table tilt. The quadrant shall be graduated in increments of 1° and marked with a numerical value every 10° or less. A locking device shall securely retain the table in any tilt position within its adjustment range. The work support of the table shall be finished and shall be flat within 0.005 inch per foot. The worktable and its supporting structure shall be capable of supporting a workpiece load of not less than 150 pounds, without damage or permanent deformation. The worktable shall have a through-slot and removable filler plate to facilitate changing bands.

3.4.7.1 Auxiliary worktable. All saws having throat depth of 36 inches and greater, shall have an auxiliary worktable. The auxiliary worktable shall be mounted to support workplaces overhanging the main worktable to the frame column. The workpiece support surface of the auxiliary worktable shall be finished and flat within 0.005 inch per foot. The auxiliary worktable shall be securely mounted on, and shall be readily removable from, the frame base. The workpiece support surface of the auxiliary worktable shall in be readily removable from, the frame base. The workpiece support surface of the auxiliary worktable shall be in the same plane as the workpiece support surface of the main table within 0.010 inch per foot.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

3.4.8 Band welder. Unless otherwise specified (see 6.2.1), a band welder shall be furnished with each saw. The band welder shall be capable of welding and annealing standard carbon steel bands of various widths up to the maximum size band width specified, for that size saw, in table I. When specified (see 6.2.1), the band welder shall be capable of welding height speed, bimetal saw bands through 1 inch width. A shear shall be mounted adjacent to the welding fixture for cutting bands. The welding shall be equipped with quick acting clamps for holding the band ends while they are bei.rlg welded. An independent electric motor driven grinding wheel, for grinding the flash area of the band after welding, shall be furnished with each band welder. The band welder shall be mounted on the column of the saw, with the exception of the size 14 saw.

3.4.9 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system shall conform to ANSI/NFPA 79. Each band saw shall draw all of its electrical power from a single 230/460-volt, 3-phase, 60-hertz (Hz) circuit. Each band saw shall be initially wired for operation on 460 volts. An identified terminal for grounding the band saw when it is installed shall be mounted i.n or near the disconnected switch. The terminal shall be suitable for connecting the size grounding conductor specified in ANSI/NFPA 79 for the disconnect fuse rating.

3.4.9.1 Motors. Motors shall be rated for continuous duty and shall be have ball or roller bearings of the sealed and permanently lubricated type. Unless otherwise specified specified (see 6.2.1), each motor enclosure shall meet the requirements for a drip-proof enclosure. All motors shall be i.n accordance with ANSI/NEMA MG 1.

3.4.9.2 Solid-state components. Solid-state design shall be used throughout for electronic components.

3.4.9.3 Control circuit voltage. Auxiliary control circuits shall be isolated from the input electric power supply by a low-voltage transformer having a secondary voltage of not more than 120 volts.

3.5 Size and capacity. Unless otherwise specified (see 6.2.1), the size and capacity of the band saw shall be not less than those specified i.n table I for the band saw size specified.

3.6 Performance. The saw shall be capable of sawing SAE 1018 steel to the accuracies specified i.n table II when tested in accordance with 4.4.

3.7 Standard equipment. Unless otherwise specified (see 6.2.1), the following equipment shall be furnished with each saw:

a. Hand tools. One set of hand tools normally furnished by the supplier.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

b. Cutting chart . A selector chart or dial indicat ing recommended cutting speeds, feeds and tooth pitches for various saw operations.

c. Tachometer or band speed indicator. A band speed chart, plate, or tachometer indicating band velocity in feed per minut-e.

d. Saw band. One saw band of the type used i.n performance testing.

3.8 Optional equipment. Optional equipment shall be furnished as specified and fully described (see 6.2.1).

3.9 Lubrication chart or plate. Unless other specified (see 6.2.1), a lubrication chart or plate shall be permanently and securely attached to each machine . If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets, with suitable means for mounting. The chart or plate shall contain the following information:

Points of lubricant application
Servicing interval
Type of lubricant
Visocity

3.10 Nameplate. Unless otherwise specified (see 6.2.1), a nameplate shall be securely attached to each band saw and contain the information listed below. If the band saw is a special model, the model designation shall include the model of the basic standard band saw and a suffix identified in the manufacturer's permanent records. The caption listed may be shortened or abbreviated, provided the entry for each caption is clear as to its identity.

Nomenclature
Manufacturer's name
Manufacturer's model designation
Manufacturer's serial number
Power input (volts, total amps, phase, frequency)
Contract Number or Order Number
National Stock Number or Plate Equipment Code
Date of manufacture

3.11 Electromagnetic interference control. When specified (see 6.2.1), equipment procured under this specification shall comply with the requirements of MIL-sTD-461.

3.12 Technical data. Technical data shall be furnished as specified (see 6.2.2).

3.13 Workmanship. Workmanship of the machine and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

4. [/lJ,\l, I'rY ASSURANCE PROVISIONS

~.1 Rt'sponsibi lity for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as o~herwise specified in the contractor may use his own or any other facilities suitable for the performance of the inspection requiremen~s specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the specification were such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

. First article inspection (see 4.2.1).
;. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. When first article approval is required under 3.1, first article inspection shall be performed. Unless otherwise specified (see 6.2.1), first article inspection shall comprise the examination in 4.3 and all tests in 4.4. Failure of the item to pass any examination or test shall be cause for disapproval of the first article.

4.2.2 Quality conformance inspection. Each item shall be subjected to quality conformance inspection prior to being offered for acceptance. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of the examination in 4.3, the test in 4.4.1 and the inspection in 4.5. Failure of the item to pass any examination, test, or inspection shall be cause for rejection.

4.3 Examination. The machine and equipment shall be examined to determine compliance with the requirements in 3.2 through 3.5 and 3.7 through 3.13.

4.4 Tests.

4.4.1 Operational test. The machine shall be operated at no load for not less than 15 minutes, during which time the controls and all operating components shall be actuated and observed to determine that they operate properly.

4.4.2 Performance tests. The saw shall be subjected to the following tests. Failure to meet the requirements shall be cause for rejection. Saw band width shall conform to table 1. The type, set and pitch shall be at the option of the supplier.

4.4.2.1 Cutting test. The saw shall be equipped with a saw band of the width specified in table I with the table adjusted to zero tilt position. The saw shall make five cuts through a l-inch by 4-inch SAE 1018 steel bar. The perpendicularity of each cut shall be in accordance with table II.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

4.4.2.2 Band welder test. A section of band shall be cut to the length required for the saw being tested. The band shall be standard carbon steel for saws equipped with a standard carbon steel welder and high speed steel band for the saws equipped with a high speed steel welder. The band shall be severed, welded, ground and annealed with the welding fixture provided with the saw. This cycle shall be repeated to produce a total of five welds on the band.

4.4.2.3 Welded band test. The welded band shall be installed and properly tensioned on the saw. A 3-1/2-inch radius semicircle in a l-inch thick plate of low carbon steel (0.02 percent carbon or less) shall be cut to prove the strength and reliability of the welds.

4.4.2.4 Guidepost deflection test. With the guidepost securely locked in its lowest operating position, a 20 pound force shall be applied to the front and then to each of the two sides, at a point 6 inches above the table workpiece support surface. Guidepost deflection shall no exceed 0.015 inch, measured at the extreme lower end of the post.

4.4.2.5 Filing and polishing test. Saws furnished with filing and polishing equipment shall be tested to demonstrate their ability to file SAE 01 tool steel and polish to a surface finish not rougher than 32 microinch.

4.5 Packaging inspection. Packaging of each item shall be inspected to determine compliance with the requirements of section 5.

## 5. PACKAGING

5.1 Preservation, packing, and marking. Unless otherwise specified, preservation, packing, and marking shall be in accordance with ASTM D 3951. When specified (see 6.2.1), level A preservation, level A or Level B packing, and marking shall be accomplished in accordance with MIL-M-18058.

## 6. NOTE S

6.1 Intended use. Saws covered by this specification are intended for general internal and external straight line and contour sawing operations. When the saw is so equipped, filing a~d polishing operations & “ferrous and nonferrous workplaces can be performed.

6.2 Ordering data.

6.2.1 Procurement requirements. Purchases should specify their requirements in procurement documents, including whether each choice is required or not required, by entering an appropriate statement identified to each of the fol low-ing:

a. Title, number, and date of this specification.

b. Size saw required (see 1.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

c. First article approval, if required (see 3.1).

d. If machine is required to be configured in a specific measurement system (US or S1), state required system (see 3.2.1).

e. Specify additional safety and health requirements (see 3.2.5).

f. Painting, if different (see 3.3.5).

g. Block-type insert for frame (size 14 saw), if required (see 3.4.1).

h. Saw and file bands, if required, as fully described (see 3.4.3).

i. Optional horsepower of special band speeds, if required (see 3.4.4 and table I).

j. Special band saw speeds on size 60 saws, if required (see 3.4.4).

k. File band guides and abrasive band platen with guides, if required (see 3.4.6).

l. Band welder, for either standard carbon steel or high speed bimetal bands, with shear and grinder, or delete band welder, if not required (see 3.4.8).

m. Electrical system and voltage, if different (see 3.4.9).

n. Type of motor enclosure, if different (see 3.4.9.1).

o. Size and capacity, if different (see 3.5).

p. Standard equipment, if different (see 3.7).

q. Optional equipment, if required (see 3.8).

r. Lubrication chart, if different (see 3.9).

s. Nameplate, if different (see 3.10).

t. Electromagnetic interference control, if required (see 3.11).

u. Technical data, if required (see 3.12).

v. First article inspection, if different (see 4.2.1).

w. Quality conformance inspection, if different (see 4.2.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

x. If preservation, packing, and marking in accordance with MIL-M-18058 is required, specify level required (see 5.1).

6.2.2 Contract data requirements. Required technical data (operating manuals, parts lists, wiring diagrams, founded and anchor bolt, plans, and acceptance test reports) should be specified on a DD Form 1423, Contract Data Requirements List, incorporated into the contract.

6.3 First article. When first article inspection is required, the item to be tested should be the first item offered for acceptance under the contract. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.4 Subject term (key word) listing:

Contour
Metal cutting
Nonfeeding
Saws band
Tilt worktable
Vertical


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

TABLE 1. Sizes and capacities.

| Characteristics | Requirements | | | | |
|---|---|---|---|---|---|
| | Size 14 | Size 20 | Size 26 | Size 36 | Size 60 |
| Throat width, inches | 14 | 20 | 26 | 36 | 60 |
| Throat height, under guide (rated workplace thickness), inches | 6-1/4 | 12 | 12 | 12 | 13 |
| Worktable dimensions, inches | 14 x 14 | 24 x 24 | 30 x 30 | 24 X 24 | 32 X 40 |
| Auxiliary worktable dimensions, inches | None | None | None | 17 x 19 | 30 x 30 |
| Maximum tilt angle: right<br>left | 45<br>10 | 45<br>10 | 45<br>5 | 45<br>10 | 45<br>5 |
| Band data: | | | | | |
| Saw band width, rahge, inches | 1/4 - 3/4 | 1/4 - 1 | 1/4 - 1 | 1/4 - 1 | 1/4 - 1 |
| File band width, range, inches | None | 1/4 - 1/2 | None | l/4 - 1/2 | None |
| Speed range, RPM | 40 - 3000 | 50 - 4000 | 5~ | 50 - 5200 | 50 - 5200 |
| Number of band speed selections | 8 or inf. var. | 8or inf. var. | 8 or inf. var. | 8 or inf. var. | 8 or inf. var. |
| Upperwheel, vertical adjustment, inches | 1 | 1-1/2 | 2 | 3 | 3 |
| Motor horsepower minimum: standard<br>optional | 1/2<br>3/4 | 1-1/2<br>2 or 3 | 5<br>3 | 1-1/2<br>2, 3 or 5 | 7-1/2<br>2,3,5 or 10 |

NOTE : Requirements are not less than those shown. Where a range is shown, the required performance is from the stated minimum or less to the stated maximum or more.





Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

TABLE II. Performance.

| Size | ~/ Perpendicularity of cut to surface resting on worktable |
|---|---|
| 14 | 0.008 |
| 20 | 0.005 |
| 26 | 0.005 |
| 36 | 0.005 |
| 60 | 0.005 |

J/ Inches per inch of cut.

Custodians:
Army - AL
Navy - SH
Air Force - 99

Review activities:
Navy - YD
Air Force - 84

User activity:
Navy - MC

Preparing activity:
DLA - 1P

Project (3405-0079)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documenti better, the DoD provides this form for use in submitting comments and suggestiona for improvements. AU usera of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the Ibose edge *(DO NOT STAPLE)*, and & tiled. In bl~k 5, be u Specific ss ~ible about particular problem areas such ss wording which required interpretation, waa too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE: This* form may not be used to request copies *of* documents, nor to request waivers, deviations, or clarification of specification requirement on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

*(Fold along thu line)*

*(Fold along thk* Ifne)

DEFENSE LOGISTICS AGENCY

111111

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

O:"FICIAL BUSINESS
PENALTY FOR PRIVATE USE S300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 WASHINGTON O C.

POSTAGE WILL BE PAID 8Y THE DEFENSE LOGISTICS AGENCY

DEFENSE LOGISTICS AGENCY
DEFENSE INDUSTRIAL PLANT EQUIPMENT CENTER
ATTN : DIPEC-SSM
MEMPHIS, TN 38114 -505i

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions - Reverse Side)

| 1. DOCUMENT NUMBER | 2. OOCUMENT TITLE |
|---|---|
| MI L-S-80201C | Saws, Band, Metal Cuttinq, Vertical, Contour |

| la NAME OF SUBMITTING ORGANIZATION | 1. TYPE OF ORGANIZATION (,Mark one) |
|---|---|
| | ❑ VENOOR |
| v. AODRESS (Street, City, *State, ZIP Code*) | O USE R |
| | [ i ] MANUFACTURER |
| | H OTHER (Specify): |

i. PR08LEM AREAS

a Pwqr~ph Number end Wording:

b. Rocommonded Wo-dine:

c. Ro~son/Rmionslc for Recommendmion:

REMARKS

| a. NAME OF SUBMITTER *(Last, Firsf, Ml) - C)ptl onal* | b. WORK TELEPHONE NUMBER (Include A Code) - Optional |
|---|---|
| MAILING AOORESS (S fmet, City, Sfole, ZIP Code) - Opt!on~l | 8 DATE OF SUBMISSION fYY.$fMDD) |

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:46Z
Check the source to verify that this is the current version before use.



(TO DETACH THIS FORM, CUT ALONG THIS LINE.)