MILITARY SPECIFICATION

VENT ASSEMBLY

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of vent assembly used on M467 Container for XM454 and 455 projectiles and containers in general.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169(MU) - Packaging, Packing, and Marking for Shipments of Inert Ammunition Components
MS 25043-10C - Cap
MS 35743-1 - Rivet, Solid, Pan Head
MS 39081-4 - Nut Plain, Hex

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8853791 - Vent Assembly
8853792 - Cap Assembly
8853794 - Retainer
8853795 - Plug
8853797 - Gasket
8853798 - Washer
8883535 - Bag, Packing, for Repair Parts
ET-8853791 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The vent assembly shall comply with all requirements specified on the drawing (dwg) 8853791, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.3.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.3.3 Burrs. Parts shall be free from burrs.

3.3.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not applicable.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Retainer (see dwg 8853794) covering a detail of dwg 8853792.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Diameter of small hole, max (.1562)	Gage
	102. Diameter of large hole, max (.6562)	Gage
	103. Thickness, min (.021)	Gage
	104. Material (see 3.1)	Visual
Minor:		
	201. Workmanship (see 3.3)	Visual-Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Gasket (see dwg 8853797) covering a detail of dwg 8853792.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Diameter, min (.635)	Gage
	102. Thickness, min (.072)	Gage
	103. Material (see 3.1)	Visual
	104. No tear, crack or hole	Visual
Minor:		
	201. Workmanship (see 3.3)	Visual-Manual

4.3.2.1.3 Cap assembly (see dwg 8853792) covering a detail of dwg 8853791.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Objective evidence (see 6.2) for cap in accordance with MS 25043-10C	Visual
	102. Objective evidence (see 6.2) for rivet in accordance with MS 35743-1	Visual
	103. Rivet tight	Manual
	104. No part missing	Visual
Minor:		
	201. Workmanship (see 3.3)	Visual-Manual

4.3.2.1.4 Plug (see dwg 8853795) covering a detail of dwg 8853791.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Pitch diameter of thread	Gage
	102. Major diameter of thread	Gage
	103. Depth of groove in flange (.040),max	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

104. Diameter adjacent to flange (.635).....Gage
105. Length of thread (.592).....Gage
106. Total length (.753).....Gage
107. Length to flange (.624).....Gage
108. Inside diameter, min (.348).....Gage
109. Distance across flats of hex (1.00).....Gage
110. Objective evidence (see 6.2) for protective finish in accordance with dwg 8853795.....Visual
111. Material (see 3.1).....Visual

Minor:
201. Workmanship (see 3.3).....Visual-Manual

4.3.2.1.5 Washer (see dwg 8853798) covering a detail of dwg 8853791.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Inside diameter, max (.615)	Gage
	102. Thickness, min (.072)	Gage
	103. Outside diameter, min (.822)	Gage
	104. No tear, crack or hole	Visual
	105. Material (see 3.1)	Visual
Minor:	None defined.	

4.3.2.1.6 Vent assembly (see dwg 8853791).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. No part missing	Visual
	102. Washer lies flat in groove and extends above face of flange	Visual
	103. Objective evidence (see 6.2) for nut in accordance with MS 39081-4	Visual
Minor:		
	201. Workmanship (see 3.3)	Visual-Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.3.2.1.7 Preparation for delivery (see 5.1).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Preservation, packaging, packing and marking in accordance with MIL-STD-1169(MU)	Visual-Manual
Minor:	None defined.	

4.3.2.1.8 Bag, packing for repair parts (see dwg 8883535 covering part number 8883535-2 and 5.2).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Material (see 3.1)	Visual
	102. Length before packing, min	*Measure
	103. Width before packing, min	*Measure
	104. Properly packed	Visual-Manual
	105. Proper heat seal	Visual-Manual
	106. No hole or crack in bag	Visual
	107. Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116	Visual

*Measure with suitable scale.

Minor:		
	201. Marking	Visual
	202. Workmanship (see 3.3)	Visual-Manual

4.3.2.1.9 Packing and marking for storage and shipments (see 8808362) and 5.2.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

Major:

101.	Gross load weight (max)	*Measure
102.	Contents tight in package	Manual
103.	Correctly packed	Visual-Manual
104.	Material (see 3.1)	Visual

*Determine weight with suitable scale.

Minor:

201.	Marking	Visual
202.	Workmanship (see 3.3)	Visual-Manual

4.3.3 Testing. Not applicable.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). ELs for assemblies are listed on the Equipment Tabulation, ET 8853791. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).

b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. Not applicable.

5. PREPARATION FOR DELIVERY

5.1 Production items.

5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1.1 Level A. The vent assembly shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

5.1.1.2 Level C. The vent assembly shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Packing.

5.1.2.1 Levels A and C. The vent assembly shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

5.2 Repair parts.

5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The vent assembly shall be packaged in accordance with dwgs 8883535 and 8808362 using the specified moisture barrier.

5.2.1.2 Level C. The vent assembly shall be packaged in accordance with dwg 8808362 except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Level A and C. The vent assembly shall be packed in accordance with dwgs 8883535 and 8808362.

5.2.3 Marking. Marking shall be as specified in accordance with dwgs 8883535 and 8808362.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Production or Repair Parts.
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a DI-E-118 when specified on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-QA-N-I.

Custodian:
Army - (AR)

Preparing activity:
Army - (AR)

Project No. 1190-A062

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.