MILITARY SPECIFICATION

WARHEAD SECTION SUBASSEMBLY, ATOMIC: M15

This amendment forms a part of Military Specification MIL-W-63181(AR) dated 17 November 1977.

PAGE 2

Drawings: Add "8885491 - Fuze Setter Assembly (M1103 Fuze)".

PAGE 4

*Delete paragraph 3.5 and substitute:

"3.5 Capacitance of the impact fuze networks.- The capacitance of the impact fuze networks shall be as specified in Table I at an ambient test temperature of 75°F. The tests on the nose section networks shall be performed prior to the tests on the overall networks. In addition, the actual capacitance value in picofarads (pf) for each network shall be recorded (see 3.13). When the capacitance is measured at an ambient temperature that differs from 75°F, the capacitance value shall be extrapolated to the equivalent capacitance at 75°F (see 6.8). Testing shall be as specified in 4.5.1.

TABLE I

Network and test points	Limits (pf) @ 75°F	Test identification number (see 3.13)
Nose section, network 1: Tee connector 2CP4 J1	464 - 517	092001
Nose section, network 2: Tee connector 2CP3 J1	467 - 520	092003
Overall network 1: 4W70 P3A to P3B-H	709 - 785	092002
Overall network 2: 4W70 P3E to P3F-D	787 - 879	092004

"

☆ U.S. GOVERNMENT PRINTING OFFICE: 1981—703-023/5429

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:22Z
Check the source to verify that this is the current version before use.

PAGE 5

Delete Table III and substitute:

"TABLE III. M1103 inertial fuze presets.

Preset	Reading
Set decrement	4000
Set velocity	1500
Set multiplier	11.0
Set time	400
Reset decrement	0000
Reset velocity	0000
Reset multiplier	2.0
Reset time	0000

"

PAGE 6

Table IV: Delete "J8-M" and substitute "J8-m".

PAGE 12

Delete Minor defect 202 and substitute:

"202. Protective cover for the J2 and J8 connectors (on aft bulkhead) missing, improper, or improperly packaged (in records receptacle) (2 covers).....Visual"

PAGE 15

*Delete paragraph 4.5.1 and substitute:

"4.5.1 Capacitance of the impact fuze networks.- The capacitance of the impact fuze networks shall be measured by using a Government-approved capacitance bridge at a frequency of 1000 hertz (Hz). The nose section shall be fastened to the center section prior to performing the tests on the overall networks. Because of the temperature sensitivity of the ceramic elements in the impact fuze, the ambient (room) temperature must be maintained for a minimum period of 4 hours before testing. Capacitance values shall be extrapolated to 75°F when the ambient test temperature differs from 75°F (see 6.8). The ambient test temperature range shall be from 50° to 90°F. The impact fuze networks shall comply with the requirements of 3.5 during this test."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:22Z
Check the source to verify that this is the current version before use.

PAGE 16

(a) Delete paragraph 4.5.3 and substitute:

"4.5.3 M1103 fuze setting.- A fuze setter assembly (dwg. 8885491), or equivalent, shall be used to apply the presets specified in Table III through the 4W36 J8 connector (located on the aft bulkhead of the M15 subassembly). The input power to the fuze setter, and the voltages to be applied to the various circuits, shall be as specified in the operating/calibration instructions for the fuze setting equipment. The fuze shall comply with the requirements of 3.7 during this test."

(b) Table XI, Motor control phase, Voltage column: Change each of the following voltages to "10 Vrms max.": "2.5, 3.5, 5.5, and 4.5 Vrms max."

PAGE 19

*Add paragraph 6.8 as follows:

"6.8 Temperature-capacitance extrapolations.- During capacitance measurements of the impact fuze networks (see 3.5), the ambient (room) temperature must be maintained at 75°F to conform with the capacitance limits of Table I. If the capacitance measurements are obtained at an ambient temperature that differs from 75°F, use the following formula to extrapolate the capacitance values to 75°F:

$$C_{75} = k(75 - t_a) + C_a$$

Where C_{75} = Capacitance (pf) extrapolated to 75°F.
t_a = Ambient test temperature (°F).
C_a = Capacitance (pf) at the ambient test temperature.
k = 1 = picofarads/degree F."

NOTE: The margins of this amendment, at left of text, are marked with asterisks to indicate where major changes (additions, modifications, corrections, deletions) were made from the previous amendment. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

(Project 1115-A075)

Preparing activity:
Army-AR

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:22Z
Check the source to verify that this is the current version before use.