The documentation and process conversion measures necessary to comply with this amendment shall be completed by 10 September 1992.

INCH-POUND

MIL-S-19500/276B
AMENDMENT 3
10 March 1992
SUPERSEDING
AMENDMENT 2
6 June 1991

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, THYRISTORS (CONTROLLED RECTIFIERS), SILICON
TYPES 2N2323, 2N2324, 2N2326, 2N2328, 2N2329, AND S VERSIONS
2N2323A, 2N2324A, 2N2326A, 2N2328A, AND S VERSIONS
JAN, JANTX, JANTXV, AND JANS

This amendment forms a part of MIL-S-19500/276B, dated 28 April 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

1.4 Primary electrical characteristics (at 25°C, unless otherwise specified), V_{FM} column: Delete "i_{FM} = 40(pK)" and substitute "i_{FM} = 4(pK)".

PAGE 3

FIGURE 1, physical dimensions, letter A, inches column, maximum limits: Delete "370" and substitute ".370".

PAGE 8

FIGURE 3, operating conditions - continued: Delete in its entirety.

* TABLE I, subgroup 3, gate trigger voltage, delete and substitute as printed below:

Gate trigger voltage	4221			V_{GT3}	0.1	---	V dc
2N2323, S, A, AS 2N2324, S, A, AS 2N2326, S, A, AS		R_L = 100Ω; R_e = 1 kΩ					
2N2328, S, A, AS 2N2329, S		R_L = 100Ω, R_e = 2 kΩ					
2N2323, S, A, AS 2B2324, S, A, AS 2B2326, S, A, AS 2B2328, S, A, AS 2B2329, S		$V_2 = V_{FBX}$ = 6 V dc $V_2 = V_{FBX}$ = 6 V dc $V_2 = V_{FBX}$ = 6 V dc $V_2 = V_{FBX}$ = 6 V dc $V_2 = V_{FBX}$ = 6 V dc					

PAGE 16

* TABLE I, subgroup 4, holding current, symbol column: Delete "I_{HOX}" and substitute "I_{HOX}".

PAGE 17

* TABLE I, subgroup 6, after surge testing, add the following:

*	End-point electrical measurements		See table IV, steps 1, 2, 3, and 4					*

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

PAGE 19

* TABLE IIa, subgroup 6, delete and substitute as follows:

*	Thermal resistance	3181	$R_{\theta JA}$ = 175°C/W max			*

PAGE 21

* TABLE IIb, group B, subgroup 5, thermal resistance, delete and substitute as follows:

*	Thermal resistance "required for qualification only"	3181	$R_{\theta JA}$ = 175°C/W max			*

PAGE 24

* TABLE IV, step 4, delete and substitute as printed below: ...

*	4. Gate trigger voltage	4221	$V_2 = V_{FBX} = 6$ V dc, $R_L = 100\Omega$	V_{FM}				*
	2N2323 through 2N2329 and 2N2323S through 2N2329S		R_e = 1 kΩ	V_{GT1} I_{GT1}	0.35 ----	0.8 200	V dc µA dc	
	2N2323A through 2N2328A and 2N2323AS through 2N2328AS		R_e = 2 kΩ	V_{GT1} I_{GT1}	0.35 ----	0.6 20	V dc µA dc	*

The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletion) from the previous amendment where made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17
NASA - NA

Review activities:
Army - MI
Navy - SH
Air Force - 85
NASA - LRC, MSF
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC, OS
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5961-1366)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.