The documentation and process conversion measures necessary to comply with this revision shall be completed by 22 June 2006.

INCH-POUND
MIL-PRF-19500/276H
22 March 2006
SUPERSEDING
MIL-PRF-19500/276G
12 May 2005

PERFORMANCE SPECIFICATION SHEET

* SEMICONDUCTOR DEVICE, THYRISTORS (CONTROLLED RECTIFIERS), SILICON, TYPES 2N2323, 2N2324, 2N2326, 2N2328, 2N2329, AND S AND U4 VERSIONS, 2N2323A, 2N2324A, 2N2326A, 2N2328A, 2N2329A, AND AS AND AU4 VERSIONS, JAN, JANTX, AND JANTXV

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for PNPN, silicon, reverse-blocking-triode thyristors. Three levels of product assurance are provided for each device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. See figures 1 (TO-39, 5) and 2 (U4).

* 1.3 Maximum ratings.

Type	V_{RM}	V_{RM} (non-rep)	V_{FBXM}	I_O (1)	I_{FSM} (2)	V_{GKM}	T_{STG}, T_J	$R_{\Theta JSP}$ max	$R_{\Theta JC}$ max	$R_{\Theta JA}$ max	Barometric pressure
	V (pk)	V (pk)	V (pk)	A dc	A(pk)	V (pk)	°C	°C/W	°C/W	°C/W	mmHg
2N2323, S, U4	50	75	50 (3)	.22	15	6	-65 to +150	6	15	175	
2N2323A, AS, AU4	50	75	50 (4)	.22	15	6					
2N2324, S, U4	100	150	100 (3)	.22	15	6					
2N2324A, AS, AU4	100	150	100 (4)	.22	15	6					
2N2326, S, U4	200	300	200 (3)	.22	15	6					
2N2326A, AS, AU4	200	300	200 (4)	.22	15	6					
2N2328, S, U4	300	400	300 (3)	.22	15	6					15
2N2328A, AS, AU4	300	400	300 (4)	.22	15	6					15
2N2329, S, U4	400	500	400 (3)	.22	15	6					15
2N2329A, AS, AU4	400	500	400 (4)	.22	15	6					15

(1) This average forward current is for an ambient temperature of 80°C and 180 electrical degrees of conduction. For other operating conditions see figure 3.
(2) Surge current is non-recurrent. The rate of rise of peak surge current shall not exceed 40 A during the first 5 μs after switching from the “off” (blocking) to the “on” (conducting) state. This is measured from the point where the thyristor voltage has decayed to 90 percent of its initial blocking value.
(3) Gate connected to cathode through 1,000 ohm resistor.
(4) Gate connected to cathode through 2,000 ohm resistor.

Comments, suggestions, or questions on this document should be addressed to Defense Supply Center, Columbus, ATTN: DSCC-VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dscc.dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

* 1.4 Primary electrical characteristics. T_C = +25°C, unless otherwise specified.

	V_{FM}	I_{HOX} (1) (2)	V_{GT} (1)	I_{GT} (1)	V_{GT} (2)	I_{GT} (2)
	I_{FM} = 4 (pk) t_p = 8.5 ms max		2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4 T_A = -65°C through +125°C		2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4 T_A= -65°C through +125°C	
	V	mA dc	V dc	µA dc	V dc	µA dc
Min			0.1		0.1	
Max	2.2	2.0	1.0	350	0.8	75

(1) Gate connected to cathode through 1,000 ohm resistor (for non-A types).
(2) Gate connected to cathode through 2,000 ohm resistor (for A types).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS


MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at http://assist.daps.dla.mil/quicksearch/ or http://assist.daps.dla.mil/ or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD	.305	.335	7.75	8.51	
CH	.240	.260	6.10	6.60	
HD	.335	.370	8.51	9.40	
LC	.200 TP		5.08 TP		6
LD	.016	.021	0.41	0.53	7, 8
LL					8, 11, 12
LU	.016	.019	0.41	0.48	7, 8
L_1		.050		1.27	7, 8
L_2	.250		6.35		7, 8
Q		.050		1.27	5
TL	.029	.045	0.74	1.14	4, 10
TW	.028	.034	0.71	0.86	3, 10
r		.010		0.25	10
α	45° TP		45° TP		6
P	.100		2.54		




NOTES:

1. Dimension are in inches.
2. Millimeters are given for general information only.
3. Beyond r (radius) maximum, TW shall be held for a minimum length of .011 (0.28 mm).
4. Dimension TL measured from maximum HD.
5. Body contour optional within zone defined by HD, CD, and Q.
6. Leads at gauge plane .054 +.001 -.000 inch (1.37 +0.03 -0.00 mm) below seating plane shall be within .007 inch (0.18 mm) radius of true position (TP) at maximum material condition (MMC) relative to tab at MMC. The device may be measured by direct methods.
7. Dimension LU applies between L_1 and L_2. Dimension LD applies between L_2 and minimum. Diameter is uncontrolled in L_1 and beyond LL minimum.
8. All three leads.
9. Lead 1 = cathode, lead 2 = gate, lead 3 = anode. The anode shall be internally connected to the case.
10. Dimension r (radius) applies to both inside corners of tab.
11. For "S" suffix devices (TO-39), dimension LL is .500 (12.70 mm) minimum, .750 (19.05 mm) maximum.
12. For "non-S" suffix devices (TO-5), dimension LL is 1.500 (38.10 mm) minimum, 1.750 (44.45 mm) maximum.
13. In accordance with ASME Y14.5M, diameters are equivalent to Φx symbology.

FIGURE 1. Physical dimensions (TO-39, 5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.



Symbol	Dimensions (U4)			
	Inches		Millimeters	
	Min	Max	Min	Max
BL	.215	.225	5.46	5.71
BW	.145	.155	3.68	3.94
CH	.049	.075	1.24	1.90
LH		.005		0.127
LW1	.135	.145	3.43	3.68
LW2	.047	.057	1.19	1.45
LL1	.115	.125	2.92	3.17
LL2	.045	.055	1.14	1.40
LS1	.070	.095	1.78	2.41
LS2	.038	.048	0.97	1.22
Q1	.045	.070	1.14	1.78
Q2	.025	.035	0.64	0.89

Terminal	
1	Anode
2	Gate
3	Cathode

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. In accordance with ASME Y14.5M, diameters are equivalent to Φx symbology.

FIGURE 2. Physical dimensions and configuration (U4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500 and as follows:

I_{FBX}	DC forward blocking current with specified conditions applied to the gate.
I_{HOX}	DC holding current with specified conditions applied to the gate.
I_{RBX}	DC reverse blocking current with specified conditions applied to the gate.
R_{GK}	External resistance between gate and cathode terminals.
V_{AA}	Anode supply voltage (dc).
V_{FBX}	Forward blocking voltage, gate connected to the specified reference terminal.
V_{GG}	Gate supply voltage.

3.4 Interface and physical dimensions. The interface and physical dimensions shall be as specified in MIL-PRF-19500 and on figure 1 and figure 2 herein.

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition specification (see 6.2).

3.4.2 Lead material. Where a choice of lead material is desired, it shall be specified in the acquisition document (see 6.2).

3.4.3 Construction. These devices shall be constructed in a manner and using materials which enable the thyristors to meet the applicable requirements of MIL-PRF-19500 and this specification.

3.5 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and tables I and II.

3.6 Electrical test requirements. The electrical test requirements shall be as specified in tables I and II.

3.7 Maximum test ratings and primary electrical characteristics. Test ratings for the devices specified herein shall be as shown in 1.3 and 1.4

3.8 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.9 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

* 4.3 Screening (JANTX and JANTXV levels). Screening shall be in accordance with appendix E, table IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table IV of MIL-PRF-19500)	Measurement JANTX and JANTXV levels
2	Optional
3a 3b	Required Not applicable
4	Optional
5	Not applicable
7a and 7b	Optional
8	Not required
9	Not applicable
10	Not applicable
11	I_{RBX1}, I_{FBX1}, V_{GT1}, I_{GT1}
12	See 4.3.1
(1) 13	Subgroup 2 of table I herein: ΔI_{RBX1} = ± 4.0 μA dc; ΔI_{FBX1} = +4.0 μA dc.
14a and 14b	Required
15	Not required
16	Not required

(1) Devices which exceed the table I limits for this test shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

4.3.1 High temperature blocking. Blocking voltage conditions are as follows: Forward blocking voltage. See figure 4, T_A = 122°C ± 3°C. t = 96 hours min.

a. V_{FBX} = 50 V dc for 2N2323, U4, S, A, AU4, AS.

b. V_{FBX} = 100 V dc for 2N2324, U4, S, A, AU4, AS.

c. V_{FBX} = 200 V dc for 2N2326, U4, S, A, AU4, AS.

d. V_{FBX} = 300 V dc for 2N2328, U4, S, A, AU4, AS.

e. V_{FBX} = 400 V dc for 2N2329, U4, S, A, AU4, AS.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 and as specified herein. If alternate screening is being performed in accordance with MIL-PRF-19500, a sample of screened devices shall be submitted to and pass the requirements of table I, subgroups 1 and 2 inspection only (table VIb, group B, subgroup 1 is not required to be performed again if group B has already been satisfied in accordance with 4.4.2).

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with appendix E, table V of MIL-PRF-19500, and table I herein.

* 4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in 4.4.2.1. Electrical measurements (end-points) shall be in accordance with the applicable steps of table II herein.

* 4.4.2.1 Group B inspection (JAN, JANTX and JANTXV).

Step	Method	Conditions
1	1037	T_A = 75°C ±5°C, I_O = 220 mA dc, see figure 3. No heatsink or forced air on the device shall be permitted. R_{GK} = 1 k ohm for 2N2323, S, U4, 2N2324, S, U4, 2N2326, S, U4, 2N2328, S, U4, 2N2329, S, U4. R_{GK} = 2 k ohm for 2N2323A, AS, AU4, 2N2324A, AS, AU4, 2N2326A, AS, AU4, 2N2328A, AS, AU4, 2N2329A, AS, AU4.
2	1027	The intermittent operation life test of step 1 shall be extended to 1,000 hours. Group B, step 2 shall not be required more than once for any single wafer lot. 45 devices, c = 0.
3	3181	$R_{\Theta JA}$ = 175°C C/W maximum (for qualification only). 22 devices, c = 0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

* 4.4.2.2 Group B sample selection. Samples selected from group B inspection shall meet all of the following requirements:

a. For JAN, JANTX, and JANTXV samples shall be selected randomly from a minimum of three wafers (or from each wafer in the lot) from each wafer lot.

b. Shall be chosen from an inspection lot that has been submitted to and passed table I, subgroup 2, conformance inspection. When the final lead finish is solder or any plating prone to oxidation at high temperature, the samples for life test group B for JAN, JANTX, and JANTXV may be pulled prior to the application of final lead finish.

c. Separate samples may be used for each step. In the event of a group B failure, the manufacturer may pull a new sample at double size from either the failed assembly lot or from another assembly lot from the same wafer lot. If the new assembly lot option is exercised, the failed assembly lot shall be scrapped.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in appendix E, table VII of MIL-PRF-19500. Electrical measurements (end-points) shall be in accordance with the applicable steps of table II herein.

4.4.3.1 Group C inspection, appendix E, table VII of MIL-PRF-19500.

Subgroup	Method	Conditions
C2	2036	Condition E. Not applicable for U4 devices.
* C5	3181	L = .375 inch (9.53 mm), $R_{\Theta JL}$ = 250°C/W maximum; $R_{\Theta JEC}$ = 100°C/W; $R_{\Theta JSP}$ =120°C/W; (see 4.3.2), 22 devices, c = 0.
C6	1037	Not applicable.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 1 2/						
Visual and mechanical examination 3/	2071	n = 45, c = 0				
Solderability 3/	2026	n = 15 leads, c = 0				
Resistance to solvents 3/ 4/	1022	n = 15, c = 0				
Temp cycling 3/	1051	Test condition F, 25 cycles. n = 22, c = 0				
Hermetic seal Fine leak Gross leak	1071	n = 22, c = 0				
Electrical measurements		Table I, subgroup 2				
Bond strength 3/	2037	Precondition T_A = +250°C at t = 24 hrs or T_A = +300°C at t = 2 hrs n = 11 wires, c = 0				
Subgroup 2						
Reverse blocking current	4211	DC method, condition B	I_{RBX1}		10	µA dc
2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4		R_2 = 1 k ohm				
2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4		R_2 = 2 k ohm				
2N2323, U4, S, A, AU4, AS 2N2324, U4, S, A, AU4, AS 2N2326, U4, S, A, AU4, AS 2N2328, U4, S, A, AU4, AS 2N2329, U4, S, A, AU4, AS		V_R = 50 V dc V_R = 100 V dc V_R = 200 V dc V_R = 300 V dc V_R = 400 V dc				

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued.						
Forward blocking current	4206	DC method, condition B	I_{FBX1}		10	µA dc
2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4		R_2 = 1 k ohm				
2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4		R_2 = 2 k ohm				
2N2323, U4, S, A, AU4, AS 2N2324, U4, S, A, AU4, AS 2N2326, U4, S, A, AU4, AS 2N2328, U4, S, A, AU4, AS 2N2329, U4, S, A, AU4, AS		V_R = 50 V dc V_R = 100 V dc V_R = 200 V dc V_R = 300 V dc V_R = 400 V dc				
Reverse gate current	4219	V_{KG} = 6 V dc	I_{KG}		200	µA dc
Gate trigger voltage and current	4221	$V_2 = V_{FBX}$ = 6 V dc; R_L = 100 ohms				
2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4		R_e = 1 k ohm	V_{GT1} I_{GT1}	0.35	0.80 200	V dc µA dc
2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4		R_e = 2 k ohm	V_{GT1} I_{GT1}	0.35	0.60 20	V dc µA dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 3						
High temperature operation:		T_A = +125°C				
Reverse blocking current	4211	DC method, condition B	I_{RBX2}		100	µA dc
2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4		R_2 = 1 k ohm				
2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4		R_2 = 2 k ohm				
2N2323, U4, S, A, AU4, AS		V_R = 50 V dc				
2N2324, U4, S, A, AU4, AS		V_R = 100 V dc				
2N2326, U4, S, A, AU4, AS		V_R = 200 V dc				
2N2328, U4, S, A, AU4, AS		V_R = 300 V dc				
2N2329, U4, S, A, AU4, AS		V_R = 400 V dc				
Forward blocking current	4206	DC method, condition B	I_{FBX2}		100	µA dc
2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4		R_2 = 1 k ohm				
2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4		R_2 = 2 k ohm				
2N2323, U4, S, A, AU4, AS		V_{FBX} = 50 V dc				
2N2324, U4, S, A, AU4, AS		V_{FBX} = 100 V dc				
2N2326, U4, S, A, AU4, AS		V_{FBX} = 200 V dc				
2N2328, U4, S, A, AU4, AS		V_{FBX} = 300 V dc				
2N2329, U4, S, A, AU4, AS		V_{FBX} = 400 V dc				

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 3 - Continued.						
Gate trigger voltage	4221		V_{GT3}	0.1		V dc
2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4		R_L = 1,000 ohm; R_e = 1 kΩ				
2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4		R_L = 100 ohm; R_e = 2 kΩ				
2N2323, U4, S, A, AU4, AS 2N2324, U4, S, A, AU4, AS 2N2326, U4, S, A, AU4, AS 2N2328, U4, S, A, AU4, AS 2N2329, U4, S, A, AU4, AS		$V_2 = V_{FBX}$ = 6 V dc				
Low temperature operation: Reverse blocking current	4211	T_A = -65°C DC method, condition B	I_{RBX3}		5	μA dc
2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4		R_2 = 1 k ohm				
2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4		R_2 = 2 k ohm				
2N2323, U4, S, A, AU4, AS 2N2324, U4, S, A, AU4, AS 2N2326, U4, S, A, AU4, AS 2N2328, U4, S, A, AU4, AS 2N2329, U4, S, A, AU4, AS		V_R = 50 V dc V_R = 100 V dc V_R = 200 V dc V_R = 300 V dc V_R = 400 V dc				

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 3 - Continued.						
Forward blocking current	4206	DC method, condition B	I_{FBX3}		5	µA dc
2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4		R_2 = 1 k ohm.				
2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4		R_2 = 2 k ohm.				
2N2323, U4, S, A, AU4, AS 2N2324, U4, S, A, AU4, AS 2N2326, U4, S, A, AU4, AS 2N2328, U4, S, A, AU4, AS 2N2329, U4, S, A, AU4, AS		V_{FBX} = 50 V dc V_{FBX} = 100 V dc V_{FBX} = 200 V dc V_{FBX} = 300 V dc V_{FBX} = 400 V dc				
Gate trigger voltage and current	4221	$V_2 = V_{FBX}$ = 6 V dc; R_L = 100 ohms				
2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4		R_e = 1 k ohm	V_{GT2} I_{GT2}		1.0 350	V dc µA dc
2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4		R_e = 2 k ohm	V_{GT2} I_{GT2}		0.8 75	V dc µA dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 4						
Exponential rate of voltage rise	4231	T_A = 125°C, condition B, 50 ohms ≤ R_L ≤ 400 ohms, C = 0.1 to 1.0 μF, repetition rate = 60 pps, test duration = 15 seconds	V_{FBX}			
2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4		dv/dt = 1.8 V/μs, R_3 = 1 k ohm				
2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4		dv/dt = 0.7 V/μs, R_3 = 2 k ohm				
2N2323, U4, S, A, AU4, AS 2N2324, U4, S, A, AU4, AS 2N2326, U4, S, A, AU4, AS 2N2328, U4, S, A, AU4, AS 2N2329, U4, S, A, AU4, AS		V_{AA} = 50 V dc V_{AA} = 100 V dc V_{AA} = 200 V dc V_{AA} = 300 V dc V_{AA} = 400 V dc		47 95 190 285 380		V dc V dc V dc V dc V dc
Forward on voltage	4226	I_{FM} = 4 A(pk) (pulse), pulse width = 8.5 ms, max; duty cycle = 2 percent max	V_{FM}		2.2	V (pk)
Holding current	4201	Condition B, V_{AA} = 24 V dc max, I_{F1} = 100 mA dc, I_{F2} = 10 mA dc, gate trigger source voltage = 6 V dc, trigger pulse width = 25 μs minimum, R_2 = 330 ohms	I_{HOX}		2.0	mA dc
2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4		R_3 = 1 k ohm				

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 4 - Continued.						
2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4		R_3 = 2 k ohm				
2N2323, U4, S, A, AU4, AS		V_R = 50 V dc				
2N2324, U4, S, A, AU4, AS		V_R = 100 V dc				
2N2326, U4, S, A, AU4, AS		V_R = 200 V dc				
2N2328, U4, S, A, AU4, AS		V_R = 300 V dc				
2N2329, U4, S, A, AU4, AS		V_R = 400 V dc				
Subgroup 5						
Not applicable						
Subgroup 6						
Surge current	4066	See figure 8; T_A = 122°C, I_{FM} = 15 A; 10 surges, 1 per minute, I_O = 0 at rated V_{RWM}, f = 60 Hz				
Electrical end-point measurements		See table II, steps 1, 2, 3, and 4				
Subgroup 7						
Nonrepetitive peak voltage		See figure 9, 10 pulses.				
2N2323, U4, S, A, AU4, AS		V_{RM} = 75 V dc				
2N2324, U4, S, A, AU4, AS		V_{RM} = 150 V dc				
2N2326, U4, S, A, AU4, AS		V_{RM} = 300 V dc				
2N2328, U4, S, A, AU4, AS		V_{RM} = 400 V dc				
2N2329, U4, S, A, AU4, AS		V_{RM} = 500 V dc				
Electrical end-point measurements		See table II, steps 1, 2, 3, and 4				

1/ For sampling plan see MIL-PRF-19500.
2/ For resubmission of failed table I, subgroup 1, double the sample size of the failed test or sequence of tests. A failure in table I, subgroup 1 shall not require retest of the entire subgroup. Only the failed test shall be rerun upon submission.
3/ Separate samples may be used.
4/ Not required for laser marked devices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

* TABLE II. Groups A, B, and C electrical (end-point) measurements. 1/ 2/ 3/

Step	Inspection	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1.	Reverse blocking current 2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4 2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4 2N2323, U4, S, A, AU4, AS 2N2324, U4, S, A, AU4, AS 2N2326, U4, S, A, AU4, AS 2N2328, U4, S, A, AU4, AS 2N2329, U4, S, A, AU4, AS	4211	DC method, condition B R_2 = 1 k ohm R_2 = 2 k ohm V_R = 50 V dc V_R = 100 V dc V_R = 200 V dc V_R = 300 V dc V_R = 400 V dc	I_{RBX1}		10	µA dc
2.	Forward blocking current 2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4 2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4 2N2323, U4, S, A, AU4, AS 2N2324, U4, S, A, AU4, AS 2N2326, U4, S, A, AU4, AS 2N2328, U4, S, A, AU4, AS 2N2329, U4, S, A, AU4, AS	4206	DC method, condition B R_2 = 1 k ohm R_2 = 2 k ohm V_{FBX} = 50 V dc V_{FBX} = 100 V dc V_{FBX} = 200 V dc V_{FBX} = 300 V dc V_{FBX} = 400 V dc	I_{FBX1}		10	µA dc
3.	Forward on voltage	4226	I_{FM} = 4A(pk) (pulse), pulse width = 8.5 ms, max; duty cycle = 2 percent max	V_{FM}		2.2	V (pk)

See footnotes at end of table.


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

* TABLE II. Groups A, B, and C electrical (end-point) measurements - Continued. 1/ 2/ 3/

Step	Inspection	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
4.	Gate trigger voltage	4221	$V_2 = V_{FBX} = 6$ V dc; $R_L = 100$ ohms				
	2N2323, S, U4 2N2324, S, U4 2N2326, S, U4 2N2328, S, U4 2N2329, S, U4		$R_e = 1$ k ohm	V_{GT1} I_{GT1}	0.35	0.80 200	V dc μA dc
	2N2323A, AS, AU4 2N2324A, AS, AU4 2N2326A, AS, AU4 2N2328A, AS, AU4 2N2329A, AS, AU4		$R_e = 2$ k ohm	V_{GT1} I_{GT1}	0.35	0.60 20	V dc μA dc

1/ The electrical measurements for table V of MIL-PRF-19500, appendix E, are as follows: Subgroups 6 and 7, see table II herein, steps 1, 2, 3, and 4.
2/ The electrical measurements for 4.4.2.1 are as follows:
  a. Step 1, see table II herein, steps 1, 2, 3, and 4.
  b. Step 2, see table II herein, steps 1, 2, 3, and 4.
3 The electrical measurements for appendix E, table VII of MIL-PRF-19500 are as follows:
  a. Subgroup 2, see table II herein, steps 1, 2, 3, and 4.
  b. Subgroup 3, see table II herein, steps 1, 2, 3, and 4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.




Test circuit details: The test circuit used must provide one of the waveforms shown. When a large number of devices are to be tested, they may be connected in parallel or series combinations with suitable provisions (resistive, reactive, etc, methods) for proper division of forward current or blocking voltages. Suitable protective elements should be used to isolate defective devices without interrupting the test and to protect the remaining devices on test. The forward current supply shall consist of a low-voltage transformer with a means of adjusting the secondary voltage. It shall supply 22 mA dc average forward current to each device under test. The gate supply shall be in phase with the forward current supply. The average power input shall not be allowed to exceed .01 watt per device.

Operating conditions: The devices shall be subjected to the following operational conditions:

a. Power sources are to be 60 Hz sinusoidal waveform sources.
b. The conduction angle of I_O shall be 150 degrees to 180 degrees.
c. The rated forward or reverse blocking voltage shall be started during the nonconducting half cycle no later than 5 degrees after conduction has ceased. For waveform A, the IRC time constant of the blocking voltage shall be 200 ±100 microseconds.
d. For accelerated steady-state operation, blocking voltage shall be equal to or greater than 30 V.
e. The duration of the blocking voltages shall be 175 ±5 degrees.
f. Ambient test temperature shall be 75 ±5°C.


FIGURE 3. Test circuit and waveforms for intermittent operation life test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.




Procedure: Adjust the power supply to the specified value for the device under test.
NOTE: Rate of rise of voltage must be limited to values specified in table I.

FIGURE 4. Blocking-voltage test.



Procedure: The above waveform shall be applied to the devices under test. During this test, the gate shall be connected to the anode through a suitable firing resistor and series diode or fired by an equivalent method. The device shall be operated at the specified maximum reverse voltage and specified temperature in a single phase circuit with a 60 Hz supply and a resistive load. The total peak device current during the surge shall be 15 amperes.

FIGURE 5. Surge current waveform.



Procedure: Adjust potentiometer to achieve the specified voltage across the device under test. Timing sequence of firing circuit is: Apply trigger pulse to CR2 once every 15 seconds, apply trigger pulse to CR1, 5.0 ±1.0 milliseconds after firing CR2. The specified number of pulses shall be applied. Alternate circuits shall apply rectangular pulses of 5.0 ±1.0 milliseconds with a maximum rise and fall time of 50 microseconds.

FIGURE 6. Nonrepetitive peak reverse voltage test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

5. PACKAGING

* 5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The notes specified in MIL-PRF-19500 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead material and finish (see 3.4.1 and 3.4.2).

d. Product assurance level and type designator.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center, Columbus, ATTN: DSCC/VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil.

6.4 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5961-2005-028)

Review activities:
Army - MI, SM
Navy - AS, MC, OS
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:01Z
Check the source to verify that this is the current version before use.