MILITARY SPECIFICATION

SEMICONDUCTOR DEVICES, THYRISTOR (CONTROLLED RECTIFIER), SILICON TYPES 2N3091, 2N3093, 2N3095, 2N3097, 2N3098, 2N3099, 2N3101, 2N3103 2N3105, and 2N3106

This amendment forms a part of Military Specification MIL-S-19500/280A(EC), dated 6 January 1978, and is approved for use by the Naval Electronic Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 1.2, Characteristic, Holding current, Max column: Delete "40" and substitute "60".

PAGE 9

* TABLE I, Holding current, Max limits column: Delete "40" and substitute "60".

PAGE 10

TABLE II, subgroup 1: After the "Forward blocking current" test, add the following new end points.

*

Examination or test	MIL-STD-750		LTPD	Limits			
	Method	Details		Symbol	Min	Max	Unit
Gate trigger voltage and gate trigger current	4221	V_2 = 6.0 V dc R_L = 10 ohms R_F = 20 ohms		V_{GT} I_{GT}	--- 5	3.0 70.0	V dc mA dc
On state voltage	4226	I_{TM} = 220 A dc pulse width = 8.5 ms duty cycle = 2 max		V_{TM}		1.7	V (pk)

"

PAGE 11

TABLE II, subgroup 4: Delete "Gate trigger voltage and gate trigger current" and "On state voltage" tests and all accompanying data.

NOTE: The margin of this amendment is marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any innaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Navy - EC

Preparing Activity:
Navy - EC

User activities:
Navy - AS, CG, MC, OS, SH

Agent:
DLA - ES

Project 5961-N565

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T14:03Z
Check the source to verify that this is the current version before use.