INCH-POUND

MIL-PRF-27/47C
w/AMENDMENT 3
24 March 2022
SUPERSEDING
MIL-PRF-27/47C
AMENDMENT 2
31 May 2019

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 25 VOLT AMPERES, 400 HZ ELECTROSTATIC SHIELDED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the transformer described herein shall consist of this specification sheet and MIL-PRF-27.




FIGURE 1. Dimensions and configurations

AMSC N/A FSC 5950

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:17Z
Check the source to verify that this is the current version before use.

Dim	Inches	mm
A	1.40 MAX	35.6 MAX
B	1.100	27.94
C	.900	22.86
D	.032 ±.002	0.81 ±.0508
E	.25 .13	6.4 3.3
F	1.20 MAX	30.48 MAX

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Tolerance on terminal position dimensions is ±.005 (0.13 mm).
4. Marking shall be on the side of the case.
5. A white dot shall be marked on the side opposite the terminals, over terminal 1, in addition to the terminal marking shown.
6. Secondary electrical values shall be marked as specified in table I, as applicable.

FIGURE 1. Dimensions and configurations – continued.

REQUIREMENTS: (When numbers in parentheses, such as (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings: See table I.

Primary voltage (1-2): 115 volts ±10 percent, 400 Hz ±5 percent.

Design and construction:

Dimensions and configuration: See figure 1.

Weight: 4.4 ounces, maximum.

Duty cycle: Continuous.

Case: Plastic encapsulated.

Material: Plastic.

Altitude: 70,000 feet, maximum.

Operating temperature range: -55˚C to +130˚C.

Terminals: Printed circuit pins – tinned brass.

Terminal strength: MIL-STD-202-211, test condition A, 2 pounds.

Dielectric withstanding voltage:

At sea level: 2.8 times the maximum working voltage specified in table I.

At reduced barometric pressure: 1.25 times the maximum working voltage specified in table I.

Electrical characteristics:

No load: With 115 volts rms, 400 Hz across (1-2): Current in (1-2) shall not exceed 25 mA rms.

Rated load: With 115 volts, 400 Hz across (1-2) and a resisitive load with current as specified in table I in (3-5), the voltage across (3-5) shall be as specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:17Z
Check the source to verify that this is the current version before use.

Efficiency: 88 percent minimum at rated load.

Electrostatic shielding: The voltage ratio shall be a minimum of 5 to 1 at 20 kHz.

Polarity: Additive with terminals 2 and 3 connected.

Regulation: $\frac{\text{Voltage (no Load) - Voltage (rated load)}}{\text{Voltage (rated load)}} \times 100$

shall not exceed 7 percent.

Phase shift: 1.0 electrical degree between primary and secondary voltage at rated load, maximum.

Temperature rise: 45°C, maximum.

Vibration: MIL-STD-202-204, test condition D.

Marking location: See figure 1.


VERIFICATION

Extent of qualification

Qualification testing and approval to M27/37-44 A or B, M27/42-44 A or B, and M27/46-44 A or B shall be sufficient to grant qualification approval to MIL-PRF-27/37 through MIL-PRF-27/47 inclusive, all parts.

Qualification testing and approval to M27/47-44 shall be sufficient to grant qualification approval to M27/47-01 through M27/47-44.

Part or Identifying Number (PIN), example:



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:17Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings.

Dash No.	Secondary voltage (3-5) (V rms) ±3%	Secondary current (3-5) (amps rms)	Working voltage (V rms) (MAX)
01 A or B	6	4.167	325
02 A or B	6.3	3.968	325
03 A or B	7	3.571	325
04 A or B	7.5	3.333	325
05 A or B	8	3.125	325
06 A or B	9	2.778	325
07 A or B	10	2.500	325
08 A or B	11	2.273	325
09 A or B	12	2.083	325
10 A or B	12.6	1.984	325
11 A or B	13	1.923	325
12 A or B	15	1.667	325
13 A or B	16	1.563	325
14 A or B	18	1.389	325
15 A or B	20	1.250	325
16 A or B	22	1.136	325
17 A or B	24	1.042	325
18 A or B	26	0.962	325
19 A or B	28	0.893	325
20 A or B	30	0.833	325
21 A or B	33	0.758	325
22 A or B	36	0.694	325
23 A or B	39	0.641	325
24 A or B	43	0.581	325
25 A or B	47	0.532	325
26 A or B	51	0.490	325
27 A or B	56	0.446	325
28 A or B	62	0.403	325
29 A or B	68	0.367	325
30 A or B	75	0.333	325
31 A or B	82	0.305	325
32 A or B	91	0.275	325
33 A or B	100	0.250	325
34 A or B	110	0.227	325
35 A or B	115	0.218	325
36 A or B	120	0.208	325
37 A or B	130	0.192	325
38 A or B	150	0.166	325
39 A or B	180	0.139	325
40 A or B	200	0.125	440
41 A or B	220	0.113	440
42 A or B	240	0.104	440
43 A or B	270	0.093	580
44 A or B	300	0.083	580

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:17Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-27, this document references the following:

MIL-PRF-27/37	MIL-PRF-27/38	MIL-PRF-27/39	MIL-PRF-27/40	MIL-PRF-27/41	MIL-PRF-27/42
MIL-PRF-27/43	MIL-PRF-27/44	MIL-PRF-27/45	MIL-PRF-27/46	MIL-STD-202-204	MIL-STD-202-211

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5950-2022-027)

Review activities:
Army - CR4, MI
Navy - AS, MC, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:17Z
Check the source to verify that this is the current version before use.