INCH-POUND


MIL-PRF-27/56G
w/AMENDMENT 2
8 April 2022
SUPERSEDING
MIL-PRF-27/56G
w/AMENDMENT 1
25 March 2016

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 25 VOLT AMPERES, 400 HZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the transformers described herein shall consist of this specification and MIL-PRF-27.



(SEE TABLE I FOR VALUE OF "X"

CIRCUIT DIAGRAM AND MARKING

CONFIGURATION A


FIGURE 1. Dimensions and configuration.

AMSC N/A
FSC 5950

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:21Z
Check the source to verify that this is the current version before use.

LTR	Dimensions (Configuration A)	
	Inches	mm
A	.234 DIA MAX	5.94 DIA MAX
B	.250	6.35
C	.125	3.18
D	1.000 ±.031	25.40 ±.0.79
E	.312 MAX	7.92 MAX
F	.344 ±.031	8.74 ±0.79
G	1.375 ±.031	34.92 ±0.79
H	1.375 ±.031	34.92 ±0.79
J	0.097 MAX	2.46 MAX



CONFIGURATION B

FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:21Z
Check the source to verify that this is the current version before use.

LTR	Dimensions (Configuration B)	
	Inches	mm
A	.234 DIA MAX	5.94 DIA MAX
B	.250	6.35
C	.125	3.18
D	1.000 ±.031	25.40 ±.0.79
E	.312 MAX	7.92 MAX
F	.344 ±.031	8.74 ±0.79
G	1.375 ±.031	34.92 ±0.79
J	0.097 MAX	2.46 MAX
K	1.125 ±.031	28.58 ±0.79

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Tolerance on terminal position dimensions is ±.015 (0.38 mm).
4. Marking shall be on the side of the case.
5. Terminals are color coded for permanent identification in addition to terminal marking shown.
6. Secondary electrical values shall be marked as specified in table I, as applicable.

FIGURE 1. Dimensions and configuration - Continued.

REQUIREMENTS: (When numbers in parentheses i.e. (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings: See table I.

Primary voltage (1-2): 115 volts ±10 percent, 400 Hz ±5 percent.

Design and construction:

Dimensions and configuration: See figure 1.

Weight: 4.95 ounces, maximum.

Duty cycle: Continuous.

Case: Metal enclosed (configuration A) or epoxy fiberglass enclosed (configuration B).

Material: Steel (configuration A) or epoxy fiberglass (configuration B).

Altitude: 70,000 feet, maximum.

Operating temperature range: -55°C to +130°C maximum.

Terminals: Feed thru.

Terminal height: .312 inch (7.92 mm), maximum.

Terminal strength: MIL-STD-202-211, test condition A, 5 pounds.

Dielectric withstanding voltage:

At sea level: 2.8 times the maximum working voltage specified in table I.

At reduced barometric pressure: 1.25 times the maximum working voltage specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:21Z
Check the source to verify that this is the current version before use.

Electrical characteristics:

No load: With 115 volts, 400 Hz across (1-2): Current in (1-2) shall not exceed 25 mA rms.

Rated load: With 115 volts, 400 Hz across (1-2) and a resistive load with current as specified in table I in (3-5), the voltage across (3-5) shall be as specified in table I.

Efficiency: 88 percent minimum at rated load.

Polarity: Additive with terminals 2 and 3 connected.

Regulation: $\frac{Voltage\ (no\ load) - Voltage\ (rated\ load)}{Voltage\ (rated\ load)} \quad x \quad 100$

Shall not exceed 7 percent.

Phase shift: 1.0 electrical degree between primary and secondary voltage at rated load, maximum.

Temperature rise: 45°C, maximum with 115 volts, 400 Hz across (1-2) at ambient temperature of 85°C.

Vibration: MIL-STD-202-204, test condition D.

Marking location: See figure 1.

VERIFICATION:

Extent of qualification:

Qualification testing and approval to M27/49-44 A or B, M27/51-44 A or B, M27/53-44 A or B, M27/56-44 and M27/66-27 shall be sufficient to grant qualification approval to MIL-PRF-27/48 through MIL-PRF-27/66 inclusive, all parts.

Qualification testing and approval to M27/56-44 shall be sufficient to grant qualification approval to M27/56-01 through M27/56-44. Qualification testing and approval to M27/56-88 shall be sufficient to grant qualification approval to M27/56-45 through M27/56-88.

Part or Identifying Number (PIN) example:

M	27/56	-01
MIL specification item	Specification sheet no.	Dash no.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:21Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings.

Dash number	Secondary voltage (3-5) (V rms) ±3%	Secondary current (3-5) (amps rms)	Working voltage (V rms max)	Configuration
01	6	4.167	325	A
02	6.3	3.968	325	A
03	7	3.571	325	A
04	7.5	3.333	325	A
05	8	3.125	325	A
06	9	2.778	325	A
07	10	2.500	325	A
08	11	2.273	325	A
09	12	2.083	325	A
10	12.6	1.984	325	A
11	13	1.923	325	A
12	15	1.667	325	A
13	16	1.563	325	A
14	18	1.389	325	A
15	20	1.250	325	A
16	22	1.136	325	A
17	24	1.042	325	A
18	26	0.962	325	A
19	28	0.893	325	A
20	30	0.833	325	A
21	33	0.758	325	A
22	36	0.694	325	A
23	39	0.641	325	A
24	43	0.581	325	A
25	47	0.532	325	A
26	51	0.490	325	A
27	56	0.446	325	A
28	62	0.403	325	A
29	68	0.367	325	A
30	75	0.333	325	A
31	82	0.305	325	A
32	91	0.275	325	A
33	100	0.250	325	A
34	110	0.227	325	A
35	115	0.218	325	A
36	120	0.208	325	A
37	130	0.192	325	A
38	150	0.166	325	A
39	180	0.139	325	A
40	200	0.125	440	A
41	220	0.113	440	A
42	240	0.104	440	A
43	270	0.093	580	A
44	300	0.083	580	A

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:21Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings - Continued.

Dash number	Secondary voltage (3-5) (V rms) ±3%	Secondary current (3-5) (amps rms)	Working voltage (V rms max)	Configuration
45	6	4.167	325	B
46	6.3	3.968	325	B
47	7	3.571	325	B
48	7.5	3.333	325	B
49	8	3.125	325	B
50	9	2.778	325	B
51	10	2.500	325	B
52	11	2.273	325	B
53	12	2.083	325	B
54	12.6	1.984	325	B
55	13	1.923	325	B
56	15	1.667	325	B
57	16	1.563	325	B
58	18	1.389	325	B
59	20	1.250	325	B
60	22	1.136	325	B
61	24	1.042	325	B
62	26	0.962	325	B
63	28	0.893	325	B
64	30	0.833	325	B
65	33	0.758	325	B
66	36	0.694	325	B
67	39	0.641	325	B
68	43	0.581	325	B
69	47	0.532	325	B
70	51	0.490	325	B
71	56	0.446	325	B
72	62	0.403	325	B
73	68	0.367	325	B
74	75	0.333	325	B
75	82	0.305	325	B
76	91	0.275	325	B
77	100	0.250	325	B
78	110	0.227	325	B
79	115	0.218	325	B
80	120	0.208	325	B
81	130	0.192	325	B
82	150	0.166	325	B
83	180	0.139	325	B
84	200	0.125	440	B
85	220	0.113	440	B
86	240	0.104	440	B
87	270	0.093	580	B
88	300	0.083	580	B

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:21Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-27, this document references the following:

MIL-PRF-27/48 MIL-PRF-27/49 MIL-PRF-27/50 MIL-PRF-27/51 MIL-PRF-27/52 MIL-PRF-27/54
MIL-PRF-27/55 MIL-PRF-27/57 MIL-PRF-27/58 MIL-PRF-27/59 MIL-PRF-27/60 MIL-PRF-27/61
MIL-PRF-27/62 MIL-PRF-27/63 MIL-PRF-27/64 MIL-PRF-27/65 MIL-PRF-27/66 MIL-STD-202-204
MIL-STD-202-211

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA - CC

Review activities:
Army – CR4, MI
Navy – AS, MC, OS
Air Force – 19

Preparing activity:
DLA - CC

(Project 5950-2022-036)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of this information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:21Z
Check the source to verify that this is the current version before use.