NOT MEASUREMENT SENSITIVE

MIL-DTL-15665/12L
3 February 2021
SUPERSEDING
MIL-DTL-15665/12K
26 April 2019

DETAIL SPECIFICATION SHEET

INSIGNIA, COLLAR, ENLISTED, AND CAP, GARRISON, U.S. MARINE CORPS

This specification is approved for use by all
Departments and Agencies of the Department of Defense


The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-15665.



RIGHT HAND



LEFT HAND



DASH NO.
-1: Collar Gold (See Note 3)
-2: Collar Black (See Note 3)
-3: Cap, Garrison, Gold (See Note 4)
-4: Cap, Garrison, Black (See Note 4)

MATERIAL:
-1, -3: Red Brass 85/15 (UNS Alloy No. C- 230)
-2, -4: Red Brass 85/15 (UNS Alloy No. C- 230) or Zinc Aluminum

FINISH:
-1, -3: 24K Gold Plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.

-2, -4: Flat Black Enamel and shall match TIOH metal Finish Chip Number 21.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:30Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT (Overall): 1 inch (REF)
WIDTH (Overall): 15/16 inch (REF)
THICKNESS (Minimum): 0.040 inch ± 0.005 inch

ATTACHING DEVICE:
1. The attaching device shall be a screw post with nut.

2. The screw post shall be 3/8 inch ± 1/32 inch long, 1/8 inch in diameter and shall have a No. 5-40 UNC-2A thread. The thumb nut shall be 0.625 inch ± 0.010 inch or 0.500 inch ± 0.010 inch in diameter and shall have a No. 5-40 UNC-2B thread.

3. The screw post shall be soldered or electronically fused the insignia in the center of the globe as indicated.

4. The registering prong shall be 3/16 inch ± 1/64 inch in length and 0.032 inch ± 0.002 inch in diameter. The prong shall be fused or soldered on the vertical center line on the back of the eagle's breast.

NOTES:
1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. Forcers shall be used to bring up the design.

3. For -1 and -2 shall be made in pairs (one left hand and one right hand).

4. Dash Numbers -3 and -4 shall be the left hand insignia only.

5. Flat black enamel for -2 and -4 shall match TIOH metal Finish Chip Number 21.

6. Trimming on both sides of the eagle's head to be accomplished without altering or distorting the design detail.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Navy - MC

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2021-164)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T06:30Z
Check the source to verify that this is the current version before use.