INCH-POUND
MIL-DTL-32460B
SUPPLEMENT 1
10 March 2020

DETAIL SPECIFICATION

ADAPTER, HYDRAULIC AND PNEUMATIC, 37 DEGREE FLARE TUBE FITTING TO O-RING FACE SEAL CONNECTORS, 1500 TO 3000 PSI AND -65°F TO 250°F, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-32460, dated 10 March 2020.

SPECIFICATION SHEETS

MIL-DTL-32460/1	-	Fitting, Adapter, Straight, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS Male
MIL-DTL-32460/2	-	Fitting, Adapter, 45 Degree Elbow, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS Male
MIL-DTL-32460/3	-	Fitting, Adapter, 90 Degree Elbow, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS Male
MIL-DTL-32460/4	-	Fitting, Adapter, Straight, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS Bulkhead
MIL-DTL-32460/5	-	Fitting, Adapter, 45 Degree Elbow, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS Bulkhead
MIL-DTL-32460/6	-	Fitting, Adapter, 90 Degree Elbow, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS Bulkhead
MIL-DTL-32460/7	-	Fitting, Adapter, Straight, Hydraulic and Pneumatic,37 Degree Flare, Male to ORFS, Female Swivel
MIL-DTL-32460/8	-	Fitting, Adapter, 45 Degree Elbow, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS, Female Swivel
MIL-DTL-32460/9	-	Fitting, Adapter, 90 Degree Elbow, Hydraulic and Pneumatic, 37 Degree Flare, Male to ORFS, Female Swivel

CONCLUDING MATERIAL

Custodians:
Army - AT
Navy - AS
Air Force - 71
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Army - AR
Navy - CG, SA, SH

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A

FSC 4730

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:26Z
Check the source to verify that this is the current version before use.