NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND


MIL-PRF-27/339D
22 January 1992
SUPERSEDING
MIL-T-27/339C
17 January 1986


PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 6 VOLTAMPERES, 400 HZ, TF5S03ZZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-T-27.





(SEE TABLE I FOR VALUE OF "X")
CIRCUIT DIAGRAM

Inches	mm
.005	0.13
.010	0.25
.031	0.79
.062	1.57
.094	2.39
.116	2.95
.125	3.18
.169	4.29
.187	4.75
.250	6.35
.375	9.53

Ltr	Dimensions	
	Inches	mm
G	1.25 ±.015	31.8 ±0.38
H	1.19 ±.015	30.2 ±0.38
J	.88 ±.015	22.4 ±0.38
K	.94 ±.015	23.9 ±0.38
L	1.00 ±.015	25.4 ±0.38
M	.250 ±.031	6.35 ±0.79

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information.
3. Marking shall be on the top and sides of case.
4. Dimensional tolerance shall be ±.031 unless otherwise specified.
5. Dimensions G and H to be measured at top of transformer.

FIGURE 1. Dimensions and configuration.

(D) denotes changes

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:16Z
Check the source to verify that this is the current version before use.

REQUIREMENTS (When numbers in parentheses, i e., (1-2) are used, they indicate the winding and the extreme terminals of the winding)

Electrical ratings·

Primary voltage (1-2) 115 volts rms, 400 ±20 hertz

Secondary voltage and current (3-5) See table I

Voltampere 6 voltamperes

Working voltage (1-2). 535 volts peak

Design and construction

Dimensions and configuration See figure 1

Duty cycle Continuous

Case Encapsulated

Material Diallyl phthalate

Terminals Turret type

Height 169 inch

Weight 15 pound, maximum

Operating temperature range -55°C to +130°C

Altitude 70,000 feet

Terminal strength MIL-STD-202, method 211, test condition A, 2 pounds

Dielectric withstanding voltage (each winding)

At sea level 1500 volts rms

At reduced barometric pressure 1 25 times the peak working voltage specified

Electrical characteristics:

Rated load With 115 volts rms and 400 Hz in (1-2), and rated current in secondary, the voltage across (3-5) shall be as specified in table I

Source: https://assist.dla.mil -- Downloaded: 202610-16T04:16Z
Check the source to verify that this is the current version before use.

DC resistance

(1-2) 61 ohms ±25 percent

(3-5) See table I

Temperature rise. 45°C with 115 volts rms, 400 hertz across (1-2) at an ambient temperature of 85°C, full load terminals (3-5).

$$\text{Regulation} \quad \frac{\text{Voltage (no load)} - \text{Voltage (rated load)}}{\text{Voltage (rated load)}} \times 100 \quad \text{(Shall not exceed 10 percent)}$$

Polarity Additive, with terminals 2 and 3 connected

Marking location See figure 1

Part or Identifying Number (PIN) M27/339-(dash number from table I)

TABLE I Electrical ratings

Dash number M27/339	Secondary voltage (3-5) (V rms) ±5% (CT)	Secondary current (3-5) (amperes)	Secondary DCR (3-5) (ohms) ±25%
-01	5 0	1 2	173
-02	6 3	95	24
-03	8 0	75	396
-04	10 0	60	587
-05	12 6	475	99
-06	14 0	428	1 11
-07	16 0	375	1 58
-08	18 0	333	2 21
-09	20 0	300	2 78

Source: https://assist.dla.mil -- Downloaded: 202640-16T04:16Z
Check the source to verify that this is the currentversion before use.

TABLE I Electrical ratings - Continued

Dash number M27/339	Secondary voltage (3-5) (V rms) ±5% (CT)	Secondary current (3-5) (amperes)	Secondary DCR (3-5) (ohms) ±25%
-10	22 0	273	2 8
-11	25 0	240	3 6
-12	28 0	214	4.2
-13	31 0	192	5 71
-14	35 0	171	6 89
-15	39 0	154	9 39
-16	43 0	139	10 25
-17	48 0	125	15 30
-18	55 0	109	17 30
-19	63 0	.095	24 9
-20	70 0	085	27 1
-21	80 0	075	39 0
-22	90 0	067	41 0
-23	100 0	060	59 5
-24	110 0	054	68 5
-25	123 0	048	96 0
-26	138 0	043	133 0
-27	157 0	038	153 0
-28	175 0	034	168 0
-29	200 0	030	248 0
-30	220 0	027	278 0
(D) -31	26 0	231	3 74
(D) -32	115 0	052	65 10

Source: https://assist.dla.mil -- Downloaded: 202610-16T04:16Z
Check the source to verify that this is the current version before use.

QUALITY ASSURANCE PROVISIONS

Extent of qualification

(D) Qualification testing and approval to M27/338-28 and M27/343-32 shall be sufficient to grant qualification approval to MIL-T-27/338 through MIL-T-27/343 inclusive, all parts.

(D) Qualification testing and approval to M27/339-32 shall be sufficient to grant qualification approval to M27/339-01 through M27/339-32

CONCLUDING MATERIAL

Custodians.
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - AR
Navy - OS
Air Force - 11, 17, 99
DLA - ES

User activities
Army - ME
Navy - AS, MC
Air Force - 19

Preparing activity.
Army - ER

Agent
DLA - ES

(Project 5950-0774)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:16Z
Check the source to verify that this is the current version before use.