
INCH-POUND
MIL-PRF-27/342F
AMENDMENT 1
9 March 2018
SUPERSEDING
MIL-PRF-27/342F
18 October 2005

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 80 VOLTAMPERES, 400 HZ

This specification is approved for use by all Departments and agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-27.




DASH NUMBERS 01, 02, AND 03

FIGURE 1. Dimensions and configurations.

AMSC N/A

FSC 5950

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:17Z
Check the source to verify that this is the current version before use.



DASH NUMBERS 04 THROUGH 32

FIGURE 1. Dimensions and configurations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:17Z
Check the source to verify that this is the current version before use.

	Inches	mm
A	.500	12.7
B	.068 MIN DIA .090 MAX DIA	1.73 MIN DIA 2.29 MAX DIA
C	.250	6.35
D	.200	6.08
E	.169 ±.005 DIA THRU HOLE (2 PLACES)	4.29 ±0.13 DIA THRU HOLE (2 PLACES)
F	.250	6.35
G	2.31 ±.015	58.7 ±.0.38
H	1.52 ±.015	38.6 ±.0.38
J	1.75 ±.015	44.5 ±.0.38
K	1.02 ±.015	25.9 ±.0.38
L	1.81 ±.015	46.0 ±.0.38
M	.500 ±.031	12.70 ±.0.79
N	.750 ±.031	19.05 ±.0.79
O	.115 ±.010 DIA	2.92 ±0.25 DIA
P	.380 MAX	8.89 MAX
Q	.500 TYP	12.7 TYP
R	.200 MAX	6.08
S	.068 MIN DIA .090 MAX DIA	1.73 MIN DIA 2.29 MAX DIA
T	.187	4.75
U	.250 TYP	6.35 TYP

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking shall be on the top and sides of the case.
4. Dimensional tolerance shall be ±.031 (0.79 mm) unless otherwise specified.
5. Dimensions G and H to be measured at top of transformer.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:17Z
Check the source to verify that this is the current version before use.

REQUIREMENTS: (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings:

Primary voltage (1-2): 115 volts rms, 400 ±20 hertz.

Secondary voltage and current (3-5): See table I.

Volt-ampere: 80 voltamperes.

Working voltage (1-2): 535 volts peak.

Design and construction:

Dimensions and configuration: See figure 1.

Duty cycle. Continuous.

Case: Encapsulated.

Material: Epoxy fiberglass or diallyl phthalate.

Terminals: Turret type.

Height: See figure 1.

Weight: 0.80 pound, maximum.

Operating temperature range. -55° to +130°C.

Altitude: 70,000 feet.

Terminal strength: MIL-STD-202-211, test condition A, 2.0 pounds.

Dielectric withstanding voltage (each winding):

At sea level: 1500 volts rms.

At reduced barometric pressure: 1.25 times the peak working voltage specified.

Electrical characteristics:

Rated load: With 115 volts rms and 400 Hz in (1-2), and rated current in secondary, the voltage across (3-5) shall be as specified in table I.

DC resistance:

(1-2): 2.0 ohms ±25 percent.

(3-5): See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:17Z
Check the source to verify that this is the current version before use.

Temperature rise: 45°C with 115 volts rms, 400 hertz across (1-2) at an ambient temperature of 85°C, full load terminals (3-5).

Regulation: $\frac{Voltage\ (no\ load) - Voltage\ (rated\ load)}{Voltage\ (rated\ load)}\ x\ 100$

Shall not exceed 10 percent.

Polarity: Additive with terminals 2 and 3 connected.

Marking location: See figure 1.

Part or Identifying Number (PIN): M27/342-(dash number from table I).

TABLE I. Electrical ratings.

Dash number M27/342-	Secondary voltage (3-5) (V rms) ±5% (CT)	Secondary current (3-5) (amperes)	Secondary DCR (3-5) (ohms) ±25%
01	5.0	16.0	.009
02	6.3	12.8	.016
03	8.0	10.0	.017
04	10.0	8.0	.030
05	12.6	6.35	.030
06	14.0	5.6	.040
07	16.0	5.0	.050
08	18.0	4.45	.080
09	20.0	4.0	.090
10	22.0	3.63	.120
11	25.0	3.2	.130
12	28.0	2.85	.140
13	31.0	2.47	.180
14	35.0	2.28	.280
15	39.0	2.05	.320
16	43.0	1.86	.350
17	48.0	1.66	.400
18	55.0	1.45	.670
19	63.0	1.27	.710
20	70.0	1.14	.800
21	80.0	1.0	.920
22	90.0	.89	1.08
23	100.0	.80	1.64
24	110.0	.728	2.03

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:17Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings – Continued.

Dash number M27/342-	Secondary voltage (3-5) (V rms) ±5% (CT)	Secondary current (3-5) (amperes)	Secondary DCR (3-5) (ohms) ±25%
25	123.0	.65	2.35
26	138.0	.58	3.17
27	157.0	.508	3.60
28	175.0	.455	5.50
29	200.0	.400	5.60
30	220.0	.364	8.10
31	26.0	3.080	0.14
32	115.0	.696	2.12

VERIFICATION:

Extent of qualification:

Qualification testing and approval to M27/338-26 and M27/343-30 shall be sufficient to grant qualification approval to MIL-PRF-27/338 through MIL-PRF-27/343 inclusive, all parts.

Qualification testing and approval to M27/342-30 shall be sufficient to grant qualification approval to M27/342-01 through M27/342-32.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-27, this document references the following:

MIL-STD-202-211

Custodians:
Army - CR
Navy - EC
Air force – 85
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Army – AR, CR4
Navy - AS, MC, OS, SH
Air Force - 19, 99

(Project 5950-2017-044)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:17Z
Check the source to verify that this is the current version before use.