NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.


MIL-PRF-27/349B
17 January 1986
SUPERSEDING
MIL-T-27/349A
5 March 1984

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 375 VOLTAMPERES,
3-PHASE, TYPE TF5S03YY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the transformer described herein shall consist of this specification and the latest issue of MIL-T-27.



INCH	mm
.010	0.25
.02	0.5
.090	2.29
.1640	4.165
.20	5.1
.25	6.4
.28	7.1
.40	10.2
1.47	37.3
1.87	47.5
1.94	49.2
2.70	68.6
3.24	82.3
4.45	113.0
4.99	126.8

(For dash numbers 01 through 06)
PRIMARY (For dash nos. 01 thru 06)
WYE, 115 V to Com 1,2,3 Line 4 Com
WYE, 200 V L-L 1,2,3

(For dash numbers 07 through 18)
SECONDARY
WYE, L Com Connect 6-8-10 Load 5-6, 7-6, 9-6
DELTA, L-L Connect 6-7,8-9 5-10 Load 5,7,9
WYE, L-L Connect 6-10, 8-10 Load 5,7,9

PRIMARY (For Dash nos. 07 thru 12)
DELTA, 115 V L-L 1,2,3

PRIMARY (For Dash nos. 13 thru 18)
DELTA, 200 V L-L 1,2,3

CIRCUIT DIAGRAMS

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.04 (1.0 mm).
4. Marking shall be on top and side of case.
5. Terminal 4 is missing for dash nos. 07 thru 18.

FIGURE 1. Dimensions and configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T04:19Z
Check the source to verify that this is the current version before use.

REQUIREMENTS (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings

Primary voltage at 400 ±20 Hz

Wye connected (dash numbers 01 through 06)

(1-4) 115 V ac.

(2-4) 115 V ac

(3-4) 115 V ac.

(1-2) 200 V ac.

(1-3) 200 V ac.

(2-3) 200 V ac.

Delta connected (dash numbers 07 through 12)

(1-2) 115 V ac.

(1-3) 115 V ac

(2-3). 115 V ac.

Delta connected (dash numbers 13 through 18)

(1-2) 200 V ac.

(1-3) 200 V ac.

(2-3) 200 V ac

Secondary voltage See table I

Secondary current See table I

Working voltage 535 volts peak maximum.

Design and construction

Dimensions and configuration See figure 1.

Duty cycle Continuous.

Case Epoxy fiberglass.

Terminals Solderable turret-type.

Height 0.28 ±.040 inch (7.11 ±1.02 mm).

Diameter .090 ±.010 inch (2.29 ±0 25 mm)

Weight 3.8 pounds maximum.

Operating temperature range -55°C to +130°C.

Altitude 70,000 feet maximum.

Terminal strength MIL-STD-202, method 211, test condition A, 5 pounds.

Source: https://assist.dla.mil -- Downloaded: 202610-16T04:19Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage (Secondary connected wye)

At atmospheric pressure (each winding) 1500 V rms.

At barometric pressure (each winding). 670 V rms.

Electrical characteristics:

Rated load. With rated voltage across the primary at 400 Hz, the voltage across each winding of the secondary, wye connected, shall be as specified in table I within ±5 percent at the current specified in table I.

Regulation Shall not exceed 10 percent when computed as follows

$$\frac{\text{Voltage (no load)} - \text{Voltage (rated load)}}{\text{Voltage (rated load)}} \times 100$$

TABLE I. Electrical rating - secondary.

Dash numbers M27/349-	Wye (L-Com) 4 wire 1/ Delta (L-L) 3 wire 2/ (each winding)		Wye (L-L) 3 wire 3/ (each winding)		DC resistance 1/ Wye (L-Com) (each winding)
	Load current		Load current		
	Volts rms	Amperes rms	Volts rms	Amperes rms	Ohms ±25%
01, 07, 13	12	10.42	20.8	6.02	.0118
02, 08, 14	15	8.34	26.0	4.82	.0189
03, 09, 15	20	6.25	34.6	3.61	.0310
04, 10, 16	28	4.47	48.5	2.58	.0648
05, 11, 17	48	2.61	83.1	1.51	.176
06, 12, 18	115	1.09	200	0.63	1.07

1/ Wye, line to common, connect (6-8-10), load (5-6), (7-6), and (9-6).

2/ Delta, line to line, connect (6-7), (8-9), and (5-10) load (5-7-9).

3/ Wye, line to line, connect (6-10), (8-10), load (5-7-9).

Efficiency (at rated load). Shall be a minimum of 90 percent when computed as follows with secondary connected wye, L-Com

$$\frac{\text{(Secondary voltage) (Secondary current)}}{\text{(Primary phase voltage) (Primary phase current)}} \times 100$$

DC resistance (dash numbers 01 through 06)

Primary.

(1-4). 0.85 ohms ±25 percent.

(2-4) 0.85 ohms ±25 percent.

(3-4) 0.85 ohms ±25 percent.

Source: https://assist.dla.mil -- Downloaded: 202610-16T04:19Z
Check the source to verify that this is the current version before use.

DC resistance (dash numbers 07 through 12).

Primary.

(1-4) 0.57 ohms ±25 percent.

(2-4) 0.57 ohms ±25 percent.

(3-4). 0.57 ohms ±25 percent.

DC resistance (dash numbers 13 through 18):

Primary

(1-4) 1.57 onms ±25 percent.

(2-4) 1 57 ohms ±25 percent.

(3-4) 1 57 ohms ±25 percent

Secondary See table I

Temperature rise 50°C with rated voltage and current at 400 Hz, the secondary shall be wye connected at an ambient temperature of 80°C.

Shock (specified pulse) MIL-STD-202, method 213.

Marking location See figure 1.

Part number M27/349-(dash number from table I).

QUALIFICATION DATA

Qualification testing and approval to M27/344-07 and M27/349-18 shall be sufficient to grant qualification approval to MIL-T-27/344 through MIL-T-27/349.

Qualification testing and approval to M27/349-18 shall be sufficient to grant qualification approval to M27/349-01 through M27/349-18.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities.
Army - MI
Navy - OS
Air Force - 11, 17, 99
DLA - ES

User activities
Army - ME
Navy - AS, MC
Air Force - 19

Preparing activity.
Army - ER

Agent.
DLA - ES

(Project 5950-0658-18)

Source: https://assist.dla.mil -- Downloaded: 202640-16T04:19Z
Check the source to verify that this is the current version before use.