INCH-POUND


MIL-DTL-3933/10G
15 August 2011
SUPERSEDING
MIL-DTL-3933/10F
19 November 2009

DETAIL SPECIFICATION SHEET

ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL
COAXIAL LINE (SERIES N),
FREQUENCY RANGE: DC TO 18 GHz, CLASS III, MEDIUM POWER


This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein
shall consist of this specification sheet and MIL-DTL-3933.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses.

FIGURE 1. Dimensions and configuration for PIN M3933/10-1.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses.

FIGURE 2. Dimensions and configuration for PIN M3933/10-2 through M3933/10-22.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:29Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Operating frequency range: DC to 18 gigahertz (GHz) (see table I).

Test frequency range for VSWR and attenuation measurements, measured or recorded, when using an Automatic Network Analyzer (ANA) or equivalent test equipment:

100 MHz (or lower) to	Dash numbers
4 GHz	01 through 05
8 GHz	06 through 10
11 GHz	11 through 15
18 GHz	16 through 22

Basic test frequency for sensitive measurements like connector repeatability, temperature sensitivity, power sensitivity, and any other measurements where a 'delta' specification is imposed:

Basic test frequency	Dash numbers
2 GHz	01 through 05
4 GHz	06 through 10
6 GHz	11 through 15
8 GHz	16 through 22

Operating temperature range:

M3933/10-1: -55°C to +85°C.
M3933/10-2 through -22: -55°C to +125°C.

Maximum weight: 6 ounces.

REQUIREMENTS:

Dimensions and configuration: See figures 1 and 2. Cooling fins shall be circular.

Nominal impedance: 50 ohms.

Attenuation: See table I. Stability and sensitivity:

Maximum attenuation change after:	Up to 10 dB, inclusive (dB)	Over 10 dB (dB/dB)
Temperature change/ thermal shock	0.05	0.005
Vibration or shock	0.1	0.01
Moisture resistance or salt spray	0.2	0.02
Peak power	0.05	0.005

Frequency sensitivity, maximum: 0.1 dB/dB/GHz.
Temperature sensitivity of attenuation, maximum: 0.0004 dB/dB/°C.

Power: See table I.
Power sensitivity for full input power, maximum: 0.005 dB/dB/Watt.

VSWR: See table I.
Connector repeatability, maximum variation in attenuation: 0.02 dB.
Part or Identifying Number (PIN): M3933/10- (and dash number from table I).

Part or Identifying Number (PIN): M3933/10- (and dash number from table I with three device level designators are space level (T), screened (S) and non-screened (N) options)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:29Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics.

Dash number	Attenuation (dB)							Maximum power Input		VSWR maximum 1/					
	Nominal	Deviation													
		DC to 4.0 GHz	DC to 6 GHz	DC to 8 GHz	DC to 11 GHz	DC to 12 GHz	DC to 18.0 GHz	AV (W) at 25°C (continuously)	Peak (kW)	DC to 4.0 GHz	4.0 to 6 GHz	4.0 to 8.0 GHz	6.0 to 11 GHz	8.0 to 12.0 GHz	12.0 to 18.0 GHz
01 N S T	6	±0.2	---	---	---	---	---	15	3 2/	1.30:1	---	---	---	---	---
02 N S T	3	±0.5	---	---	---	---	---	20 4/	1 3/	1.15:1	---	---	---	---	---
03 N S T	10	±0.5	---	---	---	---	---	20 4/	1 3/	1.15:1	---	---	---	---	---
04 N S T	20	±0.5	---	---	---	---	---	20 4/	1 3/	1.15:1	---	---	---	---	---
05 N S T	30	±0.75	---	---	---	---	---	20 4/	1 3/	1.15:1	---	---	---	---	---
06 N S T	3	±0.3	---	±0.6	---	---	---	25 5/	5 2/	1.20:1	---	1.30:1	---	---	---
07 N S T	6	±0.3	---	±0.6	---	---	---	25 5/	5 2/	1.20:1	---	1.30:1	---	---	---
08 N S T	10	±0.3	---	±0.6	---	---	---	25 5/	5 2/	1.20:1	---	1.30:1	---	---	---
09 N S T	20	±0.3	---	±0.6	---	---	---	25 5/	5 2/	1.20:1	---	1.30:1	---	---	---
10 N S T	30	±0.6	---	±1.0	---	---	---	25 5/	5 2/	1.20:1	---	1.30:1	---	---	---
11 N S T	3	±0.35	±0.65	---	±0.75	---	---	20 4/	1 2/	1.15:1	1.20:1	---	1.30:1	---	---

See footnotes at end of table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:29Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics - Continued.

Dash number	Attenuation (dB)							Maximum power Input		VSWR maximum 1/					
	Nominal	Deviation													
		DC to 4.0 GHz	DC to 6 GHz	DC to 8 GHz	DC to 11 GHz	DC to 12 GHz	DC to 18.0 GHz	AV (W) at 25°C (continuously)	Peak (kW)	DC to 4.0 GHz	4.0 to 6 GHz	4.0 to 8.0 GHz	6.0 to 11 GHz	8.0 to 12.0 GHz	12.0 to 18.0 GHz
12 N S T	6	±0.35	±0.65	---	±0.75	---	---	20 4/	1 2/	1.15:1	1.20:1	---	1.30:1	---	---
13 N S T	10	±0.35	±0.65	---	±0.75	---	---	20 4/	1 2/	1.15:1	1.20:1	---	1.30:1	---	---
14 N S T	20	±0.35	±0.65	---	±0.75	---	---	20 4/	1 2/	1.15:1	1.20:1	---	1.30:1	---	---
15 N S T	30	±0.35	±0.65	---	±0.75	---	---	20 4/	1 2/	1.15:1	1.20:1	---	1.35:1	---	---
16 N S T	3	---	---	---	---	---	±0.3	20 5/	1 2/	1.15:1	---	1.20:1	---	1.25:1	1.40:1
17 N S T	6	---	---	---	---	---	±0.3	10 5/	1 2/	1.15:1	---	1.20:1	---	1.25:1	1.40:1
18 N S T	10	---	---	---	---	---	±0.5	10 5/	2 2/	1.15:1	---	1.20:1	---	1.25:1	1.40:1
19 N S T	20	---	---	---	---	---	±0.5	10 5/	2 2/	1.15:1	---	1.20:1	---	1.25:1	1.40:1
20 N S T	30	---	---	---	---	---	±1.0	10 5/	2 2/	1.15:1	---	1.20:1	---	1.25:1	1.40:1
21 N S T	40	---	---	---	---	---	±1.0	10 5/	2 2/	1.15:1	---	1.20:1	---	1.25:1	1.40:1
22 N S T	50	---	---	---	---	---	±1.35	10 5/	2 2/	1.15:1	---	1.20:1	---	1.25:1	1.40:1

1/ VSWR value is for both ends.
2/ Peak power for a duty cycle of 5×10^{-4} maximum duration 5 microseconds.
3/ Peak power for a duty cycle of 1×10^{-3} maximum duration 5 microseconds.
4/ Derate linearly from 20 watts at 25°C to 10 percent at 125°C.
5/ Derate linearly from the stated watts at 25°C to 0 watts at 125°C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:29Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-3933, this specification sheet references the following documents:
MIL-PRF-39012/1
MIL-PRF-39012/2

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA
DLA - CC

Review activities:
Army - MI
Navy - AS, MC, SH
Air Force - 99

Preparing activity:
DLA - CC

(Project 5985-2011-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:29Z
Check the source to verify that this is the current version before use.