INCH-POUND


MIL-DTL-3933/19C
w/AMENDMENT 1
8 January 2014
SUPERSEDING
MIL-DTL-3933/19C
15 August 2011

DETAIL SPECIFICATION SHEET

ATTENUATORS, FIXED, SPACE LEVEL, NON SPACE LEVEL, COAXIAL LINE (BNC CONNECTORS), FREQUENCY RANGE: DC TO 4.5 GHZ, CLASS III, LOW POWER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3933.



NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Metric equivalents are in parentheses.

FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:32Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Operating frequency range: DC to 4.5 GHz.

Test frequency range for SWR and attenuation measurements, measured or recorded, when using an Automatic Network Analyzer (ANA) or equivalent test equipment: 100 MHz (or lower) to 4.5 GHz.

Basic test frequency for sensitive measurements like connector repeatability, temperature sensitivity, power sensitivity and any other measurements where a 'delta' specification is imposed: 2.0 GHz.

Operating temperature range: -55°C to +125°C.

Maximum weight: See table I.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table I.

Nominal impedance: 50 ohms.

Attenuation: See table I. Stability and sensitivity:

Maximum change in attenuation after:	up to 10 dB, inclusive (dB)	over 10 dB (dB/dB)
Temperature change or thermal shock	0.05	0.005
Vibration or shock	0.1	0.01
Moisture resistance or salt spray	0.2	0.02
Peak power	0.05	0.005

Frequency sensitivity, maximum: 0.1dB/dB/GHz.
Temperature sensitivity of attenuation, maximum: 0.0004 dB/dB/°C.

Power rating: See table I.
Power sensitivity for full input power, maximum: 0.005 dB/dB/Watt.

VSWR: See table I.

Connector repeatability, maximum variation in attenuation: 0.02 dB.

Part or Identifying Number (PIN): M3933/19- (and dash number from table I with three device level designators are space level (T), screened (S) and non-screened (N) options).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:32Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics.

Dash number	Attenuation dB		Maximum power input at 25°C		VSWR maximum 1/				Weight (oz) Maximum	Dimension A (inches) Maximum
	Nominal	Deviation DC to 4.5 GHz	AV (W) 2/ (continuously)	Peak (kW) 3/	DC to 1.0 GHz	1.0 to 2.0 GHz	2.0 to 3.0 GHz	3.0 to 4.5 GHz		
01 N S T	1	±0.3	4	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)
02 N S T	2	±0.3	4	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)
03 N S T	3	±0.3	4	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)
04 N S T	4	±0.3	3	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)
05 N S T	5	±0.3	3	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)
06 N S T	6	±0.3	3	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)
07 N S T	8	±0.5	2	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)
08 N S T	10	±0.5	2	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)
09 N S T	11	±0.5	2	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)
10 N S T	12	±0.5	2	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)
11 N S T	15	±0.5	2	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)

See footnotes at end of table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:32Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics - Continued.

Dash number	Attenuation dB		Maximum power input at 25°C		VSWR maximum 1/				Weight (oz) Maximum	Dimension A (inches) Maximum
	Nominal	Deviation DC to 4.5 GHz	AV (W) 2/ (continuously)	Peak (kW) 3/	DC to 1.0 GHz	1.0 to 2.0 GHz	2.0 to 3.0 GHz	3.0 to 4.5 GHz		
12 NST	20	±0.5	2	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)
13 NST	25	±0.9	2	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)
14 NST	30	±0.9	2	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)
15 NST	40	±0.9	2	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	3.0 (76.2)
16 NST	50	±1.2	2	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	3.0 (76.2)
17 NST	60	±1.4	2	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	3.0 (76.2)
18 NST	13	±0.5	2	0.5	1.10:1	1.15:1	1.20:1	1.25:1	4	2.7 (68.6)

1/ VSWR value is for both ends.
2/ Power input is derated linearly to 0.5 watts at +125°C.
3/ Peak power for a duty cycle of 5×10^{-4}; maximum pulse duration of 5 microseconds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:32Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-3933 this specification sheet references the following documents:
MIL-PRF-39012/16
MIL-PRF-39012/17

The margins of this specification sheet are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA
DLA - CC

Review activities:
Army - MI
Navy - AS, MC, SH
Air Force - 99

Preparing activity:
DLA - CC

(Project 5985-2013-045)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:32Z
Check the source to verify that this is the current version before use.