MILITARY SPECIFICATION SHEET

ATTENUATORS, FIXED, MINIATURE, COAXIAL LINE (SMA CONNECTORS),

FREQUENCY RANGE: DC TO 18 GHz, CLASS IV, LOW POWER

This amendment forms a part of MIL-A-3933/25A, dated 24 April 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Delete and substitute as printed above.

PAGE 10

TABLE I, "1/", delete and substitute:

"1/ Power input is derated linearly from +25°C to 0.5 watts at +125°C."

TABLE I, "2/", delete and substitute:

"2/ Peak power for a duty cycle of 5×10^{-4}; maximum pulse duration of 5 microseconds."

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI
Air Force - 11, 99
DLA - ES

User activities:
Navy - AS, MC, SH
Army - AR

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5985-0998-4)

FSC 5985

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Standard https://assist.dla.mil - Downloaded: 2026-10-16T22:83Z
Check the source to verify that this is the current version before use.