
INCH-POUND
MIL-DTL-3933/25C
7 April 2011
SUPERSEDING
MIL-DTL-3933/25B
7 November 2002

DETAIL SPECIFICATION SHEET

ATTENUATORS, FIXED, MINIATURE, SPACE LEVEL, NON SPACE LEVEL, COAXIAL LINE (SMA CONNECTORS), FREQUENCY RANGE: DC TO 18 GHz, CLASS IV, LOW POWER

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3933.



NOTES:

1. Dimensions are in inches.
2. Metric equivalents (in millimeters) are given for general information only.
3. Metric equivalents (in millimeters) are in parentheses.

FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:33Z
Check the source to verify that this is the current version before use.

ENGINEERING DATA:

Operating frequency range: DC to 18 GHz (see table I).

Test frequency ranges for SWR and attenuation measurements, measured or recorded, when using an Automatic Network Analyzer (ANA) or equivalent test equipment:

100 MHz (or lower) to 2.0 GHz for dash numbers 01 through 26.
100 MHz (or lower) to 12.4 GHz for dash numbers 27 through 57.
100 MHz (or lower) to 18 GHz for dash numbers 58 through 95.

Basic test frequencies for sensitive measurements like connector repeatability, temperature sensitivity, power sensitivity and any other measurements where a 'delta' spec is imposed:

1.0 GHz for dash numbers 01 through 26.
6.0 GHz for dash numbers 27 through 57.
8.0 GHz for dash numbers 58 through 95.

Operating temperature range: -55°C to +125°C. Power input is derated linearly to 0.5 watt at +125°C.

Maximum weight: 0.45 ounce.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table I.

Nominal impedance: 50 ohms.

Attenuation: See table I. Stability and sensitivity:

Maximum change in attenuation after:	up to 10 dB, inclusive (dB)	over 10 dB (dB/dB)
temperature change or thermal shock	0.5	0.05
vibration or shock	0.5	0.05
moisture resistance or salt spray	0.5	0.05
peak power	0.5	0.05

Frequency sensitivity, maximum: 0.4 dB/dB/GHz.
Temperature sensitivity of attenuation, maximum: 0.0006 dB/dB/°C.

Input power: See table I.
Power sensitivity for full input power, maximum: 0.005 dB/dB/Watt.

VSWR: See table I.

Connector repeatability, maximum variation in attenuation: 0.04 dB.

Part or Identifying Number (PIN): M3933/25- (and dash number from table I with three device level designators are space level (T), screened (S) and non-screened (N) options).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:33Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics.

Dash number	Attenuation dB						Maximum power input		VSWR maximum 3/					Dimension A (inches) maximum
	Nominal	Deviation (±)					AV (W) 1/ (continuously) at 25°C	Peak (W) 2/	DC to 2.0 GHz	2.0 to 4.0 GHz	4.0 to 8.0 GHz	8.0 to 12.4 GHz	12.4 to 18.0 GHz	
		DC to 2.0 GHz	DC to 4.0 GHz	DC to 8.0 GHz	DC to 12.4 GHz	DC to 18.0 GHz								
01 NST	1	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	0.87 (22.10)
02 NST	2	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	0.87 (22.10)
03 NST	3	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	0.87 (22.10)
04 NST	4	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	0.87 (22.10)
05 NST	5	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	0.87 (22.10)
06 NST	6	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	0.87 (22.10)
07 NST	7	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	0.87 (22.10)
08 NST	8	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	0.87 (22.10)
09 NST	9	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	0.87 (22.10)
10 NST	10	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	0.87 (22.10)
11 NST	11	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	0.87 (22.10)
12 NST	12	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	0.87 (22.10)

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:33Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics - Continued.

Dash number	Attenuation dB						Maximum power input		VSWR maximum 3/					Dimension A (inches) maximum
	Nominal	Deviation (±)					AV (W) 1/ (continuously) at 25°C	Peak (W) 2/	DC to 2.0 GHz	2.0 to 4.0 GHz	4.0 to 8.0 GHz	8.0 to 12.4 GHz	12.4 to 18.0 GHz	
		DC to 2.0 GHz	DC to 4.0 GHz	DC to 8.0 GHz	DC to 12.4 GHz	DC to 18.0 GHz								
13 NST	13	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)
14 NST	14	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)
15 NST	15	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)
16 NST	16	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)
17 NST	17	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)
18 NST	18	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)
19 NST	19	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)
20 NST	20	0.3	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)
21 NST	21	0.5	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)
22 NST	22	0.5	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)
23 NST	23	0.5	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)
24 NST	24	0.5	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:33Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics - Continued.

Dash Number	Attenuation dB						Maximum power input		VSWR maximum 3/					Dimension A (inches) maximum
	Nominal	Deviation (±)					AV (W) 1/ (continuously) at 25°C	Peak (W) 2/	DC to 2.0 GHz	2.0 to 4.0 GHz	4.0 to 8.0 GHz	8.0 to 12.4 GHz	12.4 to 18.0 GHz	
		DC to 2.0 GHz	DC to 4.0 GHz	DC to 8.0 GHz	DC to 12.4 GHz	DC to 18.0 GHz								
25 NST	25	0.5	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)
26 NST	30	0.5	---	---	---	---	2	500	1.15:1	---	---	---	---	1.03 (26.16)
27 NST	1	---	---	---	0.3	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.87 (22.10)
28 NST	2	---	---	---	0.3	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.87 (22.10)
29 NST	3	---	---	---	0.3	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.87 (22.10)
30 NST	4	---	---	---	0.3	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.87 (22.10)
31 NST	5	---	---	---	0.3	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.87 (22.10)
32 NST	6	---	---	---	0.3	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.87 (22.10)
33 NST	7	---	---	---	0.4	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.87 (22.10)
34 NST	8	---	---	---	0.4	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.87 (22.10)
35 NST	9	---	---	---	0.4	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.87 (22.10)
36 NST	10	---	---	---	0.4	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.87 (22.10)

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:33Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics - Continued.

Dash number	Attenuation dB						Maximum power input		VSWR maximum 3/					Dimension A (inches) maximum
	Nominal	Deviation (±)					AV (W) 1/ (continuously) at 25°C	Peak (W) 2/	DC to 2.0 GHz	2.0 to 4.0 GHz	4.0 to 8.0 GHz	8.0 to 12.4 GHz	12.4 to 18.0 GHz	
		DC to 2.0 GHz	DC to 4.0 GHz	DC to 8.0 GHz	DC to 12.4 GHz	DC to 18.0 GHz								
37 NST	11	---	---	---	0.4	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.87 (22.10)
38 NST	12	---	---	---	0.4	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.87 (22.10)
39 NST	13	---	---	---	0.4	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.94 (23.88)
40 NST	14	---	---	---	0.4	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.94 (23.88)
41 NST	15	---	---	---	0.4	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.94 (23.88)
42 NST	16	---	---	---	0.4	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.94 (23.88)
43 NST	17	---	---	---	0.4	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.94 (23.88)
44 NST	18	---	---	---	0.4	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.94 (23.88)
45 NST	19	---	---	---	0.4	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	0.94 (23.88)
46 NST	20	---	---	---	0.7	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	1.04 (26.42)
47 NST	21	---	---	---	0.7	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	1.04 (26.42)
48 NST	22	---	---	---	0.7	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	1.04 (26.42)
49 NST	23	---	---	---	0.7	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	1.04 (26.42)

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:33Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics - Continued.

Dash number	Attenuation dB						Maximum power input		VSWR maximum 3/					Dimension A (inches) maximum
	Nominal	Deviation (±)					AV (W) 1/ (continuously) at 25°C	Peak (W) 2/	DC to 2.0 GHz	2.0 to 4.0 GHz	4.0 to 8.0 GHz	8.0 to 12.4 GHz	12.4 to 18.0 GHz	
		DC to 2.0 GHz	DC to 4.0 GHz	DC to 8.0 GHz	DC to 12.4 GHz	DC to 18.0 GHz								
50 NST	24	---	---	---	0.7	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	1.04 (26.42)
51 NST	25	---	---	---	0.7	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	1.04 (26.42)
52 NST	30	---	---	---	1.0	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	1.04 (26.42)
53 NST	35	---	---	---	1.0	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	1.35 (34.29)
54 NST	40	---	---	---	1.0	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	1.35 (34.29)
55 NST	45	---	---	---	1.5	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	1.35 (34.29)
56 NST	50	---	---	---	2.0	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	1.35 (34.29)
57 NST	60	---	---	---	2.0	---	2	500	1.10:1	1.15:1	1.20:1	1.25:1	---	1.35 (34.29)
58 NST	0	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
59 NST	0.5	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
60 NST	1.0	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
61 NST	1.5	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:33Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics - Continued.

Dash number	Attenuation dB						Maximum power input		VSWR maximum 3/					Dimension A (inches) maximum
	Nominal	Deviation (±)					AV (W) 1/ (continuously) at 25°C	Peak (W) 2/	DC to 2.0 GHz	2.0 to 4.0 GHz	4.0 to 8.0 GHz	8.0 to 12.4 GHz	12.4 to 18.0 GHz	
		DC to 2.0 GHz	DC to 4.0 GHz	DC to 8.0 GHz	DC to 12.4 GHz	DC to 18.0 GHz								
62 NST	2.0	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
63 NST	2.5	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
64 NST	3.0	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
65 NST	3.5	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
66 NST	4.0	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
67 NST	4.5	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
68 NST	5.0	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
69 NST	5.5	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
70 NST	6.0	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
71 NST	6.5	---	---	---	---	0.3	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
72 NST	7.0	---	---	---	---	0.4	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:33Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics - Continued.

Dash number	Attenuation dB						Maximum power input		VSWR maximum 3/					Dimension A (inches) maximum
	Nominal	Deviation (±)					AV (W) 1/ (continuously) at 25°C	Peak (W) 2/	DC to 2.0 GHz	2.0 to 4.0 GHz	4.0 to 8.0 GHz	8.0 to 12.4 GHz	12.4 to 18.0 GHz	
		DC to 2.0 GHz	DC to 4.0 GHz	DC to 8.0 GHz	DC to 12.4 GHz	DC to 18.0 GHz								
73 NST	7.5	---	---	---	---	0.4	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
74 NST	8.0	---	---	---	---	0.4	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
75 NST	8.5	---	---	---	---	0.4	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
76 NST	9.0	---	---	---	---	0.5	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
77 NST	9.5	---	---	---	---	0.5	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
78 NST	10.0	---	---	---	---	0.5	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
79 NST	11.0	---	---	---	---	0.5	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
80 NST	12.0	---	---	---	---	0.5	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.87 (22.10)
81 NST	13.0	---	---	---	---	0.5	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.94 (23.88)
82 NST	14.0	---	---	---	---	0.5	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	0.94 (23.88)
83 NST	15.0	---	---	---	---	0.6	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	1.04 (26.42)
84 NST	16.0	---	---	---	---	0.6	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	1.04 (26.42)

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:33Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics - Continued

Dash number	Attenuation dB						Maximum power input		VSWR maximum 3/					Dimension A (inches) maximum
	Nominal	Deviation (±)					AV (W) 1/ (continuously) at 25°C	Peak (W) 2/	DC to 2.0 GHz	2.0 to 4.0 GHz	4.0 to 8.0 GHz	8.0 to 12.4 GHz	12.4 to 18.0 GHz	
		DC to 2.0 GHz	DC to 4.0 GHz	DC to 8.0 GHz	DC to 12.4 GHz	DC to 18.0 GHz								
85 NST	17.0	---	---	---	---	0.6	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	1.04 (26.42)
86 NST	18.0	---	---	---	---	0.6	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	1.04 (26.42)
87 NST	19.0	---	---	---	---	0.6	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	1.04 (26.42)
88 NST	20.0	---	---	---	---	0.6	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	1.04 (26.42)
89 NST	25.0	---	---	---	---	1.0	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	1.04 (26.42)
90 NST	30.0	---	---	---	---	1.0	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	1.04 (26.42)
91 NST	35.0	---	---	---	---	1.0	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	1.35 (34.29)
92 NST	40.0	---	---	---	---	1.0	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	1.35 (34.29)
93 NST	45.0	---	---	---	---	1.0	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	1.35 (34.29)
94 NST	50.0	---	---	---	---	2.0	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	1.35 (34.29)
95 NST	60.0	---	---	---	---	2.0	2	500	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	1.35 (34.29)

1/ Power input is derated linearly from +25°C to 0.5 watts at +125°C.
2/ Peak power for a duty cycle of 5×10^{-4}; maximum pulse duration of 5 microseconds.
3/ VSWR value is both ends.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:33Z
Check the source to verify that this is the current version before use.

Referenced documents: In addition to MIL-DTL-3933, this document references
MIL-PRF-39012/55
MIL-PRF-39012/57

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Army - MI
Navy - AS, MC, SH
Air Force - 99

Preparing activity.
DLA - CC

(Project 5985-2010-018)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:33Z
Check the source to verify that this is the current version before use.