INCH-POUND

MIL-T-27/11B
9 November 2009
SUPERSEDING
MIL-T-27/11A
6 December 1976

MILITARY SPECIFICATION SHEET

TRANSFORMER, AUDIO FREQUENCY

Inactive for new design
after 25 August 1998

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the transformer described herein shall consist of this specification sheet and MIL-PRF-27.



Inches	mm
.125	3.18
.138	3.51
.219	5.56
.375	9.53
1.125	28.58
1.188	30.18
1.625	41.28
2.375	60.33

FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:10Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance on overall case dimensions is +.000 (0.00 mm) -.063 (1.60 mm).
4. Tolerance on mounting dimensions is +.016 (0.41 mm).
5. Inserts not recommended for new design.
6. Terminal arrangement optional within mounting area indicated.

FIGURE 1. Dimensions and configurations - continued.

REQUIREMENTS: When numbers in parentheses, such as. (1-3), are used, they indicate the winding and the extreme terminals of the winding. When the extreme terminals of two windings are used, (4-7), the windings are connected in series, such as terminals 5 and 6 connected.

Electrical ratings:

Primary power level: .5 W, maximum; .1 W, minimum.

Working voltage (1-3): 525 V, maximum.
(4-5): 175 V, maximum.
(6-7): 175 V, maximum.

Primary current: .020 ampere dc through terminal 2, .001 ampere dc, maximum unbalanced.

Primary impedance (1-3): 60,000 ohms ct.

Design and construction:

Dimensions and configuration: See figure 1.

Material: Metal encased, steel.

Weight: .72 pound, maximum.

Duty cycle: Continuous.

Altitude: 50,000 feet, maximum.

Life expectancy: 10,000 hours, minimum.

Operating temperature range: -55°C to +105°C.

Terminals: Solder terminals, No. 18 AWG.

Height: .375 (9.53 mm) +.000 (0.00 mm) -.188 (4.78 mm).

Terminal strength: MIL-STD-202, method 211, test condition A, 5.0 pounds.

Dielectric withstanding voltage: MIL-STD-202, method 301

At sea level: 1,500 volts rms.

At reduced barometric pressure: 500 volts rms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:10Z
Check the source to verify that this is the current version before use.

Electrical characteristics:

Harmonic distortion: Not more than 1 percent with 173 V, 300 Hz across (1-3) and .020 ampere dc through terminal 2.

No load (center tap voltage unbalance only): With 173 V, 1,000 Hz across (1-3) and .020 ampere dc through terminal 2.

Unbalance (4-5) and (6-7): 1 percent, maximum.
Unbalance (1-2) and (2-3): 1 percent, maximum.

Secondary load impedance: (4-5) – 150 ohms.
(6-7) – 150 ohms ±10 percent.
(4-7) – 600 ohms ct.

Primary impedance: With approximately 10 V, 1,000 Hz across (1-3) and .020 ampere through terminal 2 and 600 ohms ct across (4-7), the primary impedance shall be 60,000 ohms ct ±10 percent across (1-3).
Frequency response:

Range: 300 to 10,000 Hz at rated power, flat within ±2 dB; reference frequency: 1,000 Hz; test voltage 10 V rms (1-3).

Insertion loss: 1.5 dB maximum, with 173 V, input at 1,000 Hz across (1-3).

Resonance: Second resonant frequency = 20,000 Hz, minimum.

Polarity: Additive, with terminals 3 and 4, and 5 and 6 connected.

Temperature rise: 20°C maximum, above an ambient temperature of 85°C, with rated power at 300 Hz.

Vibration, high frequency: MIL-STD-202, method 204, test condition B.

Shock (specified pulse): MIL-STD-202, method 213, test condition I.

Part or Identification Number (PIN): M27/11-01*.

* = See table I for mounting type.

TABLE I. Cross reference.

Mounting	MS90008		M27/11	
	Dash no.	Type designation	Dash no.	Type designation
Studs	-A	TF4RX13AJ005	-01A	TF4R21AJ
Inserts	-B	TF4RX13AJ005	-01B	TF4R21AJ

NOTE: Qualification approval to MIL-T-27/11 shall be sufficient to grant qualification approval to MIL-T-27/3 through MIL-T-27/10.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:10Z
Check the source to verify that this is the current version before use.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Referenced documents. In addition to MIL-PRF-27, this document references the following:

MIL-STD-202.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5950-2009-006)

Review activities:
Army - AR, CR4
Navy - AS, MC
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:10Z
Check the source to verify that this is the current version before use.