MILITARY SPECIFICATION SHEET

FILTER ELEMENT FLUID PRESSURE HYDRAULIC,
AIRCRAFT, DISPOSABLE, 5 MICRON ABSOLUTE

This amendment forms a part of Military Specification Sheet MIL-F-83861/1A(USAF) dated 3 August 1977, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Under REQUIREMENTS make the following changes:

Bubble point. Delete "4.6.1" and "4.7.1.1".

Cold start. Change to read:
"Cold start. The filter element shall withstand 3000 psi differential pressure across the element for the flow cycles and fluid temperature specified in 4.7.3 of general specification."

Element dirt capacity. Under element part number delete "M83861/1" and add "M83861/1-1".

Part number. Delete "MS83861/1" and add "MS83861/1-1".

PAGE 2

Media migration. Delete "4.6.9" and add "4.7.8.3.2".

Part number. Delete "M83861/1" and add "M83861/1-1".

The margins of this amendment are marked with vertical lines to indicate where changes (additions, modification, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the government assumes no liabilty whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Air Force 99

Preparing activity:
Air Force - 71

Project number:
1650 - F112

AMSC N/A

PSC 1650

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:51Z
Check the source to verify that this is the current version before use.
☆U.S. GOVERNMENT PRINTING OFFICE: 1988 — 605-038/40970