WARNING: This material contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Section 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

MIL-T-5486C(AER)
10 DECEMBER 1956
SUPERSEDES
MIL-T-5486B(AER)
1 MARCH 1953

MILITARY SPECIFICATION

TEST SET, MAGNETIC DETECTOR AN/ASM-4

This specification has been approved by the Bureau of Aeronautics, Department of the Navy.

1. SCOPE AND CLASSIFICATION

1.1 Scope - The equipment specified herein shall be a portable test set suitable for bench, preflight, and inflight testing of Detecting Set AN/ASQ-8. It shall be suitable for use in workshops and laboratories ashore and afloat, or in and around aircraft.

1.2 Classification - The equipment covered by this specification shall be of one type and shall consist of the following:

Units	Type Designation	Max. Allow. Size (Inches) W	H	L/D	Max. Allow. Wt. Lbs.	Appl. Par.
Test Set, Magnetic Detector	TS-835/ASM-4	10-1/2	14	8-1/2	18	3.3.1
Cable Assembly, Special Purpose, Electrical	CX-2850/U (8'-0')			96		3.3.2.1
Cable Assembly, Special Purpose, Electrical	CX-2851/U (8'-0")			96		3.3.2.2

2. APPLICABLE DOCUMENTS

2.1 General - The following specifications and drawings of the issue in effect on the date of invitation for bids shall form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-T-152	Treatment, Moisture and Fungus Resistant, of Communications, Electronic, and Associated Electrical Equipment, General Process for
MIL-C-172	Cases; Bases, Mounting; and Mounts, Vibration (For Use with Electronic Equipment in Aircraft)

Source: https://assist.dla.mil -- Downloaded: 20261O-17T04:52Z
Check the source to verify that this is the current version before use.

MIL-P-17555	Preparation for Delivery of Electronic Equipment; Accessories, Auxiliary Equipment, and Associated Repair (Maintenance) Parts
MIL-T-945	Test Equipment, For Use with Electronic Equipments, General Specification
MIL-C-3432	Cable, Flexible, 300 and 600 Volts
MIL-C-5015	Connectors; Electrical, "AN" Type
MIL-I-6181	Interference Limits and Tests; Aircraft Electrical and Electronic Equipment
MIL-E-4682	Electron Tubes (Choice and Application of)
MIL-T-18303	Test Procedures; Preproduction and Inspection, For Aircraft Electronic Equipment; Format for
MIL-N-18307	Nomenclature and Nameplates for Airborne Electronic and Associated Equipment

STANDARDS

MIL-STD-129	Marking for Shipment and Storage

2.2 Availability of Documents:

(1) When requesting specifications and publications refer to both title and number. All requests should be made via the cognizant Inspector of Naval Material or Bureau of Aeronautics Representative.

(2) Copies of this specification and applicable specifications and publications may be obtained upon application to the Commanding Officer, Naval Aviation Supply Depot, Philadelphia 11, Pennsylvania. Attention: Code ODPT.

2.3 Precedence - When the requirements of the contract, this specification, or applicable subsidiary specifications are in conflict, the following precedence shall apply:

(1) Contract - The contract shall have precedence over any specification.

(2) This Specification - This specification shall have precedence over all applicable subsidiary specifications. Any deviation from this specification, or from subsidiary specifications where applicable, shall be specifically approved in writing by the procuring agency.

(3) Referenced Specifications - Any referenced specification shall have precedence over all applicable subsidiary specifications referenced therein. All referenced specifications shall apply to the extent specified.

3. REQUIREMENTS

3.1 Parts and Materials - In the selection of parts and materials, fulfillment of major design objectives shall be the prime consideration. In so doing the following shall govern.

(1) Parts and materials as approved by specification MIL-E-5400 shall be given first consideration.

Source: https://assist.dla.mil -- Downloaded: 202610-17T04:52Z
Check the source to verify that this is the current version before use.

(2) When the contractors can demonstrate that the use of standard AN or JAN parts or materials will not fulfill the design objectives because of size, weight, performance or other reasons, materials and parts shall be used which most nearly meet or exceed the requirements of the respective standard specification. The use of unpotted transformers protected by flexsial, fosterite, permafil or equivalent process will be acceptable. Unpotted transformers must be approved as specified in paragraph 3. 1. 1

(3) When a non-standard part is used, the meeting of general material requirements such as non-inflammability, fungus resistance, non-toxicity, etc., and, the meeting of environmental conditions as required by specification MIL-T-945 shall be of prime consideration.

(4) In the selection of parts, the above considerations shall apply if the assembly is to be built for detail part maintenance. In the event the entire assembly is built to be expended, the assembly shall be constructed and the quality of the individual parts shall be such that the unit as a whole will pass material, electrical and environmental tests. Any assembly built to be expended shall be approved first by the procuring agency.

3. 1. 1 Non-Standard Part Approval and Material Approval - Approval for the use of non-standard parts and materials shall be obtained as outlined in specification MIL-E-5400 except as follows:

(1) Mechanical parts are expected to meet the material requirements of MIL-E-5400, and shall be submitted as non-standard parts only when the material requirements are not met.

(2) Non-standard parts, as defined in specification MIL-E-5400 of an electrical nature must be approved before the preproduction model of the equipment is delivered to the Bureau of Aeronautics. The request for approval must be forwarded by the contractor before the part is purchased or fabricated. In addition to or in lieu of the NON-Standard Part Data Sheet the contractor is requested to submit itemized lists of the parts, their sources, and the contractor's drawing or purchase specification covering the parts.

3. 1. 2 Choice of Tube Types - Electronic tubes used in the equipment shall be chosen in accordance with the following requirements and in the sequence noted:

(1) MIL-E-4682

(2) The use of any tube not meeting the requirements of (1) above must be approved by the Bureau of Aeronautics, however, before consideration for approval, the contractor must submit the following information:

(a) Quantitative data on the electrical advantages and mechanical adequacy of the proposed tube over the most nearly equivalent type on the acceptable listings.

(b) Test data and performance limits of the tube which must be maintained to insure satisfactory and reliable performance in the equipment.

Source: https://assist.dla.mil -- Downloaded: 20260-17T04:52Z
Check the source to verify that this is the current version before use.

(c) Information as to whether the tube manufacturer has received Military or Navy qualification approval for the particular tube.

3.2 General Requirements

3.2.1 General - The equipment shall fulfill all applicable design and performance requirements of specification MIL-T-945 unless otherwise specified herein.

3.2.2 Service Conditions - The performance specified herein shall be obtained under any condition of service conditions as specified in specification MIL-T-945 except that the tolerance limits specified shall apply only to performance during tests conducted with ambient temperatures between -20°C and +40°C and shall be capable of being subjected to the complete environmental tests specified in specification MIL-T-945 with no permanent damage or loss of accuracy.

3.2.3 Form Factor - The equipment shall be in the form of a rectangular solid. The overall dimensions of the equipment, including cover, handles, hinges, etc., shall not be greater than 8-1/2 inches deep, 10-1/2 inches wide, and 18 inches high. The total weight of the equipment, including accessories stowed within the lid of the combination case, shall not exceed 20 pounds.

3.2.4 Case - The equipment shall be furnished in a combination case fulfilling the requirements of specification MIL-T-945. In addition to the requirements of specification MIL-T-945, the case shall be capable of being mounted on a base meeting the requirements of specification MIL-C-172. A 3 inch deep storage space shall be provided in the lid of the combination case for stowing accessories.

3.2.4.1 Handles - The controls, indicators, connectors, etc., mounted on the front panel shall be protected by two guard-rail type handles mounted on either side of the panel. These handles shall be adequate for use in carrying the equipment and no other handles shall be provided for this purpose.

3.2.5 Operating Power - The equipment shall be designed to operate from 28 volts DC and 300 volts DC furnished through an interconnecting cable from Electronic Control Amplifier AM-294/ASQ-8 of Detecting Set AN/ASQ-8. A 1-1/2 volt battery holder to receive 1-1/2 volt BA 56 battery shall be provided and external connections for a 1-1/2 volt battery supply shall be provided.

3.2.6 Overload Protection - Overload protection for the equipment shall be provided in the equipment. All parts and circuits of the equipment which are likely to carry an overload due to any failure or poor adjustments shall have suitable protective devices or shall be proportioned to withstand such overload without permanent damage to the equipment. The use of fuses and other protective devices shall be held to a minimum.

3.2.6.1 Undervoltage Protection - The equipment shall not be damaged by voltages below the minimum specified and shall automatically resume normal operation when the voltage returns within limits.

3.2.7 Operational Stability

3.2.7.1 Electrical Stability - This equipment shall maintain the accuracies and other requirements specified herein for at least 1000 hours without requiring recalibration or readjustment of controls or adjustments other than those accessible through or located on the front panel insofar as the functions of servo gain and orientation adjustments specified herein are concerned. The provision for standard servo tests and standard calibration signals for quantitative measurements of performance are excluded from the requirements of this paragraph and the adjustments and controls exclusively required for these tests need not be located on or accessible through the front panel but must be accessible without removal of the dust cover.

Source: https://assist.dla.mil -- Downloaded: 20260-17T04:52Z
Check the source to verify that this is the current version before use.

3.2.7.2 Mechanical Stability - All controls and adjustments shall be designed so that their position of adjustment will not be altered when the equipment is subjected to the specified service conditions.

3.2.8 Operating Life

3.2.8.1 Reliable Operating Life - The equipment shall have a reliable operating life of at least 1000 hours without removal for bench servicing. Parts requiring servicing or replacement at the end of this interval to renew this service life shall be specified by the manufacturer.

3.2.8.2 Total Operating Life - The equipment shall have a minimum total operating life of 2000 hours with reasonable servicing and replacement of parts. Parts which may require replacement within this interval shall be specified by the manufacturer.

3.2.9 Cables and Connectors - Cables and connectors shall be in accordance with the requirements of specification MIL-T-945. Insofar as practical all front panel connectors shall be mounted along the lower edge of the front panel and in no case shall their location be such that the connecting cables will interfere with the operator.

3.2.10 Controls, Connectors, Adjustments and Indicators - Controls, connectors, adjustments and indicators shall be in accordance with the requirements of specification MIL-T-945 and in addition shall be designed, located and labeled to provide for ease of operation and maintenance. All controls designed for continuous adjustment shall provide smooth electrical performance over the entire range of adjustment and shall have no "critical" points at which they will require special care in setting.

3.2.10.1 Location - All operational controls, connectors, adjustments and indicators shall be located on the front panel except those exclusively required for measuring the performance of the servo and orient system as described in paragraph 3.3. These latter controls shall be accessible through an access panel located on top of the test set.

3.2.10.2 Approval - Prior to fabrication of the first equipment, the contractor shall submit a drawing indicating the proposed location, function and identification of all controls, adjustment, connectors and indicators to the Bureau of Aeronautics for approval.

3.2.11 Interference - The generation of radio interference by the equipment and the vulnerability of the equipment to radio interference shall be controlled within the limits of specification MIL-I-6181.

3.2.12 Moisture and Fungus Resistant Treatment - The equipment shall be moisture and fungus proofed by selection of parts and materials that are non-nutrient for fungus. The parts and materials shall be treated prior to their use in the equipment so that overall spraying of the equipment is not necessary. Overall spraying of the equipment in accordance with specification MIL-T-152 shall be made in the event selection of parts and materials described above is not possible.

3.2.13 Interchangeability - The interchangeability requirements between like assemblies, sub-assemblies, and replaceable parts as specified in specification MIL-T-945 shall be extended to require interchangeability of units of this equipment with the latest model of any previously produced equipment. Such interchangeability shall be measured against a model, manufacturing drawings, or other technical information as provided by the procuring agency for that purpose. In the event that requirements of specification MIL-T-945 conflict with the requirements for interchangeability, the interchangeability requirements shall govern.

3.2.14 Nomenclature and Nameplates - Nomenclature assignment and nameplate approval for equipment identification shall be in accordance with specification MIL-N-18307.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:52Z
Check the source to verify that this is the current version before use.

3.2.15 Marking and Identification - Marking and identification shall be in accordance with the requirements of specification MIL-T-945 and in addition all replaceable subassemblies shall be further identified with the following information, rubber stamped on a fixed surface when available or on a protected tag affixed in such a manner as not to impair operation of the assembly or be easily torn off.

(1) Reference symbol

(2) Name if applicable

(3) P/O Test Set TS-835/ASM-4

(4) Additional information such as ASO stock number, contractor drawing number, etc., when space permits.

3.2.16 Workmanship - The equipment covered by this specification, including all parts and accessories shall be manufactured and finished in accordance with the standards set up in specification MIL-T-945.

3.3 Detail Requirements

3.3.1 Test Set, Magnetic Detector TS-835/ASM-4 - The Test Set, Magnetic Detector TS-835/ASM-4 shall meet the following requirements:

3.3.1.1 Functions - The test set specified herein shall furnish test signals to, and measure signals from Detecting Set AN/ASQ-8 for the purpose of (a) adjusting and (b) measuring the performance of the servo and orient systems of the AN/ASQ-8, Detecting Set.

3.3.1.2 Application - For adjusting the AN/ASQ-8 the equipment shall furnish a sinusoidal low frequency signal successively to the inner and outer axis orienter magnetometers of the Detecting Head DT-37/ASQ-8 and thereafter indicate successively the values of the servo error signal from each axis servo system. This then permits adjustment of the servo gain control to a desired value. Similarly the equipment shall simultaneously furnish two sinusoidal low frequency signals, in quadrature phase, to the inner and outer axis magnetometers of the DT-37/ASQ-8 and thereafter indicate the amplitude of signals from the AM-295/ASQ-8 detector circuits. This then permits adjustment of the inner and outer orientation controls to a desired value. For measuring the performance of the AN/ASQ-8 the equipment shall furnish measured and adjustable sinusoidal low frequency calibration signals successively to the inner and outer axis orienter magnetometers and thereafter accurately measure signals from the servo and orientation circuits to allow a determination of the quantitative performance of the AN/ASQ-8.

3.3.1.3 Contents - The equipment shall include the following functional groups of circuits:

3.3.1.3.1 Signal Generator - The signal generator shall furnish sinusoidal test signals for use in adjusting and measuring the performance of the servo and orientation circuits of the AN/ASQ-8. The signal generator shall furnish signals in accordance with the following requirements:

(1) Output Impedance - The output resistor shall be 100,000 ohms ± 10% unless another value is approved by the Bureau of Aeronautics.

(2) Test Signals - For servo adjustment and measurement, a single servo test signal shall be furnished which can by suitable switching be applied to either the inner or outer axis magnetometers of the AN/ASQ-8. For orientation adjustment and measurement, dual orient test signals having quadrature phase relation shall be furnished simultaneously to the inner and outer axis magnetometers of the AN/ASQ-8.

Source: https://assist.dla.mil -- Downloaded: 202610-17T04:52Z
Check the source to verify that this is the current version before use.

(3) Frequency - The frequency of both servo and orient test signals shall be one cycle per second ± 10% throughout the service conditions specified in paragraph 3.2.2. The harmonics shall be minimized and shall be limited sufficiently to allow use in adjusting the AN/ASQ-8.

(4) Orient Test Signal Level - The dual orient test signal levels from a source with an impedance of 100,000 ohms or more shall be approximately 100 microamperes into a load impedance of approximately 50 ohms with less than 0.1 microampere d-c leakage.

(5) Servo Test Signal Level - The servo test signal level from a source with an impedance of 100,000 ohms or more shall be adjustable from 0 to 400 microamperes into a load impedance of 50 ohms with less than 10 microamperes d-c leakage. For servo adjustments a fixed level of approximately 200 microamperes shall be provided from a source with an impedance of 100,000 ohms or more into an impedance of 50 ohms with less than 10 microamperes d-c leakage.

(6) Frequency Stability - The frequency of test signals shall not change by more than 10% as the service conditions are varied through their specified range.

(7) Switching - Suitable switches and associated circuitry shall be provided to allow servo test signals to be applied successively to the inner and outer axis magnetometers and to apply the dual orient test signals simultaneously to the inner and outer axis magnetometers of the AN/ASQ-8. Such switching shall simultaneously activate and/or inactivate the proper associated servo and/or orient circuits to allow indication and measurement of servo and/or orient signals.

3.3.1.3.2 Servo Circuits - The servo circuits shall provide a means for indicating and measuring the value of servo error signals from the inner and outer axis magnetometer when the servo test signal is applied. The servo circuits shall be in accordance with the following requirements:

(1) Input Impedance - The input impedance shall be a 1 microfarad capacitor in series with a 1 megohm resistor.

(2) Error Signals - The error signals to be measured shall be derived from input signals consisting of alternate positive and negative pulses having an amplitude within the range of 1.2 to 3.2 volts. A repetition rate of 400 pulses per second (i.e. 400 positive plus 400 negative pulses per second or a total of 800 pulses per second) and a duration of 60 microseconds. The error signal to be indicated and measured shall then be the difference of amplitude between the positive and negative pulses.

(3) Indication - The error signal shall be indicated and measured on a suitably calibrated -0.5 milliampere; 0; +0.5 milliampere, 0 centered front panel meter. Negative error signals shall be indicated by a left deflection of the meter pointer. Positive error signals shall be indicated with a right deflection of the meter pointer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:52Z
Check the source to verify that this is the current version before use.

(4) Accuracy of Indication - The overall accuracy of the servo circuits shall be such that the actual and the indicated value of error signal shall not differ by more than 5% of the full scale value of the range being used.

(5) Ranges - Three ranges of sensitivity shall be provided. These ranges shall be LOW, MEDIUM and HIGH. The increase in sensitivity between each range shall be factor of two.

(6) Range Selector - A front panel selector switch (paragraph 3.3.1.3.5(1)) shall allow selection of any one of the three ranges of measurement. In addition a fourth position shall be provided on this switch to turn the measuring circuit off. This selector switch shall be common to the servo and orient circuits.

(7) Meter - The meter used to indicate and measure the servo error signal shall have a full scale accuracy of 3 %. This meter shall be common to the servo and orient circuits.

(8) Stability - After a twenty minute warm-up with a constant value input signal (either servo or orient signal) the indication of signal shall not change in value by more than 5% during any 30 minute period thereafter. This limitation of drift shall be obtained without readjustment of any controls or adjustments.

3.3.1.3.3 Orient Circuits - The orient circuits, in conjunction with the meter of the servo circuits and recorders RD-47/ASQ or RD-47A/ASQ shall provide a means for indicating and measuring the value of signals from the detector circuits of the AN/ASQ-8 when orient test signals are applied to the inner and/or outer magnetometers. The orient circuits shall be in accordance with the following requirements:

(1) Input Impedance - 1 megohm or greater. The exact value shall be determined by the contractor and maintained within this value ±10% in all equipments.

(2) Orient Signals - The signals from the detector circuits of AN/ASQ-8 which are to be indicated shall consist of sinusoidal signals having a frequency of within the range of 0.8 to 1.2 cycles per second and an amplitude within the range of 0 to 500 millivolts.

(3) Indication - The orient signal shall be indicated on a suitably calibrated -0.5 milliampere, 0, +0.5 milliampere, 0 centered front panel meter.

(4) Accuracy of Indication - The overall accuracy of the orient circuits shall be such that the actual and indicated value of orient signals shall not differ by more than 5% of the full scale value of the range being used.

(5) Ranges - Three ranges of sensitivity shall be provided. These ranges shall be LOW, MEDIUM and HIGH. The increase in sensitivity between each range shall be factor two.

(6) Range Selector - A front panel selector switch (paragraph 3.3.7.1) shall allow selection of any of the three ranges of measurement. In addition, a fourth position shall be provided on this selector switch to turn the measuring circuit off. This selector switch shall be common to the servo and orient circuits.

Source: https://assist.dla.mil -- Downloaded: 202610-17T04:52Z
Check the source to verify that this is the currentversion before use.

4.3.1 Individual Test - Each equipment submitted for acceptance shall be subjected to the Individual Test to determine compliance with the requirements of material, workmanship, operational adequacy and reliability. As a minimum each equipment accepted must successfully pass the tests specified in the following paragraph.

4.3.1.1 Scope of Test - As a minimum, each equipment shall be subjected to the following:

(1) *Examination of Product*

(2) Operational Test

(3) Reliability Test

4.3.1.1.1 Examination of Product - Each equipment shall be carefully examined to determine that the requirements for material and workmanship as specified in MIL-T-945 has been met. Also, it shall be determined that approval has been granted for the use of all non-standard parts.

4.3.1.1.2 Operational Test - Each equipment shall be operated. The period of operation shall be long enough to permit the equipment temperature to stabilize and to check sufficient characteristics and record adequate data to assure satisfactory equipment operation.

4.3.1.1.3 Reliability Test - Each equipment shall be operated under the conditions specified below for a period of 12 hours without a failure. A failure shall be defined as anything which causes malfunctioning of the equipment. Only such adjustments shall be permitted which can be made using such controls and adjustments which would normally be accessible during flight.

Temperature	Ambient Room
Humidity	*Ambient Room*
Vibration (15 minute) (Without Isolators)	Any frequency within the range of 20 to 60 cps and an amplitude of ± 5 g's

The fifteen (15) minute vibration run shall be made at the beginning of the 12 hour period. The equipment shall be operating during the vibration run. During the twelve (12) hour period of operation the equipment shall be mechanically cycled periodically through its various phases of operation. Should a failure occur, it shall be repaired and the test started over, except the fifteen (15) minute vibration period need not be repeated when it is certain the failure was not a result of the vibration. Should repetitive failures occur, corrective action must be taken to eliminate this defect from future equipment. A record shall be kept of all failures.

4.3.2 Sampling Test - Sampling Tests shall be conducted on a quantity of equipment as specified in the following paragraph. Equipments selected must first have passed all of the individual tests. Sampling Tests shall be conducted on complete equipments.

4.3.2.1 Sampling Test Schedule - Sampling Tests shall be performed on the following quantity of equipment. Selection of equipment for tests shall be under the supervision of the naval inspector.

Source: https://assist.dla.mil -- Downloaded: 202640-17T04:52Z
Check the source to verify that this is the current version before use.

Quantity Delivered for Acceptance	Quantity to be tested
From the first 10	1
From 11 to 100	2
From 101 to 200	1
From 200 and above	1 for each additional 200 or fraction thereof

4.3.2.2. Scope of Test - As a minimum each equipment selected for Sampling Test shall be subject to the tests specified below.

Tests	
I	Conduct a complete operational test at ambient room conditions and nominal input voltages, making all necessary measurements to assure all applicable specification requirements have been met.
II	Repeat the above using the highest and lowest specified input voltages and frequencies.
III	Conduct the reliability test specified in paragraph 4.3.1.1.3 except the test duration shall be 50 hours and two failures shall be permitted.

4.3.3 Special Test - Special Tests shall be conducted for the purpose of checking the effect of any design or material change on the performance of the equipment and to assure adequate quality control. Equipment selected for Special Test may be selected from equipment previously subjected to the Sampling Test.

4.3.3.1 Special Test Schedule - In selecting equipment for Special Tests the following schedule shall be followed:

(1) An early production equipment.

(2) An equipment midway of the production run.

(3) An early equipment after an engineering change.

(4) Whenever failure reports or other information indicate additional tests are necessary.

Exceptions from the above may be necessary when the number of equipments procured under contract or other factors affecting performance may require a variation to assure satisfactory quality control.

Source: https://assist.dla.mil -- Downloaded: 202640-17T04:52Z
Check the source to verify that this is the current version before use.

4.3.3.2 Scope of Test - In conducting Special Tests, test procedures previously approved for the Preproduction and Sampling Tests shall be used where applicable. When not applicable the contractor shall prepare a test procedure and submit to the Bureau of Aeronautics for approval prior to conducting the tests. As a minimum the following tests shall be made, except that for those equipments selected as a result of design changes and failure reports only such tests required to check the characteristics in question need be conducted.

(1) Temperature - Altitude Tests

(2) Vibration Test (90 minutes cycling - 30 min. in each of 3 planes - Freq 5 to 500 cps ± 5g)

(3) Humidity Tests

4.3.4 Equipment Failure - Should a failure occur during either the Sampling or Special Test, the following corrective action shall be taken.

(1) Determine the cause of failure.

(2) Determine if the failure is an isolated case or design defect.

(3) If a design defect, suggest corrective action for Bureau of Aeronautics approval.

(4) Where practical, include a test in the Individual Test to check all equipments for this requirement until reasonable assurance is obtained that the defect has been satisfactorily corrected.

4.4 Test Procedures - The procedures used for conducting Preproduction Tests, and Acceptance Tests shall be prepared by the contractor and sent to the Bureau of Aeronautics for approval. The right is reserved by the Bureau of Aeronautics or the Naval Inspector to modify the tests or require any additional tests deemed necessary to determine compliance with the requirements of this specification or the contract. Specification MIL-T-18303 shall be used as a guide for preparation of test procedures. When approved procedures are available from previous contracts the Bureau of Aeronautics will furnish the procedures to be used for testing.

4.5 Pre-Submission Testing - No item, part or complete equipment shall be submitted by the contractor until it has been previously tested and inspected by the contractor and found to comply, to the best of his knowledge and belief, with all applicable requirements. The design data submitted by the contractor for the preproduction model shall indicate its physical and electrical characteristics and other necessary test data which will establish that the equipment meets all the requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 202640-17T04:52Z
Check the source to verify that this is the current version before use.

4.6 Rejection and Retest - Electronic equipment which has been rejected may be reworked or have parts replaced to correct the defects and resubmitted for acceptance. Before resubmitting, full particulars concerning previous rejection and the action taken to correct the defects found in the original shall be furnished the Inspector. Units rejected after retest shall not be resubmitted without the specific approval of the procuring agency.

4.7 Equipment Changes - After approval of the preproduction model no changes shall be incorporated in the equipment unless approved by the Bureau of Aeronautics. To obtain Bureau of Aeronautics approval the contractor shall submit an Engineering Change Proposal (ECP) giving the necessary information concerning the change. This applies for either a Bureau of Aeronautics' recommended change or a contractor's proposed change. When required the contractor shall also prepare an Electronic Material Change (EMC) and an Electronic Material Bulletin (EMB) to cover the approved change. ECP's, EMC's and EMB's shall be prepared in accordance with the requirements of SAR-300.

5. PREPARATION FOR DELIVERY

5.1 General - All major units and parts of the equipment shall be packaged, packed and marked for shipment in accordance with the requirements of Specifications MIL-P-17555 and MIL-STD-129. Suitable interior packing or blocking and bracing shall be used to prevent shifting in the exterior shipping container and shock from handling in transit.

6. NOTES

6.1 Ordering Information - Invitation for bids and contracts or orders shall specify the title, number, and date of this specification.

PATENT NOTICE - When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T04:52Z
Check the source to verify that this is the current version before use.