|INCH-POUND|
MIL-M-28787/316A
AMENDMENT 1
17 June 1992

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

MEMORY, READ ONLY, DIGITAL

This amendment forms a part of Military Specification MIL-M-28787/316A(EC), dated 20 January 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I: Delete and substitute new table I as printed on page 2 of this amendment.

PAGE 36

TABLE XII, Test conditions K11, K12, K15, and K16, Min column: Delete "0" (four places) and subsititute "-10" (four places).

Custodians:
Army - ER
Navy - SH
Air Force - 85

Preparing activity:
Navy - NW

(Project 5963-0242)

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

AMSC N/A FSC 5963
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T17:41Z
Check the source to verify that this is the current version before use.

TABLE I. Module electrical requirements.

Test cond	Parameter	Ref test table	Test type 1/-3/	25°C ± 5°C 4/		Class I 4/				Class II 4/				Unit
						0°C ± 5°C		60°C ± 5°C		-55°C ± 5°C		85°C ± 5°C		
				Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
A1	Isolation Initial	III	S	10	INF	10	INF	10	INF	10	INF	10	INF	Mohm
	End-of-life	III	S	1	INF	1	INF	1	INF	1	INF	1	INF	Mohm
A2-A5	Isolation, used to unused pins													
	Initial	III	S	10	INF	10	INF	10	INF	10	INF	10	INF	Mohm
	End-of-life	III	S	1	INF	1	INF	1	INF	1	INF	1	INF	Mohm
B	Vcc stress test	IV	S	----------		----------		Must pass remaining tests		----------		----------		
C1-C10	Input breakdown current	V	S	0	2	0	2	0	2	0	2	0	2	mA
C11-C18	Input breakdown current	V	S	0	1	0	1	0	1	0	1	0	1	mA
D1-D16	Output short circuit current	VI	X	-15	-100	-15	-100	-15	-100	-15	-100	-15	-100	mA
E1-E16	Output leakage current, low level	VII	X	-100	100	-100	100	-100	100	-100	100	-100	100	uA
F1-F16	Output leakage current, high level	VIII	X	-100	100	-100	100	-100	100	-100	100	-100	100	uA
G1-G18	Input clamp diode voltage	IX	X	-0.4	-1.2	-0.4	-1.2	-0.4	-1.2	-0.4	-1.2	-0.4	-1.2	V
H1-H16	Output voltage, low level	X	X	0.0	0.5	0.0	0.5	0.0	0.5	0.0	0.5	0.0	0.5	V
J1-J16	Output voltage, high level	XI	X	2.4	4.5	2.4	4.5	2.4	4.5	2.4	4.5	2.4	4.5	V
K1-K10	Input current, high level	XII	X	0	100	0	100	0	100	0	100	0	100	uA
K11,K12	Input current, high level	XII	X	-10	50	-10	50	-10	50	-10	50	-10	50	uA
K13,K14	Input current, high level	XII	X	0	50	0	50	0	50	0	50	0	50	uA
K15,K16	Input current, high level	XII	X	-10	50	-10	50	-10	50	-10	50	-10	50	uA
K17,K18	Input current, high level	XII	X	0	50	0	50	0	50	0	50	0	50	uA
L1-L10	Input current, low level	XIII	X	0	-350	0	-350	0	-350	0	-350	0	-350	uA
L11-L18	Input current, low level	XIII	X	0	-275	0	-275	0	-275	0	-275	0	-275	uA
M	Power supply current	XIV	X	10	370	10	370	10	370	10	370	10	370	mA

- See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-02-20T17:41Z
Check the source to verify that this is the current version before use.