MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC
RESISTOR, ANALOG, KEY CODE GRB

This amendment forms a part of Military Specification MIL-M-28787/318A(EC), dated 5 August 1982, and is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

FIGURE 1, NOTE 2, delete and substitute:

"2. R1-R17 = 1.0 kΩ ±1%".

PAGE 5

6.4, delete and substitute:

"6.4 Module description. The following electrical parameters reflect the 0°C to 60°C and -55°C to 85°C end-of-life limits from table I.

	Class I	Class II	Unit
Maximum power dissipation	2.5	2.5	W
Maximum power dissipation per resistor (17)	0.25	0.125	W

"

PAGE 7

FIGURE 2, ITEM P01 block: Delete "10V ±1%" and substitute "11.2 V ±1%".

Agent:
DLA - ES

Preparing activity"
Navy - EC

(Project 5963-N440)

FSC 5963

* U.S. GOVERNMENT PRINTING OFFICE: 1982 - 605-084/177

Source: https://assist.dla.mil - Downloaded: 2026-10-20T17:42Z
Check the source to verify that this is the current version before use.